MIL-N-44334
22 April 1988
SUPERSEDING
N-N-002182A(Army-GL)
30 April 1986

MILITARY SPECIFICATION

NOODLES, BUTTERED, THERMOSTABILIZED, TRAY PACK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers buttered noodles thermostabilized in tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

TT-C-495	- Coatings, Exterior, for Tinned Food Cans
PPP-B-636	- Boxes, Shipping, Fiberboard

PN

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:31Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit; Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-900 - Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks and Sugars Used in the Preparation of Thermostabilized Foods for the Armed Forces

(Copies of specifications, standards, and handbooks required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Copies may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

U.S. Standards for Condition of Food Containers

(Copies may be obtained from the Chairman, Condition of Food Container Committee, Agricultural Marketing Service, U.S. Department of Agriculture, Room 0610, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

U.S. Standards for Grades of Butter

(Copies may be obtained from the Chief, Dairy Standardization Section, Dairy Division, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2750, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:31Z
Check the source to verify that this is the current version before use.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Copies may be obtained from the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Copies should be obtained from the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Copies should be obtained from the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Copies should be obtained from the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3330 - Peel Adhesion of Pressure-sensitive Tape

(Copies should be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:31Z
Check the source to verify that this is the current version before use.

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.4, 6.1, and 6.3).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Noodles, egg (fettuccini), enriched. The egg noodles shall meet the FDA Standard of Identity for Enriched Egg Noodles. The egg noodles shall be dried with no checking or cracking. The egg noodles shall have the following dimensions:

Length	-	4 inches $\pm$ 1/2 inch
Width	-	1/4 inch $\pm$ 1/16 inch
Thickness	-	0.040 inch $\pm$ 0.003 inch

The egg noodles shall conform to the following analytical requirements and shall comply with bacterial standards specified in MIL-STD-900.

Moisture	-	Not greater than 12.00 percent
Ash	-	Not greater than 0.98 percent (moisture-free basis)
Protein	-	Not less than 13.00 percent (moisture-free basis)
Egg solids	-	Not less than 5.50 percent by weight
Lipid phosphorus	-	Not less than 0.136 percent if prepared with egg yolk solids; not less than 0.101 percent if prepared with the whole eggs

3.2.2 Water. Water used for formulation, ice making, and washing shall conform to the National Primary Drinking Water Regulations.

3.2.3 Butter. Butter shall be lightly salted and the minimum grade shall be U.S. Grade A as defined in the U.S. Standards for Grades of Butter.

3.2.4 Starch, waxy maize, modified. The starch shall be white odorless, finely pulverized, modified waxy maize starch for use in canned foods. The modified starch shall demonstrate initial viscosity development in the temperature range 140° to 170°F and be fully hydrated at common retort

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:31Z
Check the source to verify that this is the current version before use.

temperature. The starch shall resist breakdown at low pH, under shear stress, and under conditions of cold storage. The starch shall be bland with essentially no cereal or starchy taste and shall comply with MIL-STD-900.

3.2.5 Salt. Salt shall be noniodized, clear, white, refined, sodium chloride with or without anticaking agents and shall comply with purity standards for sodium chloride of the Food Chemicals Codex.

3.2.6 Monosodium glutamate (MSG). Monosodium glutamate shall comply with the Food Chemicals Codex.

3.2.7 Sugar. Sugar shall be clean, refined, sucrose, granulated, cane or beet, or a combination of both and shall comply with MIL-STD-900.

3.2.8 Lecithin. Lecithin shall comply with the Food Chemicals Codex.

3.2.9 Color, annatto, dry. The annatto color shall be a reddish orange water soluble powder of the extractive of Annatto bixa arellana. The powder shall contain less than 5 percent moisture. One hundred percent shall pass through a U.S. No. 10 Standard sieve and shall be free from hard lumps. The total color (as percent Norbixin) shall be 15.0 $\pm$ 1 percent.

3.3 Preparation and processing. Processing shall be on a continuous basis.

3.3.1 Noodle preparation. The dry noodles shall be blanched in boiling water until the noodle weight approximately doubles (100 $\pm$ 3 percent). The noodles shall be immediately cooled to less than 90°F and rinsed to remove excess starch. The noodles shall be placed in trays within 2 hours after blanching has been accomplished.

3.3.2 Sauce preparation. The sauce shall be formulated and prepared as follows:

Ingredient	Percent
Water	88.65
Butter	7.00
Starch	2.00
Salt 1/	1.50
Sugar	0.60
Lecithin	0.243
Annatto, dry	0.007
	100.00

a. Add butter and approximately 80 percent of the water to the processing vessel. Heat to 180°F.

b. Add salt, sugar, and lecithin. Simmer until all ingredients are in the fluid state.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:31Z
Check the source to verify that this is the current version before use.

c. Prepare a starch slurry using the reserved water and add slowly with constant agitation.

d. Heat entire contents to 180°F and hold for 5 minutes.

e. Add color and blend until color of sauce is uniform.

f. Adjust formula volume with water to compensate for evaporation losses.

g. The sauce shall be placed in tray pack cans within 3 hours after the heating at 180°F is completed. The temperature of the sauce shall not fall below 150°F at any time prior to filling into tray pack cans.

1/ The total amount of salt in the sauce shall be adjusted as necessary to produce a product that complies with the finished product salt requirements (see 3.6).

3.4 Tray pack filling and sealing. Each tray pack can shall be filled with product so as to conform to the finished product requirements and to the following requirements:

a. Each tray pack can shall be filled with 42 ± 1 ounces of blanched noodles and filled with sauce to not less than 106 ounces.

NOTE: The noodles and sauce may be filled in any order which will ensure compliance with finished product requirements.

b. The temperature of the sauce at filling shall be not less than 150°F.

c. Each can shall be hermetically sealed under a vacuum established by a processing authority and specified in the scheduled process so as to assure compliance with the finished product requirement (see 3.6j).

d. The filled and sealed cans shall be in the retort process within 2 hours after sealing.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized in a stationary retort at 240°F or below or alternatively at 260°F in a rotary type retort with rapid rotation (approximately 24 rpm). Under both methods, the tray pack cans shall be thermostabilized until a sterilization value (F_o) of not less than 6 has been achieved. The filled and sealed thermoprocessed tray pack cans shall show no evidence of can swelling when tested for sterility as specified in 4.5.3.4.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, dirt, insects, insect parts, hair, wood, paper, paint, glass, or metal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:31Z
Check the source to verify that this is the current version before use.

b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour, rancid, musty, or moldy.

c. There shall be no color foreign to the product.

d. No individual tray pack shall have a salt content greater than 1.5 percent or less than 0.5 percent.

e. No individual can shall have a net weight of less than 104 ounces.

f. The average net weight shall be not less than 106 ounces.

g. The noodles shall be distinct strips which readily separate.

h. Noodles shall be tender but not mushy or hard.

i. Noodles shall be a uniform light yellow color.

j. Filled, sealed, and retorted cans shall show evidence of proper vacuum as determined by concavity of the can lid (see 4.5.6).

k. The product shall show no evidence of excessive heating (materially darkened or scorched).

3.6.1 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The product shall be prepared, processed, and packaged in establishments meeting the requirements of Title 21, Code of Federal Regulations, Part 110, "Current Good Manufacturing Practice in Manufacturing, Processing, Packaging or Holding of Human Foods," and the plant sanitation requirements of the appropriate Government inspection agency.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all the requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection necessary to assure compliance with the requirements of this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:31Z
Check the source to verify that this is the current version before use.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this document and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this document or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to any identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

4.5.3.1 Net weight inspection. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty

Source: https://assist.dla.mil -- Downloaded: 202640-22T01:31Z
Check the source to verify that this is the currentversion before use.

tray pack cans and lids used in preparing the product and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average net weight is less than 106 ounces or if the net weight of any individual can is less than 104 ounces, the lot shall be rejected.

4.5.3.2 Product inspection. The sample size shall be as indicated by the double sampling plan specified in table I. The tray pack cans shall be selected at random from the lot. The tray pack cans shall be heated for 35 minutes in boiling water, opened, and inspected for the defects listed in table II.

TABLE I. Double sampling plan inspection 1/

Lot size (cans)	Sample size (cans)	Cumulative sample	Acceptance number	Rejection number
0 to 3,200	8	-	0	2
	8	16	1	2
3,201 to 35,000	13	-	0	3
	13	26	3	4

1/ a. If no defects are found in the first sample, the lot shall be accepted.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:31Z
Check the source to verify that this is the current version before use.

TABLE II. Product defects 1/ 2/

Category	Defect
Major	
101	Noodles not distinct strips
102	Noodles not readily separated
103	Noodles hard
104	Noodles mushy
105	Noodle color not typical light yellow noodle color
106	Color not uniform
107	Product shows evidence of excessive heating (materially darkened or scorched)

1/ The presence of foreign material (e.g., glass, dirt, insects, insect parts, hair, paper, paint, wood, metal), foreign odor or flavor (e.g. burnt, scorched, moldy, rancid, musty, sour, stale), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance shall be cause for rejection of the lot. (This comparision shall be performed only when deemed necessary by an Agricultural Marketing Service (AMS) agent.)

4.5.3.3 Salt content testing. Nine tray packs shall be selected at random from the lot and distributed as follows:

- Three for laboratory analysis.
- Three for submission to the contractor.
- Three for retention by an AMS agent as reserve samples.

The three tray packs for laboratory analysis shall be individually tested for salt content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists. Preparation of the sample shall be as follows. The cans shall be opened and the entire contents of each can shall be separately blended in a Waring blender or equivalent. If the salt content of any individual tray pack is less than 0.5 percent or more than 1.5 percent, it is a major defect and the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:31Z
Check the source to verify that this is the current version before use.

Analysis of reserve samples at the request of the contractor shall not be permitted unless the original laboratory analysis indicated that the involved lot will be rejected because of noncompliance with the salt content requirement. When the reserve samples are analyzed, the analysis for salt shall be made and will be considered final. Unused reserve samples shall be returned to the contractor for inclusion in subsequent lots.

4.5.3.4 Commercial sterility testing. The sample size shall be one filled, sealed, and thermoprocessed tray pack can selected from each retort batch in the lot. The sample cans shall be tested for sterility by incubating the cans at 95 ± 5°F for 10 days. Any evidence of can swelling shall be considered a critical defect and shall be cause for rejection of the lot.

4.5.4 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the United States Standards for Condition of Food Containers, except that inspection for labeling shall be as specified in 4.5.4.1.

4.5.4.1 Can label examination. Labels shall be examined for defects in accordance with MIL-L-1497 (see 5.4), except that for self-adhering labels the following additional defects shall apply:

Major: Label torn or scratched so as to obliterate any of the markings.

Minor: Air bubbles under label.
Label not properly adhered to can, i.e., label raised or peeled back from edges or corners.

4.5.4.2 Label adhesive examination. Pressure-sensitive adhesive shall require no preparation prior to application. Labels shall tack quickly and adhere without curling or breaking. The adhesive shall have a minimum adhesion of 60 oz per inch width when tested in accordance with ASTM D 3330.

4.5.5 Can closure examination. Can closures shall be examined visually and by teardowns in accordance with 21 CFR, Part 113, Subpart D, and the can manufacturer's requirements. Any nonconformance based on observation of can seam teardowns or on record of can seam teardowns is a major defect and shall be cause for rejection of any involved product.

4.5.6 Vacuum examination. Cans shall be allowed to cool to 75° ± 5°F, held for at least 24 hours after sealing, and than examined for vacuum retention. To examine, lay a straight edge in the center of the lid along the length of the tray pack. Both ends of the straight edge shall touch the lid at the inside edge of the double seam. There shall be a visible gap between the straight edge and the lid for the entire distance of the label panel. Using a shorter straight edge, the same procedure shall be used across the width, in the center of the tray pack can. When examining a ribbed lid, only lay the straight edge between the two center ribs along the length of the can. The inspection lot shall include only tray packs produced in a single shift on a single sealing machine. The sample size shall be 50 cans. Any nonconformance is a major defect and shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:31Z
Check the source to verify that this is the current version before use.

4.5.7 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as indicated:

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
Reinforced with other than nonmetallic strapping or tape.
Dimensions of pads not as specified.
Interior packing with fiberboard liner or pads not as specified.

Minor: Other required markings missing, incorrect, or illegible.
Arrangement or number of cans not as specified.

4.5.8 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A or C, as specified (see 6.1).

5.1.1 Level A. A size 1001 by 1206 by 200 tray pack can shall be filled with 106 ounces of the food product, sealed, and thermoprocessed as specified in 3.4 and 3.5. The base plate of the can shall be electrolytic chromium-coated steel and shall be of sufficient temper to protect the product during shipment and storage. The base plate weight of the body and end of each can shall be 90 pounds per base box. The entire inside area of the can shall be coated. Scratches or fractures shall not penetrate through the interior can coating. The interior can coating shall not peel or blister when in contact with the product. The interior can coating shall neither affect nor be affected by the packaged product. A certificate of conformance shall be furnished to certify compliance with the interior can coating requirements. The can shall be coated overall on the outside with a coating conforming to type I of TT-C-495.

5.1.1.1 When specified (see 6.1), the base plate of the can shall be electrolytic chromium-coated steel and shall be of sufficient temper to protect the product during shipment and storage. The base plate weight of the body and end of each can shall be 98 pounds per base box. The body design shall be reinforced on the bottom with six longitudinal beads or ribs 0.050 $\pm$ 0.010 inch deep. The beads shall be 9 inches by 3/4 inch in length and width and shall be equidistant in the center panel of the bottom. The end design shall be reinforced with eight longitudinal beads 0.018 $\pm$ 0.004 inch deep. The beads shall be 11 inches by 3/4 inch in length and width and shall be equidistant in the center panel of the end. The center four beads on the end design shall be interrupted to provide a 5-inch by 5-inch flat center panel for labeling. The apex of all these beads shall be outward. The interior and exterior can coating requirements shall be as specified in 5.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:31Z
Check the source to verify that this is the current version before use.

5.1.2 Level C. The product shall be preserved as specified in 5.1.1, except that cans with commercial exterior coating will be acceptable.

5.2 Packing. The product shall be packed in accordance with level A, B, or C as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L or HSC-L with an HSC full depth cover, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads fabricated of grade V3c fiberboard. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pads dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box. Each box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament-reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1) except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

* 5.2.3 Level C packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of the same material as the box.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:31Z
Check the source to verify that this is the current version before use.

5.4 Labeling. Each package shall be labeled in accordance with MIL-L-1497 and with the following:

- Official establishment number (e.g., est 38) or a three letter code identifying the establishment.
- Lot number 1/
- Production shift number 1/
- Retort identification number 1/
- Retort cook number 1/

1/ The lot number shall be expressed as a four digit Julian code. The first digit shall indicate the year of production and the next three digits shall indicate the day of the year (Example, March 19, 1987, would be coded as 7078). The Julian code shall represent the day the product was packaged and processed. Sub-lotting (when used) shall be represented by an alpha character immediately following the four digit Julian code. Following the four-digit Julian code and the alpha character (when used), the other required code information shall be printed in the sequence as listed above.

Alternatively, a preprinted, self-adhering, 0.002-inch thick, clear polyester label printed with indelible black ink may be used. Self-adhering labels shall be applied after retorting. Pressure-sensitive adhesive shall require no preparation prior to application. Labels shall tack quickly and adhere without curling or breaking. The adhesive shall have a minimum adhesion of 60 ounces per inch width when examined as specified in 4.5.4.2.

In addition, the name of the product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined as specified in 4.5.4 after preparation of the product in accordance with heating instructions. Paper labels are not permitted. Cans shall show the following statements:

TO HEAT: Submerge unopened can in boiling water. Simmer gently for 40 to 45 minutes. Avoid overheating (can shows evidence of bulging).

CAUTION: Use care when opening as pressure may have been generated within the can.

To heat in oven: Either punch several holes in lid of can or open can in usual manner leaving the loose lid in place. Place in a 350°F oven for approximately 35 to 40 minutes.

WARNING: Do not place unopened can in oven. This may cause the can to burst.

YIELD

Serves 18 portions of 2/3 cup each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:31Z
Check the source to verify that this is the current version before use.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, when tray pack cans are fabricated from 90 pounds per base box, the following precautionary marking in capital letters larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE, UNLESS PALLET RACKS ARE USED

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1, 4.4, and 6.3).
c. Provisions for approved preproduction samples (see 3.6.1 and 6.3).
d. Level of preservation and packing required (see 5.1 and 5.2).
e. When tray pack cans are to be fabricated from 98 pounds per base box (see 5.1.1.1).
f. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling, and storage of the specified item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.4 Subject term (key word) listing.

Canned foods
Combat field feeding
Noodles, buttered
Thermostabilized
Tray pack

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:31Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Review activities:

Army - MD, TS
Navy - MC
DP - SS

Preparing activity:

Army - GL

Project No. 8940-0608

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:31Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US Army Natick Research, Development, and
Engineering Center
Natick, MA 01760-5014

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research, Development,
and Engineering Center
ATTN: STRNC-ES
Box 14A
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:31Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-N-44334	Noodles, Buttered, Thermostabilized, Tray Pack

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:31Z
Check the source to verify that this is the current version before use.