MIL-O-44327
4 March 1988
SUPERSEDING
C-E-002187A(Army-GL)
26 September 1985

MILITARY SPECIFICATION

OMELET WITH HAM, ARTIFICIALLY COLORED, THERMOSTABILIZED, TRAY PACK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers omelet with ham, thermostabilized in tray pack cans for use by the Department of Defense as a component of operation rations.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issue of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

TT-C-495	-	Coatings, Exterior, For Tinned Food Cans
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-L-1497	-	Labeling of Metal Cans for Subsistence Items
MIL-L-35078	-	Loads, Unit; Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-900 - Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks, and Sugars Used in the Preparation of Thermostabilized Foods for the Armed Forces

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.2 Other Government documents. The following other Government documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

United States Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Food Safety and Inspection Service, Canning of Meat and Poultry Products (9 CFR Part 318)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

Regulations Governing the Inspection of Eggs and Egg Products (7 CFR Part 59)

(Application for copies should be addressed to the Director, Poultry Division, AMS, U.S. Department of Agriculture, Washington, DC 20250.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Application for copies should be addressed to the Office of Drinking Water Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Application for copies should be addressed to the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3330 - Peel Adhesion of Pressure-sensitive Tape

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.4, 6.1, and 6.3).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent and insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Eggs, whole, liquid or frozen. Whole eggs may be liquid or frozen and shall have been processed in accordance with the Regulations Governing the Inspection of Eggs and Egg Products (7 CFR Part 59). The whole eggs shall be egg whites and egg yolks in their natural proportions as broken directly from the shell as evidenced by a USDA Egg Products Inspection Certificate. For liquid whole eggs, the certificate shall state the date and time of pasteurization. Liquid whole eggs shall be held at a temperature of 40°F or lower and shall be held for not more than 72 hours from the time of pasteurization until the start of formulation of the product in which they are used. Frozen whole eggs shall be held at 10°F or lower and used within 120 days. The whole eggs shall be in excellent condition, i.e., free from objectionable odors, such as musty, sour, or fruity.

3.2.2 Ham, canned or cooked. The ham shall be high commercial quality. The ham shall not be labeled "water added", and shall not contain dextrose. The canned or cooked ham shall be maintained in the temperature range of 28° to 40°F for a period of time not to exceed 60 days from date of pack until preparation of the finished product.

3.2.3 Water. Water used for formulation, ice-making, and washing shall conform to the National Primary Drinking Water Regulations.

3.2.4 Oil, vegetable. Vegetable oil shall possess a clean, bland flavor and shall have a minimum stability of 15 hours (A.O.M.), a free fatty acid value not to exceed 0.05 percent, and a moisture/volatile matter content not to exceed 0.06 percent and shall pass a cold test of 5.5 hours (minimum).

3.2.5 Starch, instant (for eggs), waxy maize, modified, pregelatinized. The starch shall be pure off-white and odorless, finely ground powder. The starch shall be modified, pregelatinized, cross linked and stabilized. The starch shall be resistant to breakdown under high temperature conditions, shall possess good low temperature stability, and shall not set to a gel. After cooking, the starch shall possess good clarity, excellent taste, and a smooth, short textured heavy body. The starch shall comply with MIL-STD-900.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.

3.2.6 Starch, waxy maize, modified. The starch shall be white, odorless, finely pulverized, modified waxy maize starch for use in thermostabilized foods and shall comply with MIL-STD-900. The modified starch shall demonstrate initial viscosity development in the temperature range of 140° to 170°F and a typical viscosity (be fully hydrated) at common retort temperatures. The starch shall resist breakdown at low pH, under shear stress and under conditions of cold storage. The cooked modified starch slurry shall be bland with essentially no cereal or starch taste.

3.2.7 Salt. Salt shall be non-iodized, white, refined sodium chloride with or without anticaking agents and shall comply with purity standards for sodium chloride of the Food Chemicals Codex.

3.2.8 Pepper, white, ground. Ground white pepper shall be derived from the dried mature berries of Piper nigrum L. from which the outer covering or the outer and inner covering have been removed. The ground pepper shall have a characteristic penetrating odor, a hot, biting, pungent flavor, and a light color. The ground white pepper shall contain not less than 1.0 mL of volatile oil per 100 grams of ground white pepper and be of such size that not less than 95 percent shall pass through a U.S. Standard No. 40 sieve.

3.2.9 Citric acid. Citric acid shall comply with the Food Chemicals Codex.

3.2.10 Color, annatto, dry. Annatto color shall be a reddish-orange water soluble powder of the extractive of Annatto bixa Orellana. The powder shall contain not more than 5.0 percent moisture and 100 percent of the powder shall pass through a U.S. Standard No. 10 sieve. The total color (as percent Norbixin) shall be 15 percent.

3.2.11 Preblended spice and seasoning mixture. Preblended spices and seasonings may be used. The spices and seasonings in the mixture shall comply with the individual requirements specified in this document. The containers used for the spice and seasoning blend shall be labeled with each ingredient and the percentage of each ingredient in the blend. The ingredients shall be in the same proportions as specified in the ingredient formula.

3.3 Preparation and further processing. Processing shall be on a continuous basis.

3.3.1 Preparation of ham. The ham shall be mechanically diced with dicer settings of approximately 3/8 by 3/8 by 3/8 inches. The ham dices shall be maintained in the temperature range of 28° to 40°F for not more than 48 hours prior to the time of product preparation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.

3.3.2 Preparation of the omelet with ham. All mixing shall be at a slow speed setting to minimize the incorporation of air into the product. The omelet with ham shall be prepared as follows:

Ingredients	Percent by weight
Eggs, whole	46.000
Ham, dices	26.000
Water	15.296
Oil, vegetable	7.500
Starch, instant (for eggs) waxy maize, modified, pregelatinized	3.750
Starch, waxy maize, modified	1.000
Salt	0.300
Pepper, white, ground	0.100
Citric acid	0.050
Color, annatto, dry	0.004

a. The instant starch shall be gradually combined with the oil to form a smooth mixture.

b. The eggs, citric acid, annatto color, salt, and white pepper shall be gradually added and blended only until a smooth emulsion (no lumps) is formed.

c. The 1.0 percent starch and the water shall be thoroughly mixed into the emulsion.

d. The diced ham shall be added to the emulsion and uniformly mixed.

3.4 Tray pack filling and sealing. Each tray pack can (see 5.1.1) shall be filled with product so as to conform to the finished product requirements and to the following requirements:

a. Each can shall be hermetically sealed under a vacuum established by a processing authority and specified in the scheduled process so as to assure compliance with the finished product requirements (see 3.6.n).

b. Each filled and sealed tray pack can shall be in the retort process within 2 hours after preparation.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized by retorting until a sterilization value (F_o) of not less than 6 has been achieved.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, dirt, insect parts, hair, wood, glass, or metal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.

b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour, rancid, or moldy.

c. There shall be no color foreign to the product.

d. The average net weight shall be not less than 102 ounces.

e. No individual can shall contain less than 100 ounces of product.

f. No individual can shall contain more than 3.0 ounces by weight of free liquid.

g. Ham dices shall be dispersed evenly throughout the product.

h. Texture of the product shall not be rubbery.

i. The average fat content shall not be greater than 15.0 percent.

j. No individual can shall have a fat content greater than 17.0 percent.

k. No individual can shall have a salt content greater than 1.3 percent or less than 0.5 percent.

l. The product shall show no evidence of excessive heating (materially darkened or scorched).

m. The product shall show no visible lumps of starch.

n. Filled, sealed, and retorted cans shall show evidence of proper vacuum as determined by concavity of the can lid (see 4.5.6).

3.6.1 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The meat component and the finished product shall originate and be produced, processed, and stored in plants regularly operating under Meat and Poultry Inspection Regulations of the U.S. Department of Agriculture.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection necessary to assure compliance with the requirements of this document.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this document and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this document or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods, such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

4.5.3.1 Net weight inspection. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty tray pack cans and lids used in preparing the product and dividing the total weight by 30) from the weight of each tray pack in the sample. Results shall be reported to the nearest 1 ounce. If the average net weight is less than 102 ounces or if the net weight of any individual can is less than 100 ounces, the lot shall be rejected.

4.5.3.2 Product inspection. The sample size shall be as indicated by the double sampling plan specified in table I. The tray pack cans shall be selected at random from the lot. Tray pack cans shall be heated for 35 minutes in boiling water, opened, and inspected for the defects listed in table II.

TABLE I. Double sampling plan for product inspection 1/

Lot size (cans)	Sample size (cans)	Cumulative sample	Acceptance number	Rejection number
0 to 3200	8	-	0	2
	8	16	1	2
3201 to 35000	13	-	0	3
	13	26	3	4

1/ a. If no defects are found in the first sample, the lot shall be accepted.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.

TABLE II. Product defects 1/ 2/

Category	Defect
Major	
151	Ham dices not dispersed evenly throughout the product.
152	Texture of the product is rubbery.
153	Product shows evidence of excess heating (materially darkened or scorched).
154	Free liquid in a can weighs more than 3.0 ounces. 3/
155	Product shows visible lumps of starch. 3/

1/ The presence of foreign material (e.g., glass, dirt, insect parts, hair, wood, metal) foreign odor or flavor (e.g., burnt, scorched, moldy, rancid, sour, stale), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an Agricultural Marketing Service (AMS) agent.)

3/ To determine the weight of free liquid and to inspect for gel lumps, bone, cartilage, and discoloration, the following precedure shall be used. The product shall be placed into an 18-inch diameter US Standard No. 8 sieve. A portion of the omelet (approximately 5 inches by 2-1/2 inches) shall be cut out of one corner of the omelet and separated from the remainder, but left on the sieve. The sieve shall be tilted with the cut corner downward to an approximate 45 degree angle and allowed to drain 1 minute before determining the weight of free liquid by subtracting the sieve tare weight from the gross weight. The free liquid shall be reported to the nearest 0.1 ounce. The product shall be divided into ten approximately equal portions (including the cut out portion) for inspection for gel lumps, bone, cartilage, and discoloration.

4.5.3.3 Fat and salt content testing. Nine tray pack cans shall be selected at random from the lot and distributed as follows:

- three for laboratory analysis
- three for submission to the contractor
- three for retention by an AMS agent as a reserve sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.

The three tray packs for laboratory analysis shall individually be tested for fat and salt content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists (AOAC), chapter: Meat and Meat Products, except that preparation of the samples shall be as follows: The three unopened cans shall be gently warmed in a water bath to melt fat adhering to the inside of the cans. The cans shall be opened and the entire contents of each can shall be separately blended in a Waring blender or equivalent. The test results shall be reported to the nearest 0.1 percent. Any test failure is a major defect. The lot shall be rejected if any of the following major defects occur:

a. The average fat content of the three tray packs is greater than 15.0 percent.

b. The fat content of any individual tray pack is greater than 17.0 percent.

c. The salt content of any individual tray pack is less than 0.5 percent or greater than 1.3 percent.

Analysis of reserve samples at the request of the contractor shall not be permitted unless the original laboratory analysis indicated that the involved lot will be rejected because of noncompliance with the fat or salt content requirement. When the reserve samples are analyzed, the analyses for both fat and salt shall be made and will be considered final. Unused reserved samples shall be returned to the contractor for inclusion in subsequent lots.

4.5.4 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the United States Standards for Condition of Food Containers except that the inspection for labeling shall be in accordance with 4.5.4.1.

4.5.4.1 Can label examination. Labels shall be examined for defects in accordance with MIL-L-1497 (see 5.4), except, that for self-adhering labels, the following additional defects shall apply:

Major: Label torn or scratched so as to obliterate any of the markings.

Minor: Air bubbles under label.
Label not properly adhered to can, i.e., label raised or peeled back from edges or corners.

4.5.4.2 Label adhesive examination. When self-adhering labels are used, the adhesive shall be tested in accordance with ASTM-D-3330.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.

4.5.5 Can closure examination. Can closures shall be examined visually and by teardowns in accordance with the can manufacturer's requirement and 21 CFR, Part 113, Subpart D, or 9 CFR, Part 318, Subpart G, as applicable. Any nonconformance based on observation of can seam teardowns or of record of can seam teardowns is a major defect and shall be cause for rejection of any involved product.

4.5.6 Vacuum examination. Cans shall be allowed to cool to 75° ± 5°F, held for at least 24 hours after sealing, and then examined for vacuum retention. To examine, lay a straight edge in the center of the lid along the length of the tray pack. Both ends of the straight edge shall touch the lid at the inside edge of the double seam. There shall be a visible gap between the straight edge and the lid for the entire distance of the label panel. Using a shorter straight edge, the same procedure shall be used across the width, in the center of the tray pack can. When examining a ribbed lid, only lay the straight edge between the two center ribs along the length of the can. The inspection lot shall include only tray packs produced in a single shift on a single sealing machine. The sample size shall be 50 cans. Any nonconformance is a major defect and shall be cause for rejection of the lot.

4.5.7 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
Reinforced with other than nonmetallic strapping or tape.
Dimensions of pads not as specified.
Interior packing with fiberboard liner or pads not as specified.

Minor: Other required markings missing, incorrect, or illegible.
Arrangement or number of cans not as specified.

4.5.8 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A or C as specified (see 6.1).

5.1.1 Level A. A size 1001 by 1206 by 200 tray pack can shall be filled with 102 ounces of the food product, sealed and thermoprocessed as specified in 3.4 and 3.5. The base plate of the can shall be electrolytic chromium-coated steel and shall be of sufficient temper to protect the product during shipment and storage. The base plate weight of the body and end of each can shall be 90 pounds per base box. The entire inside area of the can shall be coated. Scratches or fractures shall not penetrate through the interior can coating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.

The interior can coating shall not peel or blister when in contact with the product. The interior can coating shall neither affect nor be affected by the packaged product. A certificate of conformance shall be furnished to certify compliance with the interior can coating requirements. The can shall be coated overall on the outside with a coating conforming to type I of TT-C-495.

5.1.1.1 When specified (see 6.1), the base plate of the can shall be electrolytic chromium-coated steel and shall be of sufficient temper to protect the product during shipment and storage. The base plate weight of the body and end of each can shall be 98 pounds per base box. The body design shall be reinforced on the bottom with six longitudinal beads or ribs 0.050 $\pm$ 0.010 inches deep. The beads shall be 9 inches by 3/4 inch in length and width and shall be equidistant in the center panel of the bottom. The end design shall be reinforced with eight longitudinal beads 0.018 $\pm$ 0.004 inches deep. The beads shall be 11 inches by 3/4 inch in length and width and shall be equidistant in the center panel of the end. The center four beads on the end design shall be interrupted to provide a 5-inch by 5-inch flat center panel for labeling. The apex of all these beads shall be outward. The interior and exterior can coating requirements shall be as specified in 5.1.1.

5.1.2 Level C. The product shall be preserved as specified in 5.1.1, except that cans with commercial exterior coating will be acceptable.

5.2 Packing. The product shall be packed in accordance with level A, B, or C as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L or HSC-L with a HSC full depth cover, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads fabricated of grade V3c fiberboard. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box. Each box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament-reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1) except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1 except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.

5.2.3 Level C packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of the same material as the box.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping except for type II, class F, loads.

5.4 Labeling. Each tray pack can shall be labeled in accordance with MIL-L-1497 and with the following:

- Official establishment number (e.g., est 38) or a three letter code identifying the establishment.
- Lot number 1/
- Product shift number 1/
- Retort identification number 1/
- Retort cook number 1/

1/ The lot number shall be expressed as four digit Julian code. The first digit shall indicate the year of production and the next three digits shall indicate the day of the year (Example, March 19, 1987 would be coded as 7078). The Julian code shall represent the day the product was packaged and processed. Sub-lotting (when used) shall be represented by an alpha character immediately following the four digit Julian code. Following the four digit Julian code and the alpha character (when used), the other required code information shall be printed in the sequence as listed above.

Alternatively, a pre-printed self-adhering 0.002 inch thick clear polyester label printed with indelible black ink may be used. Self-adhering labels shall be applied after retorting. Pressure-sensitive adhesive shall require no preparation prior to application. Labels shall tack quickly and adhere without curling or breaking. The adhesive shall have a minimum adhesion of 60 ounces per inch width when examined as specified in 4.5.4.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.

In addition, the name of product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined as specified in 4.5.4 after preparation of product in accordance with heating instructions. Paper labels are not permitted. Cans shall show the following statements:

TO HEAT: Submerge unopened can in boiling water. Simmer gently for 40 to 45 minutes. Avoid overheating (can shows evidence of bulging).

CAUTION: Use care when opening as pressure may have been generated within the can.

To heat in oven: Either punch several holes in lid of can or open can in usual manner leaving the loose lid in place. Place in a 350°F oven for approximately 35 to 40 minutes.

WARNING: Do not place unopened can in oven. This may cause the can to burst.

YIELD: Serves 18 portions of 2/3 cup each.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, when tray pack cans are fabricated from 90 pounds per base box, the following precautionary marking in capital letters larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1, 4.4, and 6.3).
c. Provisions for approved preproduction samples (see 3.6.1 and 6.3).
d. Level of preservation and packing required (see 5.1 and 5.2).
e. When tray pack cans are to be fabricated from 98 pounds per base box (see 5.1.1.1).
f. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A.DLAR 4145.7.

6.3 First article. When a first article sample is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Starch, waxy maize, modified, pregelatinized, instant. It has been found that National 78-0018 Food Starch manufactured by National Food Starch and Chemical Corporation, Food Products Division, P.O. Box 6500, Bridgewater, NJ 08807 meets the requirements of 3.2.5 and performs satisfactorily in this product.

6.5 Subject term (key word) listing.

Canned foods
Combat field feeding
Egg
Ham
Thermostabilized
Tray pack

Custodians:

Army - GL
Navy - SA
Air Force - 50

Preparing activity:

Army - GL

Project No. 8940-0604

Review activities:

Army - MD, TS
Navy - MC
DP - SS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-O-44327	Omelet with Ham, Artifically Colored, Thermostabilized, Tray Pa

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 NATICK/OPI Feb 86 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:28Z
Check the source to verify that this is the current version before use.