INCH-POUNDS

MIL-F-44330 (GL)
28 November 1988

MILTARY SPECIFICATION

FOOD SANITATION CENTER, FOR USE WITH FIELD KITCHENS

This specification is approved for use by the U.S. Army Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1 Scope. This specification covers the components of the food sanitation center.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

A-A-295	-	Waste Receptacle, Mobile, Plastic, with Lid
PPP-T-45	-	Tape, Gummed, Paper Reinforced and Plain, For sealing and Securing
PPP-T-76	-	Tape, Pressure Sensitive Adhesive, Packaging / Paper (For Carton Sealing)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Reseach, Development, and Engineering Center, Natick MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of the document or by letter.

AMSC N/A FSC 7360

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:30Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-226	-	Preservation, Methods of
MIL-B-117	-	Bag, Sleeve and Tubing - Interior Packing
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible
MIL-T-704	-	Treatment and Painting of Material
MIL-L-1594	-	Lantern, Gasoline, Leaded or Nonleaded Fuel with Case
MIL-T-3462	-	Thermometer, Self Indicating, Bimetallic, 5-1/2 Inch
MIL-W-8611	-	Welding, Metal Arc and Gas, Steels, Corrosion and Heat Resistant Alloys, Process for
MIL-P-14105	-	Paint, Heat-resisting (For Steel Surfaces)
MIL-B-26195	-	Box, Wood-cleated, Skidded, Load-bearing Base
MIL-B-40098	-	Burner Unit, Gasoline, Field Range Outfit, M2A
MIL-T-44271	-	Tents, Expendable, Modular, Personnel (Temper), Assembly Components
MIL-C-46168	-	Coating, Aliphatic Polyurethane, Chemical Agent Resistant
MIL-P-53022	-	Primer, Epoxy Coating, Corrosion Inhibiting, Lead and Chromate Free

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-130	-	Identification Marking of U.S. Military Property

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

Department of the Army Technical Manuals

TM 10-7360-204-13&P - Equipment Publication Technical Manual Operator, Oraganizational, and Direct Support Maintenance Manual Including Repair Parts and Special Tools List for Range Outfit, Field, Gasoline Model M59.

TM 10-7360-211-13&P - Equipment Publication Technical Manual Operator, Oraganizational, and Direct Support Maintenance Manual Including Repair Parts and Special Tools List for Sanitation Center.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:30Z
Check the source to verify that this is the current version before use.

TM 10-8340-224-13&P - Operator's, Organizational, and Direct Support Maintenance Manual Including Repair Parts and Special Tools List for Tent, Extendable, Modular

(Copies of the Army Technical Manuals are availible from the U.S. AG Publications Center, 1655 Woodson Road, St. Louis, MO 63144.)

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-13-3749	-	Three Sink Drain Hose Assembly
5-13-3868	-	Base Rack Assembly
5-13-3875	-	Burner Rack Assembly
5-13-4050	-	Storage Rack Assembly
5-13-4120	-	Sink Assembly
5-13-4121	-	Sink Body Assembly
5-13-4207	-	Sink Cover Top Assembly
5-13-4240	-	Sink Drain Table Assembly
5-13-4241	-	Drain Table, Top Assembly
5-13-4242	-	36 Inch Field Table Assembly
5-13-4243	-	Table Top Assembly
5-13-4245	-	Leg Adapter Assembly
5-13-4247	-	Leg Mounting Bracket Assembly
5-13-4255	-	Rack, Sink, Immersion
5-13-4256	-	Sink Adapter
5-13-4257	-	Shelf Assembly
5-13-4258	-	Body, Shelf
5-13-4261	-	Thermometer Bracket, Sink
5-13-4262	-	Guide, Shelf

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, STRNC-EMSS, Natick, MA 01760-5014.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

NATIONAL SANITATION FOUNDATION (NSF)

Standard No. 2 - Food Service Equipment
Criteria No. 2 - Special Equipment and/or Devices

(Application for copies should be addressed to the National Sanitation Foundation, 3475 Plymouth Rd., P.O. Box 1468, Ann Arbor, MI 48106.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:30Z
Check the source to verify that this is the current version before use.

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraies or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, shall supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Alternate components. Components offered as equivalent to components specified hereinafter and on the referenced drawings as a specific manufacturer's part or model number or equal, shall be funtionally equal to the manufacturer's model number identified, and of equal or better quality. The incorporation and inclusion of such a component in the design of the specified end product shall not require modification or change to any other specified component, and shall not reduce ease of maintenance to it or any other components, unless such modification or change is specifically approved by the contracting officer. Prior to manufacture of the first article, or if none is required, prior to commencing production, the contractor shall submit for the contracting officer's approval, a list identifying each proposed alternate component, together with proof that each listed component complies with requirements specified above. The contracting officer, at his option, may require a physical sample of the proposed substitution. Approval of the submitted listing, together with the necessary supporting data, authorizes commencement of manufacture but does not relieve the contractor of responsibility that these components perform in accordance with specified requirements when incorporated into the end product.

3.3 Materials and components. The materials and components used shall conform to the applicable referenced specifications, standards, drawings, and requirements specified herein. Where materials are not definitely specified, they shall be of the quality normally used for the purpose in commercial practice provided the completed items comply with all provisions of this document. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document.

3.4 Design and construction. The sanitation center is designed for field cleaning of food service equipment. The design and construction shall be as specified herein and as specified on the applicable drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:30Z
Check the source to verify that this is the current version before use.

3.4.1 Welders. Prior to assigning any welder to structural welding on the food sanitation center components to be furnished under this specification, the contractor shall provide the contracting officer or his authorized representative with the names of welders to be employed in the work, together with certification that each of these welders has passed qualification tests as prescribed by either of the following listed codes for the type of welding operation to be performed.

a. Standard Qualification Procedure of the American Welding Society

b. Welding Qualification of the American Society of Mechanical Engineers

3.5 Contractor furnished components. Each food sanitation center shall included the contractor furnished components specified in 3.5.1 thru 3.5.9.

3.5.1 Sink adapter. Two adapters shall be provided with each sanitation center. The adapters shall conform to Drawing 5-13-4256.

3.5.2 Bracket, thermometer. Three thermometer brackets shall be provided with each sanitation center. The thermometer brackets shall conform to Drawing 5-13-4261.

3.5.3 Hose, drain. One three-sink drain hose assembly shall be provided with each sanitation center. The drain hose shall conform to Drawing 5-13-3749.

3.5.4 Rack set, storage and drying. Two storage rack sets shall be provided with each sanitation center. Each set shall consist of three storage rack assemblies conforming to Drawing 5-13-4050.

3.5.5 Rack, sink immersion. Two sink immersion racks shall be provided with each sanitation center. The sink immersion racks shall conform to Drawing 5-13-4255.

3.5.6 Sink assembly. Three sink assemblies shall be provided with each sanitation center. The sinks shall conform to Drawing 5-13-4120 which consist of the sink body assembly, Drawing 5-13-4121; burner rack assembly, Drawing 5-13-3875; base rack assembly, 5-13-3868. When tested as specified in 4.4.5, the sink body shall show no leakage of water.

3.5.6.1 Data name plate. The three sinks shall each be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for; (a) Methods of applying, (b) Identification tags, (c) Information not required and (d) Optional marking information shall not apply. The data name plate shall be made of minimum 20 gauge (0.035 inch) corrosion

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:30Z
Check the source to verify that this is the current version before use.

resisting metal and attached to the sink by rivets, by screws or by welding in such a manner as to meet the applicable National Sanitation Foundation (NSF) sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved, or applied by photosensitive means:

National Stock Number (NSN)
Procurement Instrument Identification Number
Specification Data (Document No.)
Manufacturer's Name, Address, and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Numbers (see 6.2)

Each plate shall be placed on the right side panel, in the upper left hand corner, so that it is readily visible to the operator during normal operating use, and so as to not adversely affect the life and utility of the sink.

3.5.7 Table, drain. One drain table shall be provided with each sanitation center. The drain table shall conform to Drawing 5-13-4240.

3.5.8 Table, field, 36 inches high. One field table shall be provided with each sanitation center. The field table shall conform to Drawing 5-13-4242.

3.5.9 Shelf. One shelf shall be provided with each sanitation center. The shelf shall conform to Drawings 5-13-4257, 5-13-4258, and 5-13-4262.

3.6 Government-furnished property (GFP). Each sanitation center shall include the Government-furnished property listed below (see 6.4).

Item No.	Description	Identification National Stock Number	Quantity
1.	Tent extendable, modular (16 by 20 foot, utility) MIL-T-44271	8340-01-185-2613	1
2.	Burner unit, M2A, conforming to MIL-B-40098	7310-00-017-1285	3
3.	Extinguisher, fire	4210-01-149-1356	1
4.	Lantern, gasoline, conforming to MIL-L-1594	6260-00-170-0430	2

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:30Z
Check the source to verify that this is the current version before use.

Item No.	Description	Identification National Stock Number	Quantity
5.	Thermometer, 5-1/2 inch conforming to MIL-T-3462	6685-00-444-6500	3
6.	Trash barrel, plastic, 32 gallen with Lid, conforming to A-A-295	7240-00-151-6629	2
7.	TM-10-7360-211-13&P		1
8.	TM-10-7360-204-13&P		1
9.	TM-10-8340-224-13&P		1

3.7 Welding. The surfaces of parts for the components in 3.5.1 to 3.5.9 to be welded shall be free from oxide, scale, paint, grease, or other foreign matter. Welds shall have a smooth, regular bead, shall be uniform in cross section, and shall be free of pits, cracks, holes, undercuts, or incomplete fusion. All scale, weld flack, flux, splatter, rough surface, and projecting modules shall be removed.

3.8 Fastening devices. Threaded fastener and rivet holes of the components in 3.5.1 to 3.5.9 shall have burrs removed. Threaded fasteners shall not be broken, cracked, or stripped and shall be securely torqued. Rivets shall fill the holes completely and the heads shall be in full contact with the surface of the riveted members.

3.9 Finish.

3.9.1 Surface preparation. The exterior surfaces of the sink, sink cover, base rack, burner rack, rack set (storage and drying), shelf, and table top shall be cleaned and conditioned. Rough or sharp edges and corners, burrs, and slivers shall be removed. Ferrous surfaces on any components to be painted shall first be thoroughly cleaned and conditioned in accordance with type F of MIL-T-704. Aluminum and aluminum alloy surfaces shall be cleaned and conditioned in accordance with type G of MIL-T-704.

3.9.2 Primer paint treatment. After surfaces are thoroughly dried from cleaning and conditioning, a coat of primer in accordance with MIL-P-53022 shall be applied in accordance with MIL-T-704, type G.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:30Z
Check the source to verify that this is the current version before use.

3.9.3 Finish coat. After primer has thoroughly dried, the base rack and burner rack shall be given a finish coat conforming to MIL-C-46168, type II, color green 383. The exterior surface of the sink and sink cover, rack set (storage and drying), shelf, and table top shall have a finish coat of MIL-P-14105 paint in color to match green 383 of MIL-C-46168. This paint shall contain no lead or chromate. The paint shall be applied so that there will be no streaks, crops, pinholes, cheeks, or cracks.

3.10 Workmanship. The components of the food sanitation center shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as a part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)
b. Quality conformance inspection (see 4.4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:30Z
Check the source to verify that this is the current version before use.

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4 and tested for the characteristic specified in 4.4.5. The presence of any defect or failure to pass any test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document. In addition the components listed in 3.5.1 through 3.5.9 shall be inspected in accordance with 4.4.2.1 through 4.4.5.

4.4.2 In-process inspection. Inspection of components shall be made at any point or during any phase of the manufacturing process to determine whether dimensions which cannot be examined in the finished product are in accordance with specified requirements. Whenever nonconformance is noted, correction shall be made to the items affected, the lot in progress, and to the operation. Parts which cannot be corrected shall be removed from production.

4.4.2.1 In-process inspection of welding. In lieu of inspecting welding in accordance with the following procedures, the contractor may propose to the Procuring Contracting Officer (PCO), alternative procedures for operator and equipment certification. When necessary or when requested by the Government, the contractor shall submit representative samples supporting these alternative procedures. The Government will reply to the contractor within ten working days after receipt of the proposal.

4.4.2.1.1 Spot welding. Spot welding shall be inspected in accordance with MIL-W-8611 (metal arc and gas welding) except that pull tests shall be performed in lieu of magnetic, penetrant, and radiographic tests. The pull tests shall be performed at the daily start of each production run on each machine or whenever there is a break in production, adjustment of welding machine, or change in operator. The pull tests shall verify minimum nugget size and complete bonding of the two metals. At least two sample welds shall be tested using material identical to the applicable components.

4.4.2.1.2 Fillet welding. Fillet welding shall be inspected in accordance with MIL-W-8611.

4.4.3 Component visual examination. The components and assemblies specified in 3.5.1 through 3.5.9 shall be examined in a separate lots for the applicable defects listed in table I. The lot size shall be expressed in units of like components or assemblies. The sample unit shall be one component or assembly as applicable. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 1.0 for major defects and 4.0 for minor defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:30Z
Check the source to verify that this is the current version before use.

TABLE I. Component visual defects

Examine	Defect	Classification Major	Minor
Material	Hole or crack in any component	101	
	Dent, bend, or other malformation in any component	102	
Finish	Material such as rust, dirt, oil or grease		201
	Rough tool, die, or grind mark		202
	Dent, scratch, or crack not affecting serviceability		203
	Dent, scratch, or crack affecting serviceability	103	
	Burr or sliver which may inflict injury	104	
	Sharp edge or sharp corner	105	
	Burr on inside of holder of can opener	106	
	Finish on top of table or holder of can opener not as specified	107	
Painted surfaces	Color not as specified	108	
	Film not smooth or not uniform		204
	Area of no paint		205
	Painted surface contains run, streak, wrinkle, drop or grit		206
	Paint is peeling		207
Welding	Missing, incomplete or incorrectly located square groove or fillet weld	109	
	Weld not of the specified type or size		208
	Irregular or non-uniform cross section of fillet weld beed		209
	Crack, burnhole, undercutting, or overlapping of weld		210
	Weld scale, flux, or spatter not removed		211
Sink	Does not have a data name Palte	110	
	Data name plate incorrect or illegible	111	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:30Z
Check the source to verify that this is the current version before use.

TABLE I. Component visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Field table	Legs do not travel to, and lock in fully opened position, and close under no more than moderate hand pressure	112	
	Legs fold without releasing lock arm	113	
	Nut with washer is not tightly securing leg to table		212
	Lower edge of table is not fully rolled back		114

4.4.4 Component dimensional examination. The components and assemblies listed in table II shall be examined in separate lots for conformance to the dimensions specified in table II. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of like components or assemblies. The sample unit shall be one component or assembly as applicable. The inspection level shall be S-4 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

TABLE II. Component for dimensional examination 1/

Component	Examine
Sink adapter (Dwg. 5-13-4256)	All dimensions specified.
Bracket, Thermometer (Dwg. 5-13-4261)	All dimensions specified.
Hose, drain (Dwg. 5-13-3749)	All dimensions specified.
Storage Rack Assembly (Dwg. 5-13-4050)	All dimensions specified.
Rack, Sink immersion (Dwg. 5-13-4255)	All dimensions specified.
Sink body assembly (Dwg. 5-13-4121)	All dimensions specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:30Z
Check the source to verify that this is the current version before use.

TABLE II. Component for dimensional examination 1/ (cont'd)

Component	Examine
Sink cover top assembly (Dwg. 5-13-4207)	All dimensions specified.
Burner rack assembly (Dwg. 5-13-3875)	All dimensions specified.
Base rack assembly (Dwg. 5-13-3868)	All dimensions specified.
Table, drain (Dwg. 5-13-4240)	All dimensions specified, and those dimensions on the following sub-assembles: a. Drain table, top assy. (Dwg. 5-13-4241) b. Leg adapter assembly (Dwg. 5-13-4245-2)
Table, field, 36 inches high (Dwg. 5-13-4242)	All dimensions specified. and those dimensions on the following sub-assembles: a. Table top assembly (Dwg. 5-13-4243) b. Leg mounting bracket assembly (Dwg. 5-13-4247-1) c. Leg adaptor assembly (Dwg. 5-13-4245-1)
Shelf (Dwg. 5-13-4257)	All dimensions specified.

1/ Only those dimensions that can be evaluated without damaging or disassembling the component shall be examined.

4.4.5 Sink testing. Close valve of sink body assembly, then fill the sink with tap water to within 2 inches of the top. Let stand for 5 minutes, at that time observe the sink for leakage. Any evidence of leakage shall constitute a rejection of that sink body assembly.

4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:30Z
Check the source to verify that this is the current version before use.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Components not adequately blocked, braced, or stored in available space within the equipment.
Content	Not as specified.

5. PACKAGING

5.1 Preservation. Preservation shall be level A.

5.1.1 Level A. The component parts of each complete sanitation center shall be cleaned and preserved in accordance with table III. Grease-proof barrier material shall conform to MIL-B-121. Paper tape used to secure barrier material shall conform to type III, grade A of PPP-T-45 or PPP-T-76.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:30Z
Check the source to verify that this is the current version before use.

TABLE III. Preservation of food sanitation center components

Quantity per unit	Component	Method of cleaning (MIL-P-116)	Type of preservative and application (MIL-P-116)	Type of grease proof barrier	Method of preservation (MIL-P-116)
2	Barrel, trash	None	None	None	III
3	Base rack	None	None	None	III
3	Bracket, thermometer	None	None	None	III
3	Burner rack	None	None	None	III
3	Burner unit, M2A	C-1	P-14 Burner only Grade A	Type I or II or of MIL-B-121	I
1	Fire extinguisher	None	None	None	III
1	Hose assembly	None	None	None	III
2	Lanterns, gasoline	None	None	None	III
2	Rack sets, drying/storage	None	None	None	III
2	Rack, sink, immersion	None	None	None	III
1	Shelf	None	None	None	III
2	Sink adapter	None	None	None	III
3	Sink, body	None	None	None	III

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T01:30Z
Check the source to verify that this is the current version before use.

TABLE III. Preservation of food sanitation center components (cont'd)

Quantity per unit	Component	Method of cleaning (MIL-P-116)	Type of preservative and application (MIL-P-116)	Type of grease proof barrier	Method of preservation (MIL-P-116)
3	Sink, cover	None	None	None	III
1	Table, drain	None	None	None	III
1	Table, field	None	None	None	III
3	Technical manual	None	None	MIL-B-117	IC-1
1	Tent, Extendable, modular (16 by 20 foot section)	None	None	None	III
3	Thermometer, sink	None	None	None	III

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T01:30Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A.

5.2.1 Level A. Each complete food sanitation center, preserved as specified in 5.1, shall be packed in the most compact manner in a wood-cleated plywood box conforming to type II, style B, class 1, grade I of MIL-B-26195. Maximum use shall be made of available space within the equipment for packing smaller components and nesting when possible. The contents of each box shall be cushioned, blocked or braced to prevent movement or damage while in transit. Each box shall be provided with ventilating holes or slots and strapped in accordance with MIL-B-26195.

5.3 Marking. In addition to any special marking required by the contract or order, unit packs and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The sanitation center is an assemblage of equipment that provides the capability of cleaning pots, pans and food service equipment associated with the combat field feeding system, and the modular field kitchen (MIL-K-44329), in basic, hot, cold, and severe cold climate conditions with shelter from the environment.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this document.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Source and delivery of government furnished property (see 3.6)
e. Government approved manual numbers to be included in data name plate (see 3.5.6.1).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Government-furnished property. The contacting officer should arrange to furnish the property listed in 3.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:30Z
Check the source to verify that this is the current version before use.

6.5 Subject term (key word) listing.

Cleaning
Combat field feeding system
Sterilizing
Washing

Custodian:
Army - GL

Review activities:
Army - MD, TS

Preparing activity:
Army - GL

(Project 7360-0161)

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-44330(GL)	Food Sanitation Center, For Use with Field Kitchen

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026/10-22T01:30Z
Check the source to verify that this is the current version before use.

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP-1, Feb 86

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:30Z
Check the source to verify that this is the current version before use.