INCH-POUND

MIL-F-44330A(GL)
13 January 1995
SUPERSEDING
MIL-F-44330(GL)
28 November 1988

DETAIL SPECIFICATION

FOOD SANITATION CENTER, FOR USE WITH FIELD KITCHENS

This specification is approved for use by the Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the components of the food sanitation center.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are needed to meet the requirements specified in sections 3, 4, and 5 of this specification. This section does not include documents in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all requirements documents cited in sections 3, 4, and 5 of this specification, whether or not they are listed.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development and Engineering Center, Natick, MA 01760-5018 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of the document or by letter.

AMSC N/A FSC 7360

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:29Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards, (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

DEPARTMENT OF DEFENSE

MIL-T-704 - Treatment and Painting of Materiel

STANDARDS

DEPARTMENT OF DEFENSE

MIL-STD-2219 - Fusion Welding for Aerospace Applications

(Unless otherwise indicated, copies of the above specifications, standards and handbooks are available from the Standardization Documents Order Desk, Building 4D,700 Robbins Avenue, Philadelphia, PA 19111-5094,)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

Department of the Army Technical Manuals

TM 10-7360-204-13&P - Equipment Publication Technical Manual Operator, Organizational, and Direct Support Maintenance Manual Including Repair Parts and Special Tools List for Range Outfit, Field, Gasoline Model M59.

TM 10-7360-211-13&P - Equipment Publication Technical Manual Operator, Organizational, and Direct Support Maintenance Manual Including Repair Parts and Special Tools List for Sanitation Center.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:29Z
Check the source to verify that this is the current version before use.

TM 10-8340-224-13 - Operator's, Organizational, and Direct Support Maintenance Manual Including Repair Parts and Special Tools List for Tent, Extendable, Modular

(Copies of the Army Technical Manuals are available from the U.S. AG Publications Center, 1655 Woodson Road, St. Louis, MO 63144.)

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

5-13-3749	-	Three Sink Drain Hose Assembly
5-13-3868	-	Base Rack Assembly
5-13-3875	-	Burner Rack Assembly
5-13-4050	-	Storage Rack Assembly
5-13-4061	-	One Sink Drain Hose Assembly
5-13-4120	-	Sink Assembly
5-13-4121	-	Sink Body Assembly
5-13-4207	-	Sink Cover Top Assembly
5-13-4240	-	Sink Drain Table Assembly
5-13-4241	-	Drain Table, Top Assembly
5-13-4242	-	36 Inch Field Table Assembly
5-13-4243	-	Table Top Assembly
5-13-4245	-	Leg Adapter Assembly
5-13-4247	-	Leg Mounting Bracket Assembly
5-13-4255	-	Rack, Sink, Immersion
5-13-4256	-	Sink Adapter
5-13-4257	-	Shelf Assembly
5-13-4258	-	Body, Shelf
5-13-4261	-	Thermometer Bracket, Sink
5-13-4262	-	Guide, Shelf

(Copies of drawings are available from the U.S. Army Natick Research, Development and Engineering Center, SATNC-WEF, Natick, MA 01760-5018.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:29Z
Check the source to verify that this is the current version before use.

AMERICAN WELDING SOCIETY (AWS)

Standard Qualification Procedure of the American Welding Society

(Application for copies should be addressed to the American Welding Society, 550 N.W. Lejeune Road, Miami, FL 33126.)

American Society of Mechanical Engineers (ASME)

Welding Qualifications of the American Society of Mechanical Engineers

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East Street, New York, NY 10017.)

NSF INTERNATIONAL

Standard No. 2 - Food Service Equipment
Criteria No. 2 - Special Equipment and/or Devices

(Application for copies should be addressed to NSF International, 3475 Plymouth Rd., Ann Arbor, MI 48105.)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, except for related associated specifications, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.3.

3.2 Alternate components. Components offered as equivalent to components specified hereinafter and on the referenced drawings as a specific manufacturer's part or model number or equal, shall be functionally equal to the manufacturer's model number identified, and of equal or better quality. The incorporation and inclusion of such a component in the design of the specified end product shall not require modification or change to any other specified component, and shall not reduce ease of maintenance to it or any other components, unless such modification or change is specifically approved by the contracting officer. Prior to manufacture of the first article, or if none is required, prior to commencing production, the contractor shall submit for the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:29Z
Check the source to verify that this is the current version before use.

contracting officer's approval, a list identifying each proposed alternate component, together with proof that each listed component complies with requirements specified above. The contracting officer, at his option, may require a physical sample of the proposed substitution. Approval of the submitted listing, together with the necessary supporting data, authorizes commencement of manufacture but does not relieve the contractor of responsibility that these components perform in accordance with specified requirements when incorporated into the end product.

3.3 Materials and components. The materials and components used shall conform to the applicable referenced specifications, standards, drawings, and requirements specified herein. Where materials are not definitely specified, they shall be of the quality normally used for the purpose in commercial practice provided the completed items comply with all provisions of this document. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document.

3.4 Design and construction. The sanitation center is designed for field cleaning of food service equipment. The design and construction shall be as specified herein and as specified on the applicable drawings.

3.4.1 Welders. Prior to assigning any welder to structural welding on the food sanitation center components to be furnished under this specification, the contractor shall provide the contracting officer or his authorized representative with the names of welders to be employed in the work, together with certification that each of these welders has passed qualification tests as prescribed by either of the following listed codes for the type of welding operation to be performed.

a. Standard Qualification Procedure of the American Welding Society

b. Welding Qualification of the American Society of Mechanical Engineers

3.5 Contractor furnished components. Each food sanitation center shall include the Contractor furnished components specified in 3.5.1 thru 3.5.9.

3.5.1 Sink adapter. Two adapters shall be provided with each sanitation center. The adapters shall conform to Drawing 5-13-4256.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:29Z
Check the source to verify that this is the current version before use.

3.5.2 Bracket, thermometer. Three thermometer brackets shall be provided with each sanitation center. The thermometer brackets shall conform to Drawing 5-13-4261.

3.5.3 Hose, drain. One three-sink drain hose assembly and a one-sink drain hose assembly shall be provided with each sanitation center. The three sink drain hose shall conform to Drawing 5-13-3749, and the one-sink drain hose shall conform to Drawing 5-13-4061.

3.5.4 Rack set, storage and drying. Two storage rack sets shall be provided with each sanitation center. Each set shall consist of three storage rack assemblies conforming to Drawing 5-13-4050.

3.5.5 Rack, sink immersion. Two sink immersion racks shall be provided with each sanitation center. The sink immersion racks shall conform to Drawing 5-13-4255.

3.5.6 Sink assembly. Three sink assemblies shall be provided with each sanitation center. The sinks shall conform to Drawing 5-13-4120 which consist of the sink body assembly, Drawing 5-13-4121; burner rack assembly, Drawing 5-13-3875; and base rack assembly, Drawing 5-13-3868. When tested as specified in 4.3.5, the sink body shall show no leakage of water.

3.5.7 Table, drain. One drain table shall be provided with each sanitation center. The drain table shall conform to Drawing 5-13-4240.

3.5.8 Table, field, 36 inches high. One field table shall be provided with each sanitation center. The field table shall conform to Drawing 5-13-4242.

3.5.9 Shelf. One shelf shall be provided with each sanitation center. The shelf shall conform to Drawings 5-13-4257, 5-13-4258, and 5-13-4262.

3.6 Government-furnished property (GFP). Each sanitation center shall include the Government-furnished property listed below (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:29Z
Check the source to verify that this is the current version before use.

Item No.	Description	Identification National Stock Number	Quantity
1.	Tent extendable, modular (16 by 20 foot, utility) MIL-T-44271	8340-01-185-2613	1
2.	Burner unit, M2A, conforming to MIL-B-40098	7310-01-113-9172	3
3.	Extinguisher, fire	4210-01-149-1356	1
4.	Lantern, gasoline, conforming to A-A-52078	6260-00-837-0996	2
5.	Thermometer, 5-1/2 inch, conforming to A-A-54520	6685-00-444-6500	3
6.	Waste receptacle, plastic, 32 gallon with lid, conforming to A-A-295	7240-00-151-6629	2
7.	TM-10-7360-211-13&P		1
8.	TM-10-7360-204-13&P		1
9.	TM-10-8340-224-13		1

3.7 Welding. The surfaces of parts for the components in 3.5.1 to 3.5.9 to be welded shall be free from oxide, scale, paint, grease, or other foreign matter. Welds shall have a smooth, regular bead, shall be uniform in cross section, and shall be free of pits, cracks, holes, undercuts, or incomplete fusion. All scale, flux, splatter, and rough surfaces shall be removed.

3.8 Fastening devices. Threaded fastener and rivet holes of the components in 3.5.1 to 3.5.9 shall have burrs removed, Threaded fasteners shall not be broken, cracked, or stripped and shall be securely torqued. Rivets shall fill the holes completely and the heads shall be in full contact with the surface of the riveted members.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:29Z
Check the source to verify that this is the current version before use.

3.9 Finish.

3.9.1 Surface finishing. The exterior surfaces of the sink, sink cover, base rack, and burner rack shall be cleaned, conditioned, primed and painted in accordance with type F or G of MIL-T-704, as applicable. Rough or sharp edges and corners, burrs, and slivers shall be removed prior to any painting. The base rack and burner rack shall be given a finish coat of chemical agent resistant paint conforming to green 383. The exterior surface of the sink and sink cover shall have a finish coat of heat resistant green 383 paint. This paint shall contain no lead or chromate. The paint shall be applied so that there will be no streaks, pinholes, cheeks, or cracks.

3.10 Workmanship. The components of the food sanitation center shall conform to the quality of product established by this specification.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2)
b. Conformance inspection (see 4.3)

4.2 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.3.3 and 4.3.4, and tested for the characteristic specified in 4.3.5. The presence of any defect or failure to pass any test shall be cause for rejection of the first article.

4.3 Conformance inspection. Conformance inspection shall include the examinations of 4.3.2.1, 4.3.2.1.1, 4.3.2.1.2, 4.3.3, 4.3.4, and the test of 4.3.5. Sampling for inspection shall be as specified in the contract or purchase order (see 6.2).

4.3.1 Component and material inspection. The components listed in 3.5.1 through 3.5.9 shall conform with the requirements of referenced documents.

4.3.2 In-process inspection. Inspection of components shall be made at any point or during any phase of the manufacturing process to determine whether dimensions which cannot be examined in the finished product are in accordance with specified requirements. Whenever nonconformance is noted, correction shall be made to the items affected, the lot in progress, and to the operation. Parts which cannot be corrected shall be removed from production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:29Z
Check the source to verify that this is the current version before use.

4.3.2.1 In-process inspection of welding. In lieu of inspecting welds in accordance with the following procedures, the contractor may propose to the Procuring Contracting Officer (PCO), alternative procedures for operator and equipment certification.

4.3.2.1.1 Spot welding. Spot welds shall be inspected in accordance with the peel test procedure listed below. The peel test shall verify minimum nugget size, as specified on the drawings, and complete bonding of the two metals. At least two sample welds shall be tested per production run using material identical to the applicable components specified in the sanitation center.

4.3.2.1.1.1 Peel test procedure. The weldment on simulated specimens shall be separated by driving a chisel, or like instrument, between the welded component in an unwelded area or by peeling one sheet back against the weld until failure occurs. Failure of the base metal outside the weld area shall be considered evidence that the welds are satisfactory.

4.3.2.1.2 Fusion welding. Fusion welding shall be inspected in accordance with the requirements of class C of MIL-STD-2219.

4.3.3 Component visual examination. The components and assemblies specified in 3.5.1 through 3.5.9 shall be examined in separate lots for the applicable defects listed in table I. The lot size shall be expressed in units of like components or assemblies. The sample unit shall be one component or assembly as applicable. The sample size shall be as specified in the contract or purchase order. Unless otherwise specified in the contract or purchase order, the finding of any major or minor defect shall be cause for rejection of the lot of components or assemblies.

TABLE I. Component visual defects

Examine	Defect	Classification Major	Minor
Material	Hole or crack in any component	101	
	Dent, bend, or other malformation in any component	102	
Finish	Material such as rust, dirt, oil or grease		201
	Rough tool, die, or grind mark		202
	Dent, scratch, or crack not affecting serviceability		203
	Dent, scratch or crack affecting serviceability	103	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:29Z
Check the source to verify that this is the current version before use.

TABLE I. Component visual defects, (cont'd)

Examine	Defect	Classification Major	Minor
	Burr or sliver which may inflict injury	104	
	Sharp edge or sharp corner	105	
	Burr on inside of holder of can opener	106	
	Finish on top of table or holder of can opener not as specified	107	
Painted surfaces	Color not as specified	108	
	Film not smooth or not uniform		204
	Area of no paint		205
	Painted surface contains run, streak, wrinkle, drop or grit		206
	Paint is peeling		207
Welding: Fusion	Missing, incomplete or incorrectly located square groove or fillet weld	109	
	Weld not of the specified type or size		208
	Irregular or non-uniform cross section of fillet weld bead		209
	Crack, burnhole, undercutting, or overlapping of weld		210
	Weld scale, flux, or splatter not removed		211
Spot	Cracks, tip pickup, pits or metal expulsion		212
Field table	Legs do not travel to, and lock in fully opened position, and close under no more than moderate hand pressure	110	
	Legs fold without releasing lock arm	111	
	Nut with washer is not tightly securing leg to table		213
	Lower edge of table is not fully rolled back	112	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:29Z
Check the source to verify that this is the current version before use.

TABLE I. Component visual defects, (cont'd)

Exammine	Defect	Classification Major	Minor
Components and assemblies	Any component or assembly missing, or not as specified, or not furnished in the quantity specified	113	
Any item provided by the Government as a GFP item	Missing or not as specified or not furnished in the quantity specified	114	

4.3.4 Component dimensional examination. The components and assemblies listed in table II shall be examined in separate lots for conformance to the dimensions specified in table II. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of like components or assemblies. The sample unit shall be one component or assembly, as applicable. The sample size shall be as specified in the contract or purchase order. Unless otherwise specified in the contract or purchase order the finding of any defect shall be cause for rejection of the lot of components or assemblies.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:29Z
Check the source to verify that this is the current version before use.

TABLE II. Component for dimensional examination 1/

Component	Examine
Sink adapter (Dwg. 5-13-4256)	All dimensions specified.
Bracket, thermometer (Dwg. 5-13-4261)	All dimensions specified.
Hose, drain (Dwgs. 5-13-3749 and 5-13-4061)	All dimensions specified.
Storage rack assembly (Dwg. 5-13-4050)	All dimensions specified.
Rack, sink immersion (Dwg. 5-13-4255)	All dimensions specified.
Sink body assembly (Dwg. 5-13-4121)	All dimensions specified.
Sink cover top assembly (Dwg. 5-13-4207)	All dimensions specified.
Burner rack assembly (Dwg. 5-13-3875)	All dimensions specified.
Base rack assembly (Dwg. 5-13-3868)	All dimensions specified.
Table, drain (Dwg. 5-13-4240) assemblies:	All dimensions specified, and those dimensions on the following sub- a. Drain table, top assy. (Dwg. 5-13-4241) b. Leg adapter assembly (Dwg. 5-13-4245-2)
Table, field, 36 inches high (Dwg. 5-13-4242) assemblies:	All dimensions specified. and those dimensions on the following sub- a. Table top assembly (Dwg. 5-13-4243) b. Leg mounting bracket assembly (Dwg. 5-13-4247-1) c. Leg adaptor assembly (Dwg. 5-13-4245-1)
Shelf (Dwg. 5-13-4257)	All dimensions specified.

1/ Only those dimensions that can be evaluated without damaging or disassembling the component shall be examined.

Source: https://assist.dla.mil -- Downloaded: 202640-22T01:29Z
Check the source to verify that this is the current version before use.

4.3.5 Sink testing. All sink assemblies shall be tested as follows: close the sink body assembly valve, fill the sink with tap water to within 2 inches of the top, let stand for 5 minutes, then observe the sink for any leakage. Evidence of leakage shall constitute a rejection of that sink body assembly.

5. PACKAGING

5.1 Packaging. Packaging requirements shall be as specified in the contract or purchase order.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The sanitation center is an assemblage of equipment that provides the capability of cleaning pots, pans and food service equipment associated with the combat field feeding system, and the modular field kitchen (MIL-K-44329), in basic, hot, cold, and severe cold climate conditions with shelter from the environment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2.1 and 2.3).
c. When a first article is required (see 3.1).
d. Source and delivery of government furnished property (see 3.6)
e. Sampling plan, lot size and sample size (see 4.3, 4.3.3 and 4.3.4)
f. Packaging requirements (see 5.1).

6.3 Government-furnished property. The contracting officer should arrange to furnish the property listed in 3.6.

6.4 Subject term (key word) listing.
Cleaning
Combat field feeding system
Sterilizing
Washing

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:29Z
Check the source to verify that this is the current version before use.

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - GL

Review activities:
Army - AV, MD, QM-1

Preparing activity:
Army - GL

(Project 7360-A177)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-F-44330A(GL)	95-01-13

3. DOCUMENT TITLE

FOOD SANITATION CENTER, FOR USE WITH FIELD KITCHENS

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON /DSN
U.S. Army Natick RD&E Center	508-651-5175	256- 5175
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SATNC- WEF Natick, MA 01760-5018	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 NATICK OPl, JUL 91 *Previous editions are obsolete.*

198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:29Z
Check the source to verify that this is the current version before use.