INCH-POUND

MIL-S-44309B
5 September 1991
SUPERSEDING
MIL-S-44309A
27 April 1988

MILITARY SPECIFICATION

SLEEPING BAGS, FOR SLEEPING SYSTEMS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers sleeping bags for use as part of the extreme and intermediate cold weather sleeping systems.

1.2 Classification. The sleeping bags shall be of the following types as specified (see 6.2).

Type I - Extreme Cold Weather Sleeping Bag
Type II - Intermediate Cold Weather Sleeping Bag

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5019 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

V-F-106 - Fastener, Slide, Interlocking
DDD-L-20 - Label: For Clothing, Equipage and Tentage, (General Use)
PPP-B-636 - Boxes, Shipping, Fiberboard

MILITARY

MIL-L-35078 - Loads, Unit; Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage: General Specification For

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

2-2-433 - Sleeping Bag, Extreme Cold Weather Sleeping System
2-2-501 - Sleeping Bag, Intermediate Cold Weather Sleeping System

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-UX, Natick, MA 01760-5017.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

3.2 Guide samples. Samples, when furnished, are solely for guidance and information to the contractor (see 6.4). Variations from this specification may appear in the sample in which case this specification shall govern.

3.3 Materials. The materials shall be as specified herein and on Drawing 2-2-433 and 2-2-501 and all subsidiary drawings and parts lists pertaining thereto. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3.1 Labels and markings. The direct marking and label for the instructions for use and maintenance, laundry instructions, and identification shall conform to DDD-L-20 in the types and classes specified. The sewn label shall be one continuous length with the identification printed first, use and maintenance second, and laundry instructions last. The width of the label shall be no more than 5 inches and the length shall be governed by the contents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.

3.3.1.1 Marking. The marking "US" shall be applied to the sleeping bag per Drawing 2-2-433 or Drawing 2-2-501, as applicable, and shall conform to type III or IV, class 9 in solid black letters 2 inches high minimum. In addition, the following markings conforming to type III or IV, class 2 shall be applied per Drawing 2-2-433 or Drawing 2-2-501, as applicable, in characters 1/2 inch high minimum:

INTERMEDIATE COLD WEATHER
or
EXTREME COLD WEATHER

The words "Extreme Cold Weather" or "Intermediate Cold Weather" shall not be abbreviated. The fastness of the class 9 markings shall be as specified for class 5 labels.

3.3.1.2 Identification and instruction and maintenance label. The label shall conform to Drawings 2-2-433 and 2-2-501 for ECWSS and ICWSS respectively and the instructions for each shall be as follows:

INSTRUCTIONS FOR USE

1. To keep the bag dry:

a. The outside cover (bivy cover) of the sleeping bag is water repellent and will protect against moisture. Select the driest ground and if possible keep the bag out of the rain.

b. Breathe through face opening to prevent moisture from wetting the bag. If face is cold, reduce face opening by pulling drawstrings at head end. DO NOT TIE DRAWSTRINGS.

c. AVOID sweating in bag. If too warm, adjust clothing layers.

d. Open the bag completely and air thoroughly each day.

e. Use the mattress under bag to protect from ground moisture.

2. To keep warm:

a. FLUFF BAG thoroughly before using.

b. Wear clean dry winter underwear and sleeping socks in the bag. Additional layers of the Extreme Cold Weather Clothing System may be worn in the bag for added warmth.

3. To keep bag clean:

a. ALWAYS wear sleeping hood in bag.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.

b. Brush and clean clothing before entering bag.

c. Remove dirt and grease from sleeping bag by spot-cleaning with a damp cloth and soap.

4. Slide fastener closure:

To close bag, keep both sides of slide fastener close together before pulling webbing loop on slider. For EMERGENCY EXIT, grasp each side of the opening above the slider and spread apart quickly forcing the slider downward.

NOTE: If chain separates below slider, pull slider down beyond separation, then pull up to reclose chain.

5. Snap fastener closure:

Use the snap fastener flap closure ONLY when the slide fastener fails. Close the bag by snapping the male and female parts together. For EMERGENCY EXIT, grasp each side of the opening above the snap and spread apart quickly.

6. DO NOT smoke in sleeping bag.

7. Maintenance:

Repair bag in accordance with D/A TM 10-8400-203-23.

8. Do not store bag in stuff sack for long periods of time. Store in cool dry place out of direct sunlight.

3.3.1.3 Laundry instruction. The laundry instruction labels shall conform to type IV, class 3. The size of the print shall be not less than 3/32 to 1/8 inch in height. All words shown in capital letters shall be 3/16 inch minimum. The laundry instructions shall be as follows:

POLYESTER FILLED

Launder in accordance with formula 2 of D/A FM 10-280. DO NOT DRY CLEAN.

CAUTION - DRYING TEMPERATURE MUST BE BELOW 130°F.

3.3.2 Slide fastener. The slide fastener for the type I and type II sleeping bags shall conform to type III, style 1, size MHS, Black or OD-7 of V-F-106. The slide fastener tape shall be 1 ± 1/16 inch wide, dyed to match Olive Drab 7, S.A. 66519, or black and treated with a durable water repellent. The slide fastener shall be polyester continuous element, with the exception that the slider on chain initial operation force shall be not

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.

more than 22.9 ounces. The operating force after salt spray shall not apply. The fastener shall have a reversible double-pull, non-locking slider with wire stirrup pulls and thongs attached. Continuous chain application shall be acceptable.

3.4 Design and construction. The design and construction of the sleeping bag shall be as specified herein and as shown on Drawing 2-2-433 or Drawing 2-2-501 and all subsidiary drawings and parts lists pertaining thereto.

3.4.1 Stitches, seams, and stitching. All stitches, seams, and stitching shall conform to FED-STD-751. The type of seam and stitching and stitches per inch shall be as shown on Drawing 2-2-433, Drawing 2-2-501, and subsidiary drawings and parts lists pertaining thereto. Seam allowances shall be maintained with seams sewn so that no raw edges, run-offs, twists, pleats, puckers, or open seams occur. Overedge stitching shall be 3/16 to 1/4 inch gauge.

3.4.1.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched not less than 1/2 inch except where ends are turned under or caught in other seams or stitching. Ends of continuous line of stitching shall be overlapped not less than 1/2 inch. Thread tensions shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be imbedded in the materials sewn.

3.4.1.1.1 Repairs of type 301 stitching.

a. When thread breaks, skipped stitches, run-offs, or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch back of the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area, continue over the defective area, and continue a minimum of 1 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.4.1.2 Types 503, 504, 515, 516, and 401 stitching. All repairs shall be in accordance with 3.4.1.1.1a. and b. Thread tension shall be maintained so that there will be no loose or excessively tight stitching resulting in puckering of the materials sewn. Repairs to stitch type 401 may be accomplished by use of stitch type 301. Both ends of all seams and stitching produced with the 401 stitch type when not caught in other seams or stitching shall have a 1/2 inch minimum chain extending beyond each end.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.

3.4.1.3 Bartacks. Unless otherwise specified, all bartacks shall be 1/2 ± 1/16 inch long and 1/8 ± 1/32 inch wide, and shall contain 28 stitches. Bartacking shall be free from thread breaks and loose stitching.

3.4.1.4 Thread ends. All thread ends shall be trimmed to 1/4 inch maximum length.

3.4.1.5 Panel repair. For the front and back panel outer and inner joining seam, one repair may be made to each sleeping bag to repair an open seam that is 3 inches or less in length. The open seam shall be repaired using seam type SSc-1, stitch type 301, size 50-2 thread with 10 to 14 stitches per inch. The stitching shall start and stop a minimum of 1 inch beyond the ends of the open seam.

3.4.2 Setting snap fasteners. A hole shall be prepunched through the materials before inserting the male or female part of the snap fasteners. The hole punched before inserting the male or female part of the snap fastener shall be smaller than the outside diameter of the fastener barrel so that the barrel must be forced through the hole. The fasteners shall be securely clinched without cutting the adjacent material and no more than three splits shall occur in the button or eyelet barrels.

3.4.3 Automatic stitching. Automatic stitching machines may be used to perform any of the required stitch patterns provided the requirements for the stitch pattern, stitches per inch, size and type of thread are met, and at least three or more tying, overlapping or back stitches are used to secure the ends of the stitching.

3.5 Finished measurements. The sleeping bag shall conform to the following measurements:

Area to be measured	Measurement inches	Tolerance inches
Length 1/	78	± 1-1/2
Widest width 2/	36	± 1
Narrowest width 3/	12	+ 1-1/2 - 1/2
Hood length 4/	15	± 3/4

1/ With the two drawstrings totally loosened and the slide fastener fully closed, place the sleeping bag face up on a flat surface. With the bag in this position, measure length in a straight line from the drawstring tunnel seam to the foot piece seam.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.

2/ With the sleeping bag positioned as indicated at footnote 1/, measure across the width of the sleeping bag at its widest point from top slide fastener seam across first batting stitch line to side seam.

3/ With the sleeping bag positioned as indicated in footnote 1/, measure horizontally across the bottom of the foot piece along the stitchline that divides the foot piece evenly and holds the insulation to the foot piece from the right side seam to the left side seam.

4/ With hood relaxed open, measure from top of tunnel to hood joining seam.

3.6 Workmanship. The finished sleeping bag shall conform to the quality of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality level.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1.3 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such test items to determine the validity of the certification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.2 and 4.4.3. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Certification. The contractor shall furnish a certificate of compliance for the barrel lock requirements specified in Drawing 2-2-433, Drawing 2-2-501 and all subsidiary drawings.

4.4.2 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of sleeping bags. The sample unit shall be one sleeping bag. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 15.0 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Fabric	Hole, cut, or tear	101	
	Any abrasion mark, smash, large slub, broken or missing yarn, multiple float, or open place, clearly visible at normal inspection distance	102	
	Fine or coarse filling bar		201
	Any mend, darn, patch, or unauthorized splice	103	
	Needle chews	104	
	NOTE: Needle holes visible as the result of broken or skipped stitching or stitching that has been removed shall not be considered as needle chews providing that the holes are spaced as in normal stitching.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine		Defect	Classification Major	Minor
Webbing and tape		Cut or frayed edge	105	
		Not firmly and tightly woven		202
		Needle chews:		
		- up to 1/8 inch in length		203
		- over 1/8 inch in length	106	
Panel repair		More than one repair to front and back outer and inner joining seam	107	
Open seams:	NOTE:	A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or run-off stitches occur. On double-stitched seams, a seam shall be considered open when either one or both sides of the seam are open.		
		1/2 inch or less		204
		More than 1/2 inch	108	
		Any open seam on both rows of double stitched seam	109	
Raw edges (when securely caught in stitching):				
Along face and front opening		1/2 inch or more		205
On all other parts of bag		1 inch or more		206
	NOTE:	Raw edges not securely caught in stitching shall be classified as open seams.		
Seam and stitch type		Wrong seam or stitch type	110	
Stitching		Loose tension, resulting in a loose top or bottom thread		207
		Excessively tight tension resulting in puckering of material		208

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Stitching (cont'd)			
	NOTE: Defects to be scored only when the condition exists for 4 inches or more or in several areas with an accumulated distance of 8 inches or more. Applicable to individual seams.		
	Stitching ends and breaks not backstitched or not overstitched as specified		209
Stitches per inch	One to two less than minimum specified		210
	Three or more less than minimum specified	111	
	One or more in excess of maximum specified		211
Cleanness	Spots or stains, clearly noticeable; thread ends not trimmed as specified		212
Face opening	Binding twisted or pleated, causing excessive puckering or pleats at face opening		213
	Ends of binding not finished as specified		214
	Free ends of drawstrings not knotted or any end not seared		215
	Ends of drawstrings not secured as specified		216
Snap fasteners, general	Not specified style	112	
	Finish omitted or not as specified		217
	One or more omitted, broken or malformed failing to serve intended purpose; burrs; or sharp edges	113	
	Insecurely clinched to a degree that one or more fasteners may be detached from flap or tape; one or more excessively clinched cutting adjacent material		218

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Snap fasteners, general (cont'd)	Four or more splits in button or eyelet barrel		219
	Edge of male snap fastener projects more than 1/16 inch beyond edge of webbing	114	
Slide fastener	Not specified type or size	115	
	Does not provide a smooth and secure closure full length of bag opening	116	
	Slider jams or fails to interlock chain scoops	117	
	Any portion of fastener broken, bent, missing, or not aligned making fastener unusable	118	
	Fastener tape width not as specified	119	
	Color not as specified		220
	Fastener tape not 1 inch wide	120	
	Slider not double pull, not furnished with two stirrup pulls, or stirrup pulls not made out of wire	121	
	Thong(s) omitted	122	
	Chain not plastic or not of the configuration specified	123	
NOTE:	The slide fastener shall be fully closed and opened to determine whether fastener operates smoothly and provides a secure closure.		
Slide fastener - weatherstrip and flap assembly	Stitching too close to chain, preventing slider from sliding freely	124	
	Top end of fastener guard strip not fully and securely caught in face opening binding	125	
	End at bottom end not turned under		221
	Ends of foundation strip at bottom end of fastener assembly not folded and stitched		222
	Bartacks at bottom of assembly do not pass through reinforcement tape	126	
	Weatherstrip placed on right side in lieu of left side of front opening		223

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Slide fastener - weatherstrip and flap assembly (cont'd)	Top end of weatherstrip not fully caught in binding of face opening		224
	Batting not tucked in when closing weatherstrip or flap along side and ends for a distance of 1/2 inch or more		225
	Tube portion of weatherstrip caught in slide fastener assembly stitching		226
	Not assembled as specified		227
Labels and markings	Omitted or incorrect	127	
	Not positioned as specified		228
Drawcord	Any drawcord caught in stitching restricting use of drawcord	128	
	Any end not heat sealed		229
	Any drawcord omitted	129	
	Any end not knotted and having a barrel lock		230
	Any drawcord insufficient in length	130	

4.4.3 End item dimensional examination. The end items shall be examined for the finished dimensions specified in 3.5. Any dimension not within the specified tolerances shall be scored as a defect. The lot size shall be expressed in units of sleeping bags. The sample unit shall be one sleeping bag. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.4.4 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and unit pack)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.

Workmanship	Inadequate application of components, such as: incomplete closure of container flap, loose strapping, improper taping, or inadequate stapling. Bulged or distorted container. Open or noncontinuous heat-sealed seams and closures of polyethylene bags. Incorrectly fabricated polyethylene bag.
Content	Number per container is more or less than required.

4.4.5 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Load not bonded as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted, incorrect, illegible, of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Each type I or type II sleeping bag with the slide fastener closed shall be rolled to measure approximately 27 inches in length and 10 inches in width and secured.

5.1.2 Commercial. The type I or type II sleeping bags shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. One type I or one type II sleeping bag, preserved as specified in 5.1, shall be packed in a top-opening or end-opening shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The flutes of the box and liner shall run parallel to the score line of the opening of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.

box (see PPP-B-636, figure 2) and the height of the liner shall be full inside width of the box. Inside dimensions of the box shall be approximately 27 inches in length, 10 inches in width, and 10 inches in depth. The inside of each container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15C of PPP-B-636. Each box shall be closed, waterproofed, and reinforced in accordance with the appendix of PPP-B-636. Boxes shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. One type I or one type II sleeping bag, preserved as specified in 5.1, shall be packed in a shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275, end-opening box of PPP-B-636. The flutes of the box and liner shall run parallel to score line of the opening of the box (see PPP-B-636, figure 2) and the height of the liner shall be the full inside width of the box. Inside dimensions of the box shall be approximately 27 inches in length, 10 inches in width, and 10 inches in depth. The inside of each box shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Each box shall be closed in accordance with method II as speciifed in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4.

5.2.2.1 Weather-resistant shipping container. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4.

5.2.3 Commercial packing. Type I or type II sleeping bags, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), type I or type II sleeping bags, packed as specified in 5.2.2 or 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be number 35 for both type I and type II sleeping bags in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers and unit load shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.

6.1 Intended use. The sleeping bags are intended for use by personnel of the Department of Defense as component of the Extreme and Intermediate Cold Weather Sleeping Systems.

6.2 Acquisition requirements. Acquisition requirements must specify the following:

a. Title, number, and date of this specification.
b. Type required (see 1.2).
c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1, 2.1.2 and 2.2).
d. When a first article is required (see 3.1, 4.3 and 6.3).
e. Levels of preservation and packing (see 5.1 and 5.2).
f. Type and class of unit load required (see 5.2.1).
g. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
h. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.4 Samples. For access to samples, address the contracting activity issuing the invitation for bids or request for proposal.

6.5 Subject term (key word) listing.

Bivy
ECWSS
Extreme cold weather
ICWSS
Intermediate cold weather

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - MD
Navy - MC
Air Force - 82
DLA - CT

User activity:

Air Force - 45

Preparing activity:

Army - GL

(Project 8465-0075)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.

travel over snow and ice covered terrain. The crawlers shall be manufa

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-S-44309B	1991 September 5

3. DOCUMENT TITLE

SLEEPING BAGS, FOR SLEEPING SYSTEMS

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U.S. Army Natick RD&E Center	(1) Commercial 508-651-4532	(2) AUTOVON/DSN 256-4532
ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: STRNC-IRT Natick, MA 01760-5019	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:21Z
Check the source to verify that this is the current version before use.