INCH-POUND

MIL-V-44323A
AMENDMENT-1
31 January 1989

MILITARY SPECIFICATION

VEST, TACTICAL LOAD BEARING

This amendment forms a part of MIL-V-44323A, dated 27 April 1988, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 5

3.5, lines 1 and 2: Delete first sentence.

Add the following new paragraph:

"3.5.1 Label. A combination identification/instruction label shall be applied in the location shown on Drawing 2-1-1997 and shall conform to type VI, class 15 of DDD-L-20. The label color shall be Medium Green, Cable No. 70034, 70130, or 70131. Special instructions on the label shall read:

Hand Washing:

1. Scrape dirt/dust from item using a brush or flat stick which will not cut fabric/webbing.

2. Wash item in a pail of warm water by using mild detergent or soap.

3. Rinse "thoroughly" in clean warm water.

4. DO NOT USE CHLORINE BLEACH, YELLOW SOAP, CLEANING FLUIDS OR SOLVENTS - WILL DISCOLOR/DETERIORATE THE ITEM.

5. Dry item in shade or indoors.

6. DO NOT DRY IN DIRECT SUNLIGHT, DIRECT HEAT OR OPEN FLAME."

Add the following new paragraph:

"3.6.1 Component marking and cutting. The component parts of the vest shall be cut, marked, or bundled to unsure uniform size and shade throughout the item. The following marking methods shall not be used:

1. Corrosive metal fastening devices.

2. Sew-on type tickets.

3. Adhesive type tickets which leave an impression or traces of paper or adhesive on the material upon removal of the tickets."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:26Z
Check the source to verify that this is the current version before use.

PAGE 9

Table I: Delete last defect for "Brass grommets and eyelets" and substitute:

Defect	Classification Major	Minor
"Eyelet or button barrel splits		
- more than two		X
- more than four	X"	

PAGE 12

Table I, in line 2 of second defect for "Location markings": Delete "or" and substitute "and".

PAGE 14

4.4.5, in the first line of the second "NOTE:": Delete the word "six".

PAGE 15

4.4.5: Add the following new "Examination" and "Defect"

"Fit of equipment belt into belt loops.	With the vest placed flat on a table, camouflage side up, place the equipment belt between the two portions of the ten belt loops. First fold each upper portion under the belt to secure the hook and pile fasteners. Next, fold each lower loop up to join the snap fasteners. The hook and pile and snap fasteners shall meet and allow the belt to fit into the loops with enough ease to allow freedom of movement."

Custodians:
Army - GL
Navy - NU
Air Force - 99

Review activities:
Army - MD
Navy - MC
Air Force - 82
DLA - CT

Preparing activity:
Army - GL

(Project 8415-0699)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:26Z
Check the source to verify that this is the current version before use.