MIL-L-655B
29 JANUARY 1965
SUPERSEDING
MIL-L-655A
20 JUNE 1960

MILITARY SPECIFICATION

LIPSTICK, ANTICHAP AND SUNBURN PROTECTIVE

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers an unpigmented lipstick with antichapping and sunburn-protective properties (see 6.1).

1.2 Classification. The lipsticks covered under this specification shall be of the following types as specified: (see 6.2)

Type I — Cold climate.
Type II — Hot climate.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-636 — Box, Fiberboard.
PPP-B-676 — Boxes, Set-Up, Paperboard.

STANDARDS

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 — Marking for Shipment and Storage.

(Copies of specifications, standards, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publication. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

DEPARTMENT OF HEALTH, EDUCATION AND WELFARE

Federal Food, Drug, and Cosmetic Act and General Regulations for its Enforcement.

(Application for copies should be addressed to the Superintendent of Documents, U. S. Government Printing Office, Washington-25, D. C.).

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

FSC 8510

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:11Z
Check the source to verify that this is the current version before use.

* **3.1 Formulation approval.** Unless otherwise specified (see 6.2), the bidder shall submit with his bid a statement of the composition of the lipstick formulation which he proposes to furnish for approval by the contracting officer. All ingredients shall be identified by chemical name and grade and the percentage by weight of each stated.

* **3.2 Preproduction sample.** When specified (see 6.2), before production is commenced, a sample of ten (10) lipsticks of the type to be furnished, shall be submitted or made ready for the contracting officer or his authorized representative for inspection as specified in 4.2. The approval of the preproduction sample authorizes the commencement of production but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured by the supplier in the same facilities to be used for the manufacture of the production items.

* **3.3 Materials.** Ingredients used in the manufacture of the lipstick shall conform to the requirements of the Federal Food, Drug, and Cosmetic Act. A certificate of compliance covering the foregoing shall be furnished to the contracting officer.

3.4 Construction. The lipstick shall consist of the unpigmented antichap and sunburn protective formulation formed into a cylindrical stick and encased in the dispenser described in 3.11.

3.5 Composition. Lipsticks shall conform to the composition submitted with the invitation for bid, unless written authorization for variation therefrom is received from the contracting officer. For each production lot, the supplier shall furnish a certificate of compliance covering the foregoing requirement.

3.5.1 *Types.* Type I and type II lipsticks shall be of such composition as to comply with requirements of 3.9.1 and 3.9.2 respectively.

3.6 Odor and taste. The lipstick formulation shall not have a strong or objectionable odor or taste and these characteristics shall not change after the test specified in 4.5.2.

* **3.7 Weight.** The weight of the useable lipstick shall not be less than 4.75 grams when tested as specified in 4.5.3.

3.8 Ultraviolet light transmission. The lipstick when tested as specified in 4.5.1 shall show an ultraviolet light transmission (wavelength 2900 to 3150 Angstrom units) not greater than 5 percent for a film thickness of 0.002 inch.

3.9 Stability.

3.9.1 *Low temperature stability.* There shall be no visible separation of ingredients of the lipstick when tested as specified in 4.5.2.

3.9.2 *High temperature stability.* There shall be no rancidity or visible separation of ingredients of the lipstick when tested as specified in 4.5.2.

3.10 Application. The lipstick formulation shall apply easily and evenly to the lips without breaking or crumbling or cause lip discomfort before and after the conditioning and application specified in 4.5.2.

* **3.11 Dispenser.** The lipstick shall be packaged in a cylindrical commercial screw-type dispenser with a snug-fitting, slipcover style closure. The dispenser shall be so constructed that the lipstick can be advanced or retracted into the container body by turning an external knurled knob. The dispenser top, body, lipstick holder, and screw mechanism may be made of either plastic or metal. Metal containers shall have a smooth uniform exterior coating. The over-all dispenser dimensions shall be 2.7 ± 0.2 inch in length by 0.60 ± 0.02 inch in diameter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:11Z
Check the source to verify that this is the current version before use.

3.12 Marking. Each dispenser shall be legibly and neatly marked with the name of the item, the type and the name of the manufacturer or supplier. There shall be no commercial advertising on the dispenser.

3.13 Workmanship. Lipsticks shall be clean, smooth, homogeneous and well-formed. The dispensers shall operate freely and the covers shall fit snugly. Exterior coatings of the dispensers shall be free from runs, sags and wrinkles.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Preproduction sample inspection. When a preproduction sample is specified, it shall be examined for the defects in 4.4.1.1 and 4.4.1.2 and tested in accordance with 4.4.2. Two copies of the supplier's certified test report containing complete test result data, also a complete description and percentage of the materials used in the formulation of the finished product, with the additional provision that the ingredient materials used are nonirritant and nontoxic in the proportions used in the manufacture of the end product, shall be submitted with the preproduction sample.

4.3 Inspection. Sampling for inspection shall be in accordance with the provisions of MIL–STD–105, except where otherwise indicated.

* **4.3.1** *Inspection of components and materials.* The supplier is responsible for insuring that all components and materials used were manufactured and inspected in accordance with the requirements of this specification and of referenced specifications.

4.4 Inspection of the end item.

* **4.4.1** *Examination of the end item.* The end item shall be examined for the defects in the applicable sub-paragraphs at the inspection levels and acceptable quality levels (AQLs) set forth in 4.4.1.4. The lot size, for purpose of determining the sample size in accordance with MIL–STD–105 shall be expressed in units of lipsticks with dispensers for examination in 4.4.1.1 and 4.4.1.2 and in units of shipping containers for examination in 4.4.1.3.

* **4.4.1.1** *Examination of the end product for defects in appearance, construction and workmanship.* The sample unit for this examination shall be one complete lipstick, with dispenser.

Examine	Defect
Lipstick	Form, color, cleanliness, and appearance do not compare favorably with approved sample.
	Not cylindrical in shape, not smooth.
	Evidence of pigmentation or dirt.
	Breaks; visible separation of ingredients.
	Objectionable odor or taste.
Dispenser	Not cylindrical, not metal or plastic, not screw-type. Not commercial type.
	Lipstick cannot be advanced or retracted fully into the container by turning the knurled knob.
	Cover does not fit snugly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:11Z
Check the source to verify that this is the current version before use.

Examine	Defect
Exterior coating	Color not uniform. Not smooth.
	Coating runs, sags or wrinkles.
Labeling of dispenser	Not legible or neat.
	Name of item missing.
	Name of manufacturer or supplier missing.
	Type not indicated.
	Presence of commercial advertising.

* 4.4.1.2 *Examination of the end product for dimensional defects.* The sample unit for this examination shall be one lipstick, with dispenser.

Examine	Defect
Dimensions:	
Dispenser	Diameter not 0.60 ± 0.02 inches.
	Length not 2.7 ± 0.2 inches.
Weight of lipstick	Net weight of lipstick less than 4.75 grams.

* 4.4.1.3 *Examination of the packaged end product for defects in packaging, packing, and marking.* The sample unit for this examination shall be one shipping container.

Examine	Defect
Packaging	Mixed types in unit package.
	Not packaged in units of 100 each per box; not snug fitted.
	Unit packages not as specified.
	Closures not accomplished by specified or required methods or materials.
Packing	Not as specified.
	Number of unit containers not as specified.
	Mixed types in same container.
	Unit containers not snugly packed.
	Liner material (as applicable) missing or not as specified.
	Container material not as specified.
	Closures not accomplished by specified or required methods or materials.
Markings	Illegible, incorrect, incomplete, omitted, or not in accordance with contract requirements.

4.4.1.4 *Inspection levels and acceptable quality levels (AQLs) for examinations.* The inspection levels, for determining the sample size, and the acceptable quality levels (AQLs) expressed in defects per 100 units, shall be as follows:

Examination paragraph	Inspection level	AQLs
4.4.1.1	S-4	2.5
4.4.1.2	S-2	2.5
4.4.1.3	S-2	2.5

* 4.4.2 *Testing of the end item.* The end item shall be tested for the characteristics specified in Section 3 in accordance with test methods specified in table I. The lot size for test purposes shall be the number of units of complete lipsticks, with dispensers, of the specified type, submitted for inspection at one time. The sample unit shall be eight complete lipsticks with dispensers, Each sample unit shall be selected at random throughout the lot. The sample size for tests shall be as indicated below. The lot shall be unacceptable if there is any failure of any sample unit to meet any characteristic applicable to the sample unit.

Lot size	*Sample size*
800 or less	2
801 to 22,000	3
22,001 or more	5

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:11Z
Check the source to verify that this is the current version before use.

TABLE I. *Instructions for Testing of the End Item*

Characteristic	Specification reference		Requirements Applicable to		Number determinations per unit	Results reported as		Inspect level	AQL
	Requirement	Test method	Individ. unit	Lot aver.		Pass or fail	Numerically to nearest		
Ultraviolet transmission, percent	3.8	4.5.1	X		Average of 2		1.0		
Stability and application:									
Low temperature exposure	3.9	4.5.2	X		1	X			
High temperature exposure	3.9	4.5.2	X		1	X			
Weight, grams	3.7	4.5.3	X		Average of 2		0.1		

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:11Z
Check the source to verify that this is the current version before use.

4.5 Test procedures.

4.5.1 *Ultraviolet light transmission.* A Beckman spectrophotometer or other suitable instrument which will indicate accurate transmission results in the range specified, shall be used. The specified thickness of the lipstick 0.050 ± 0.005 mm. shall be examined in this instrument and a transmission curve shall be plotted for every 100 Angstrom units in the specified region (2900 to 3150 Angstrom units).

4.5.2 *Stability and application.* With dispenser cap in place, sample lipsticks shall be exposed to the temperature specified herein for the applicable type for a period of 7 days. After exposure they shall be allowed to return to room temperature and then examined for evidence of the applicable types of deterioration specified in 3.9. After examination, apply to the lips and note the ease, evenness, and comfort of application and any fracture of the stick. Note also taste and odor. A fresh sample lipstick shall be used for each exposure.

4.5.2.1 *Low temperature exposure (refrigerated space).*

Type I — minus 20° ± 2°F.
Type II — 50° ± 2°F.

4.5.2.2 *High temperature exposure (oven).*

Type I — 120° ± 2°F.
Type II — 145° ± 2°F.

4.5.3 *Weight of useable lipstick.* The useable weight of lipstick shall be determined by weighing that portion of the lipstick that can be cut off cleanly at the outlet top of the dispenser after full extension of the screw mechanism.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

* 5.1.1 *Level A.* One hundred lipsticks of one type only complete with dispenser shall be packaged on end 10 in length and 10 in width in a snug-fitting two-piece full telescope set-up box conforming to type I, class C, style 4 of PPP–B–676. Box closure shall be in accordance with the appendix of the box specification.

5.1.2 *Level C.* Lipsticks shall be packaged in accordance with the industry's practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 *Level A.* Two thousand lipsticks of one type only, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to V3c or V3s, style RSC of PPP–B–636. Each shipping container shall be closed, waterproofed by means of tape and reinforced with flat steel strapping or tape banding in accordance with the appendix of the container specification.

5.2.2 *Level B.* Two thousand lipsticks of one type only, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF or SF, class domestic, variety optional, grade 275 of PPP–B–636. Closure shall be in accordance with the appendix of the container specification.

* 5.2.3 *Level C.* Lipsticks packaged as specified in 5.1 shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Container shall be in accordance with rules or regulations of carrier applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL–STD–129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:11Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. Lipsticks covered by this specification are intended for use in prevention of chapped or sunburned lips in both hot and cold climates.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.

(b) Type required.

(c) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

(d) Whether statement of composition is waived with bid submission (see 3.1).

(e) Whether a preproduction sample is required (see 3.2).

6.3 Notations. The outside margins of this document have been marked to indicate where changes from the previous issue have been made. An asterisk (*) indicates a substantive change in the paragraph text. The sign (#) indicates the addition of a completely new paragraph. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content as written, irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army—GL
Navy—SA
Air Force—67

Review activities:
Army—GL, MD
Navy—SA, MS
Air Force—67, 11

User activities:
Army—SM
Navy—MC
Air Force—26

Preparing activity:
Army—GL
Project No. 8510-0010

Review and User information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current Federal Supply Classification Listing Of DOD Documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:11Z
Check the source to verify that this is the current version before use.

"to detach this form, cut along this line"

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

Lipstick, Antichap and Sunburn Protective - MIL-L-655B

ORGANIZATION	CITY AND STATE	
CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:11Z
Check the source to verify that this is the current version before use.