MIL-B-2378H
20 May 1985
SUPERSEDING
MIL-B-2378G
18 March 1980

MILITARY SPECIFICATION

BAG, BARRACKS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers the requirements for one type and size, olive green, cotton sateen barracks bag with drawstring closure.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

V-T-285	-	Thread, Polyester
UU-P-268	-	Paper, Kraft, Wrapping
DDD-L-20	-	Label: For Clothing, Equipage, and Tentage (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S.Army Natick Research and Development Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8465

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-B-371 - Braid, Textile, Tubular
MIL-C-10296 - Cloth, Sateen, Cotton
MIL-G-16491 - Grommet, Metallic

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

DRAWING

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

2-3-2 - Bag, Barracks

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

COLOR ASSOCIATION OF THE UNITED STATES, INC.

Department of Defense Standards Shades for Sewing Threads

(Application for copies should be addressed to the Color Association of the United States, Inc., East 38th Street, New York, NY 10016.)

AMERICAN ASSOCIATION OF TEXTILE CHEMISTS AND COLORISTS (AATCC)

Chromatic Transference Scale

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Association of Textile Chemists and Colorists, P.O. Box 12215 Research Triangle Park, NC 27709.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Guide samples. Samples, when furnished, are solely for guidance and information to the contractor (see 6.3). Variations from this document may appear in the sample, in which case this document shall govern.

3.1.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.4).

3.2 Materials (see 6.5).

3.2.1 Cloth, sateen, cotton. The cloth shall conform to class 1 of MIL-C-10296, color Olive Green 107.

3.2.2 Thread, polyester. The thread for all stitching shall conform to type I, class 1, sub-class A or sub-class B, size E of V-T-285. The thread shall be dyed Olive Drab S-1 (C.A. 66022) and shall show fastness to laundering equal to or better than the standard sample (see 6.3). If no standard sample is available the thread shall show good fastness to laundering.

3.2.3 Braid, tubular, cotton. The cotton braid shall conform to type V, class 1 of MIL-B-371.

3.2.4 Grommets. The grommets shall conform to type III, class 3, size No. 1 of MIL-G-16491.

* 3.3 Construction. The construction shall conform in all respects to Drawing 2-3-2 and shall be as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.

3.3.1 Stitches, seams and stitchings. All stitching, except bartacking, shall conform to FED-STD-751 as follows:

For all stitching except optional stitching indicated by "Z" on drawing:
- Type 301, 8 to 10 stitches per inch.

For optional stitching indicated by "Z" on drawing:
- Type 401, 8 to 10 stitches per inch. Chain portion of stitching shall not appear on outside of bag.

3.3.1.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched 1 inch minimum except where ends are turned under or caught in other seams or stitching. Thread tension shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread, or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be embedded in the materials sewn.

3.3.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch back of the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area, continue over the defective area, and continue a minimum or 1 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.3.1.2 Type 401 stitching. Ends of type 401 stitching not caught in other seams or stitching shall have a 1/2 inch minimum chain extending beyond the edge of the fabric. Thread tension shall be maintained so that there will be no loose stitching. All repairs shall be in accordance with 3.3.11.1.a and 3.3.1.1.1b.

3.3.1.3 Bartacking. Bartacking shall be 3/4 ± 1/16 inch in length, 1/8 ± 1/32 inch in width, and shall contain not less than 42 stitches. Bartacking shall be free of thread breaks, skipped stitching, and loose stitching.

3.3.1.4 Automatic stitching. Automatic stitching may be used to perform any of the required stitch patterns provide the requirements for the stitch pattern, stitches per inch, and size and type of thread are met; and at least three tying, overlapping or backstitches are used to secure the ends of the stitching.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.

3.3.1.5 Thread ends. All thread ends shall be trimmed to a length of not more than 1/4 inch.

3.3.2 Setting of grommets. Holes punched to receive the grommets shall be smaller than the outside diameter of grommet barrels so that the barrels must be forced through the holes. The grommets shall be securely clinched in a manner that will prevent detachment from, or cutting of, the surrounding material.

3.3.3 Repairs. Repairing the barracks bag by mending, patching or darning is not allowed.

3.3.4 Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects or damages that are classified as defects in 4.4.3 shall be removed from production and replaced with non-defective and properly matched components.

3.4 Marking. The identification marking shall be applied in the location shown on Drawing 2-3-2 and shall conform to type IV, class 5 of DDD-L-20. The letters "US" shall be applied in the size characters and in the location indicated on the drawing and shall conform to type IV, class 9 of DDD-L-20. Fastness of class 9 marking shall be as specified for class 5 marking.

3.5 Workmanship. The barracks bag shall conform to the quality of product established by this document. The occurrence of defects shall not exceed the applicable acceptable quality level.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection . Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.2 In-process inspection. Inspection of sub-assemblies shall be made to ascertain that construction details which cannot be examined in the finished product are in accordance with specified requirements. This examination shall include inspection of the method of attaching the draw strings and inspection to determine that holes for receiving grommets are smaller than the outside diameter of the grommet barrel. Whenever nonconformance is noted, corrections shall be made to the parts affected and lot in-process. Parts which cannot be corrected shall be removed from production.

* 4.4.3 End item visual examination. The end item shall be examined for the defects listed in table I. The lot size shall be expressed in units of bags. The sample unit shall be one bag. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 15.0 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Cloth	Hole, cut, or tear; any smash, weak place, broken or missing yarn, multiple floats, or open place, clearly visible.	X	
	Shade bar, fine or coarse filling bar.		X
Grommet	Clinched excessively tight, cutting surrounding material.	X	
	Insecurely clinched to a degree that grommet may be detached from material.	X	
Seams and stitching:			
Open seam	1/2 inch or less.		X
	More than 1/2 inch.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Seams and stitching: (cont'd)			
NOTE:	A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or run-off stitches occur. On double-stitched seams, a seam shall be considered open when either one or both sides of the seam are open.		
Raw edge (on edge required to be finished)	More than 1/2 inch when securely caught in stitching.		X
NOTE:	Raw edge not caught in stitching shall be classified as an open seam.		
Run-off	(Classify as an open seam).		
Seam and stitch type	Wrong seam or stitch type.	X	
Stitch tension	Loose tension, resulting in a loose top or bottom thread.		X
	Excessively tight tension resulting in puckering of material.		X
Stitches per inch	One stitch less than minimum specified.		X
	Two or more stitches less than minimum specified.	X	
	One or more stitches in excess of maximum specified.		X
Seams and stitching:			
NOTE:	Variation in the number of stitches per inch, caused by operator speeding up the machine and pulling the fabric in order to sew over heavy places or heavy seams or in turning		

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Seams and stitching: (cont'd)			
	corners, shall be classified as follows: a. Within the minor defect classification - no defect. b. Within the major defect classification - minor defect.		
Stitching ends	Ends of type 301 stitching not secured as specified.		X
	Ends of seams produced with 401 stitch type, when not caught in other seams or stitching, having chain extending less than 1/2 inch.		X
Thread breaks, skipped stitches, or run-offs (unless otherwise classified herein) NOTE:	Overstitched less than 1 inch in each direction beyond the defective stitching area.		X
	Thread breaks or two or more consecutive skipped or run-off stitches not overstitched shall be classified as open seams.		
Bartacks	Stitching loose, incomplete, or broken.		X
	Any bartack omitted.	X	
Stitching indicated by "Z" on drawing (when type 401 is used)	Chain portion of stitching showing on outside of bag.		X
Component and assembly	Any mend, darn, or patch.	X	
	Body of bag formed with more pieces of fabric than specified.	X	
	Any component omitted, misplaced or not as specified (unless otherwise classified herein).	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Component and assembly (cont'd)	Any operation omitted, added or not properly performed (unless otherwise classified herein).	X	
	Seams badly pleated or puckered.		X
	Needle chews.		X
Hems	Formed on outside of bag.	X	
	Twisted or pleated.		X
Drawstrings (two required in hem)	Either drawstring caught in hem stitching causing failure to draw freely.	X	
	Loop not extended thru grommet on each side.	X	
Markings	Omitted, incorrect, illegible, misplaced or size of characters not as specified.		X
Cleanness	Spots or stains clearly noticeable; thread ends not trimmed to 1/4 inch maximum length.		

* 4.4.4 End item dimensional examination. The end item shall be examined for the defects listed in table II. The lot size shall be expressed in units of bags. The sample unit shall be one bag. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.

TABLE II. End item dimensional defects

Examine	Defect	Classification Major	Classification Minor
Overall dimensions	Smaller than nominal dimensions less applicable minus tolerance indicated on drawing, but not smaller than nominal dimensions less twice the applicable minus tolerance.		X
	Smaller than nominal dimensions less twice the applicable minus tolerance indicated on drawing.	X	
	Larger than nominal dimensions and applicable plus tolerance indicated on drawing.		X
Length of drawstring loop extending through grommet (bag opening at full width)	Less than minimum specified.	X	
Stitch margin	Exceeds specified tolerance		X
All other dimensions not classified herein	Exceeds specified tolerance.		X

4.4.5 Packaging inspection. An examination shall be made to determine that the preservation, packing, and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. Examination of closure defects listed below shall be made on shipping containers fully packaged. The lot size shall be the number of shipping containers in the inspection lot. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.

Examine	Defect
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, loose strapping, incomplete taping, or inadequate stapling. Bulged or distorted container.
Content	Number of bundles per shipping container is more or less than required. Number of bags per bundle is more or less than required. 1/

1/ For this defect, one bundle shall be examined from each shipping container in the sample.

4.4.6 Palletization examination. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length,width, or height exceeds specified maximum requirement.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Each bag shall be laid out flat, folded in half the length. The folded bag shall measure approximately 24 inches in length by 16 inches in width. Ten folded bags, alternated end for end, shall be stacked to form a compact bundle. The bundle shall be securely tied with cotton tape or twine approximately 4 inches from each end.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.

5.1.2 Commercial. The bag shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Fifty bags, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A bundles shall be packed flat, five in depth within a shipping container. Inside dimensions of each container shall approximate 24-1/2 inches in length, 16-1/2 inches in width, and 12-1/2 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30 pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced in accordance with the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.2 Level B packing. Fifty bags, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A bundles shall be packed flat, five in depth within a shipping container. Inside dimensions of each container shall approximate 24-1/2 inches in length, 16-1/2 inches in width, and 12-1/2 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on top and bottom with a sheet of 30 pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the box specification, except that the inspection shall be in accordance with 4.4.5.

5.2.3 Commercial packing. Bags, preserved as specified in 5.1 shall be packed in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.

* 5.3 Palletization. When specified (see 6.2), bags, packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The barracks bag is intended for use as a laundry bag to hold the soiled clothing of enlisted men and women.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1.1, 4.3, and 6.4).
c. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
d. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
e. When palletization is required (see 5.3).

6.3 Samples. For access to samples, address the contracting activity issuing the invitation for bids.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample consisting of one finished barracks bag. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for inspection and approval of the first article.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.

6.6 Changes from previous issue. The margins of this document are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - GL

Preparing activity:

Army - GL

Project No. 8465-0889

Review activities:

Army - MD
DLA - CT

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-23791H	Bag, Barracks

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 1 Apr 84

Source: https://assist.dla.mil – Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.