MILITARY SPECIFICATION

CEMENT, LIQUID, TENT PATCHING

This amendment forms a part of Military Specification MIL-C-2399B, dated 6 June 1966, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, under "SPECIFICATIONS". Add the following:

"MILITARY

MIL-C-43627 - Cloth, Duck, Cotton, Plied Yarns, Fire, Water, Weather and Mildew Resistant Treated, Light Dry Finish."

PAGE 2

2.2, under "Other Publications". Add the following:

"NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC.,

National Motor Freight Classification

(Application for copies should be addressed to American Trucking Associations Inc., Tariff Order Section, 1616 P Street, N.W., Washington, D.C. 20036).

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)"

3.1, line 2. Delete "an oil resistant elastomer" and substitute "complymers of butadiene and acrylonitrile".

Add the following new requirement at the end of the paragraph:

"The solvent blend shall meet the following compositional requirements

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.

PAGE 2 (cont'd)

limiting air pollutability:

a. A combination of hydrocarbons, alcohols, aldehydes, esters, ethers or ketones having a olefinic or cycloolefinic type of unsaturation: 5% maximum.

b. A combination of aromatic compounds with eight or more carbon atoms to the molecule except ethyl benzene: 8% maximum.

c. A combination of ethyl benzene, ketones having branched hydrocarbon structures, trichlorethylene or toluene: 20% maximum.

d. Total of a + b + c: 20% maximum."

PAGE 3

4.1 Delete second sentence entirely and substitute: "Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government."

PAGE 4

4.2 Delete entirely and substitute:

"4.2 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105 except when otherwise indicated hereinafter."

PAGE 7

Table II Add the following:

"Characteristic	Requirement paragraph	Test method
Solvent blend	3.1	1/"

PAGE 8

4.4.4.1 Add a second sentence: "Also, test specimens shall be made from cloth conforming to MIL-C-43627."

4.4.4.2, line 1. Delete "the" and substitute "each".

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.

PAGE 9

4.4.4.3, line 1. Delete "three" and substitute "six".

4.4.5.1, line 1, after "of". Insert "each".

line 8. Delete the words "to set for the specified time" and substitute "to set for the time specified below for each test".

4.4.5.2, line 2, after "D903-49". Insert "except conditioning shall be as specified below for each test".

4.4.5.6, lines 2 and 3. Delete entirely and substitute: "Specimens prepared as specified in 4.4.5.1 shall be allowed to set for 72 hours at 73.4 $\pm$ 2°F. then shall be immersed in water at room temperature for 48 hours and immediately tested while wet as specified in 4.4.5.2."

PAGE 10

5.1.1, line 4. Delete "(see 6.2.1)".

5.2.3, last sentence. Delete entirely and substitute: "Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable."

5.3.1 Include the following additional precautionary marking:

"When applicable, limit amount of daily solvent discharge into atmosphere or reduce emissions as provided in Rule 66, Los Angeles Air Pollution District or other air pollution regulations."

PAGE 11

6.2.1 Delete entirely.

Custodians:

Army - GL
Navy - AS
Air Force - 84

Preparing activity:

Army - GL

Project No. 8040-0316

Review activities:

Army - MD, MR

User activities:

Army - MI, SM
Navy - MC

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:50Z
Check the source to verify that this is the current version before use.