MIL-C-2440E (AR)
AMENDMENT 4
15 May 1985
SUPERSEDING
AMENDMENT 3
12 June 1984

MILITARY SPECIFICATION

CONTAINERS, METAL, FOR PROPELLING CHARGE

This Amendment forms a part of Military Specification MIL-C-2440E (AR), dated 29 October 1979, and is approved for use by the U.S. Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Standards, Military: Delete "MIL-STD-1188 - Commercial Packaging of Supplies and Equipment".

PAGE 3

Other Publications, American Society for Testing Materials:
Add:
"ASTM-D412 - Tension Testing of Vulcanized Rubber, Standard Method of
ASTM-D3951-82 - Commercial Packing, Standard Practice for".

PAGE 5

4.3.2, line 1: After "see MIL-A-48078" and Table I specified herein."

Add the included Table I to the specification.

PAGE 9

Add the included Classification of Defects and Tests (4.4.2.5, 4.4.2.6, 4.4.2.7, 4.4.2.8 and 4.4.2.9) to the specification.

PAGE 10

4.4.3.7 Weld of nut to spider (see dwg. 8880554) : Delete in its entirety.

FSC 8140

DISTRIBUTION STATEMENT A. APPROVED FOR PUBLIC RELEASE: DISTRIBUTION IS UNLIMITED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

PAGE 11

4.4.3.9: Add new paragraph as follows:

"4.4.3.9 Tensile stress of gasket (see dwg. 880558), Major Defect. Five (5) gaskets shall be randomly selected from each lot for this test. If any gasket fails to meet the requirement, the lot shall be rejected."

PAGE 12

4.5.7 Weld of nut to spider: Delete in its entirety.

4.5.9 Add new paragraph as follows:

"4.5.9 Tensile strength of gasket. The tensile stress shall be determined in accordance with ASTM-D412."

5. Delete in its entirety and substitute the following:

"5. PACKAGING

5.1 Unit packing. None required.

5.2 Packing. Packing shall be commercial. Propelling charge containers shall be prepared in accordance with ASTM D3951-82 (Standard Practice for Commercial Packing).

5.3 Marking. Shipping marking shall comply with ASTM D3951-82 and the following additional instructions. No shipping marking shall be placed directly on the containers. Commercial shipping tags attached with wire shall be used unless otherwise specified. The following information shall be shown: item name and model number, part number and revision, contract number, lot number and date, name and address of manufacturer. If containers are bundled, boxed or palletized, the gross weight and quantity shall be included. The above information may be placed on pallets or boxes by labeling or stenciling."

PAGE 14

* Add new paragraph as follows:

"6.5 Superseded container designs. Containers and their components, whose designs have been superseded, are not acceptable for renovation (see Appendix) without prior approval of the procuring activity."

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

* The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.3.2.1	Containers, Metal, for Propelling Charges and Components	1 OF 4	See Below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body (see dwg. 8880538)				
	a. Examination for defects	5	-		
	1. Thickness			3.1	Gage
	2. Length			3.1	Gage
	3. Location of bead for rim			3.1	Gage
	b. Tensile strength			3.3.1	4.5.1
	Bottom (see dwg. 8880539 or 8880540, as applicable)				
	Examination for defects	5	-		
	1. Thickness			3.1	Gage
	Plug (see dwg. 8880552)				
	Examination for defects	5	-	3.1	4.4.2.2
	Rim (see dwg. 8880541)	5	-	3.1	4.4.2.4
	Examination for defects				
	Ring (see dwg. 8880542)				
	Examination for defects	5	-		
	1. Thickness			3.1	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

(3a)

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 4		DRAWING NUMBER
4.3.2.1	Containers, Metal, for Propelling Charges and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Screw Assembly (see dwg. 8880544, 8880545 or 8880547 as applicable)				
	a. Examination for defects	5	-		
	1. Pitch diameter of thread			3.1	Gage
	2. Major diameter of thread			3.1	Gage
	3. Total length			3.1	Gage
	b. Crimp of handle to sleeve			3.1	4.5.5
	Stud (see dwg. 8880549)				
	Examination for defects	5	-		
	1. Total length			3.1	Gage
	2. Pitch diameter of thread			3.1	Gage
	3. Minor diameter of thread			3.1	Gage
	4. Small outside diameter			3.1	Gage
	Cover (see dwg. 8880550)				
	Examination for defects	5	-		
	1. Overall height (1 9/16")			3.1	Gage
	2. Width of gasket groove			3.1	Gage
	3. Height of lip			3.1	Gage
	Nut (see dwg. 8880553, 9232378, 9282857, or 9311209 as applicable)				
	Examination for defects	5	-		
	1. Minor diameter of thread			3.1	Gage
	2. Pitch diameter of thread			3.1	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 3 OF 4		DRAWING NUMBER
4.3.2.1	Containers, Metal, for Propelling Charges and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Spider (see dwg. 8880555)				
	Examination for defects	5	-		
	1. Diameter of hole			3.1	Gage
	2. Location from center of hole to edge of wing (Dimension A)			3.1	Gage
	3. Thickness			3.1	Gage
	Base (see dwg. 8880556 or 8880557, as applicable)				
	Examination for defects	5	-		
	1. Height			3.1	Gage
	2. Thickness			3.1	Gage
	3. Diameter of hole			3.1	Gage
	Gasket (see dwg. 8880558)				
	a. Examination for defects	5	-		
	1. Angularity, maximum			3.1	Gage
	2. Inside diameter			3.1	Gage
	3. Height (11/16")			3.1	Gage
	4. Large width (3/8")			3.1	Gage
	5. Height from base to edge of large width (3/16")			3.1	Gage
	b. Tensile strength (see note)	3 of 5		3.1	4.5.9/dwg. 8880558

NOTE: The gasket tensile stress test shall be performed after the other inspections have been performed on the applicable samples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-2440E (AR)
AMENDMENT 4

PARAGRAPH	TITLE		SHEET 4 OF 4		DRAWING NUMBER
4.3.2.1	Containers, Metal, for Propelling Charges and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body Assembly, unpainted (see dwg. 8880537)	5	-		
	a. Examination for defects			3.1	4.4.2.1
	b. Weld of rim to body			3.1	4.5.6
	Spider and Nut Assembly (see dwg. 8880554)				
	a. Crimp of nut to spider	2	-	3.1	4.5.8
	Cover Assembly (see dwg. 8880543)				
	a. Weld of stud cover	5	-	3.1	4.5.4
	Assembly (see dwg. 9332423)	5	-		
	a. Examination for defects			3.1	4.4.2.3
	b. Assembly of cover and body			3.4	4.5.2
	c. Air pressure test			3.6	4.5.3

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-2440E (AR)
AMENDMENT 4

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Body	1 OF 1	8880538
			NEXT HIGHER ASSEMBLY: 8880537

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness		0.40%	3.1	Gage
102	Length		0.40%	3.1	Gage
103	Location of bead for rim		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Cover	1 OF 1	8880550
			NEXT HIGHER ASSEMBLY: 8881028

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Overall height (1 9/16")		0.40%	3.1	Gage
102	Width of gasket groove		0.40%	3.1	Gage
103	Height of lip		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-2440E (AR)
AMENDMENT 4

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Screw assembly	1 OF 1	8880544, 8880545 or 880547 as applicable
			NEXT HIGHER ASSEMBLY: 8880543

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread		0.40%	3.1	Gage
102	Major diameter of thread		0.40%	3.1	Gage
103	Total length		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil (9c) Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-2440E (AR)
AMENDMENT 4

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
4.4.2.8	Stud		1 OF 1		8880549
					NEXT HIGHER ASSEMBLY
					8880543
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total length		0.40%	3.1	Gage
102	Pitch diameter of thread		0.40%	3.1	Gage
103	Minor diameter of thread		0.40%	3.1	Gage
104	Small outside diameter		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Gasket	1 OF 1	8880558
			NEXT HIGHER ASSEMBLY: 8880543

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Angularity, max.		0.40%	3.1	Gage
102	Inside diameter		0.40%	3.1	Gage
103	Height (11/16")		0.40%	3.1	Gage
104	Large width (3/8")		0.40%	3.1	Gage
105	Height from base to edge of large width		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140-A709)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.