INCH-POUND

MIL-C-2440E (AR)
AMENDMENT 5
27 February 1989
SUPERSEDING
AMENDMENT 4
15 May 1984

MILITARY SPECIFICATION

CONTAINERS, METAL, FOR PROPELLING CHARGE

This Amendment forms a part of Military Specification MIL-C-2440E (AR), dated 29 October 1979, and is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Standards, Military: Delete "MIL-STD-1188 - Commercial Packaging of Supplies and Equipment".

PAGE 3

Other Publications, American Society for Testing Materials:

Add:

"ASTM-D412 - Tension Testing of Vulcanized Rubber, Standard Method of

ASTM-D3951-82 - Commercial Packing, Standard Practice for".

PAGE 5

4.3.2, line 1: After "see MIL-A-48078" and Table I specified herein."

Add the included Table I to the specification.

PAGE 9

Add the included Classification of Defects and Tests (4.4.2.5, 4.4.2.6, 4.4.2.7, 4.4.2.8 and 4.4.2.9) to the specification.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH 4.3.2.1	TITLE Containers, Metal, for Propelling Charges and Components		SHEET 1 OF 4		DRAWING NUMBER See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body (see dwg. 8880538)				
	a. Examination for defects	5	-		
	1. Thickness			3.1	Gage
	2. Length			3.1	Gage
	3. Location of bead for rim			3.1	Gage
	b. Tensile strength			3.3.1	4.5.1
	Bottom (see dwg. 8880539 or 8880540, as applicable)				
	Examination for defects	5	-		
	1. Thickness			3.1	Gage
	Plug (see dwg. 8880552)				
	Examination for defects	5	-	3.1	4.4.2.2
	Rim (see dwg. 8880541)	5	-	3.1	4.4.2.4
	Examination for defects				
	Ring (see dwg. 8880542)				
	Examination for defects	5	-		
	1. Thickness			3.1	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 4		DRAWING NUMBER
4.3.2.1	Containers, Metal, for Propelling Charges and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Screw Assembly (see dwg. 8880544, 8880545 or 8880547 as applicable)				
	a. Examination for defects	5	-		
	1. Pitch diameter of thread			3.1	Gage
	2. Major diameter of thread			3.1	Gage
	3. Total length			3.1	Gage
	b. Crimp of handle to sleeve			3.1	4.5.5
	Stud (see dwg. 8880549)				
	Examination for defects	5	-		
	1. Total length			3.1	Gage
	2. Pitch diameter of thread			3.1	Gage
	3. Minor diameter of thread			3.1	Gage
	4. Small outside diameter			3.1	Gage
	Cover (see dwg. 8880550)				
	Examination for defects	5	-		
	1. Overall height (1 9/16")			3.1	Gage
	2. Width of gasket groove			3.1	Gage
	3. Height of lip			3.1	Gage
	Nut (see dwg. 8880553, 9232378, 9282857, or 9311209 as applicable)				
	Examination for defects	5	-		
	1. Minor diameter of thread			3.1	Gage
	2. Pitch diameter of thread			3.1	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 3 OF 4	DRAWING NUMBER
4.3.2.1	Containers, Metal, for Propelling Charges and Components		See Below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Spider (see dwg. 8880555)				
	Examination for defects	5	-		
	1. Diameter of hole			3.1	Gage
	2. Location from center of hole to edge of wing (Dimension A)			3.1	Gage
	3. Thickness			3.1	Gage
	Base (see dwg. 8880556 or 8880557, as applicable)				
	Examination for defects	5	-		
	1. Height			3.1	Gage
	2. Thickness			3.1	Gage
	3. Diameter of hole			3.1	Gage
	Gasket (see dwg. 8880558)				
	a. Examination for defects	5	-		
	1. Angularity, maximum			3.1	Gage
	2. Inside diameter			3.1	Gage
	3. Height (11/16")			3.1	Gage
	4. Large width (3/8")			3.1	Gage
	5. Height from base to edge of large width (3/16")			3.1	Gage
	b. Tensile strength (see note)	3 of 5		3.1	4.5.9/dwg. 8880558

NOTES: The gasket tensile stress test shall be performed after the other inspections have been performed on the applicable samples.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 4 OF 4		DRAWING NUMBER
4.3.2.1	Containers, Metal, for Propelling Charges and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body Assembly, unpainted (see dwg. 8880537)	5	-		
	a. Examination for defects			3.1	4.4.2.1
	b. Weld of rim to body			3.1	4.5.6
	Spider and Nut Assembly (see dwg. 8880554)				
	a. Crimp of nut to spider	2	-	3.1	4.5.8
	Cover Assembly (see dwg. 8880543)				
	a. Weld of stud cover	5	-	3.1	4.5.4
	Assembly (see dwg. 9332423)	5	-		
	a. Examination for defects			3.1	4.4.2.3
	b. Assembly of cover and body			3.4	4.5.2
	c. Air pressure test			3.6	4.5.3

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Body		8880538
			NEXT HIGHER ASSEMBLY 8880537

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness		0.40%	3.1	Gage
102	Length		0.40%	3.1	Gage
103	Location of bead for rim		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-2440E (AR)
AMENDMENT 5

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8880550
4.4.2.6	Cover				NEXT HIGHER ASSEMBLY 8881028
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Overall height (1 9/16")		0.40%	3.1	Gage
102	Width of gasket groove		0.40%	3.1	Gage
103	Height of lip		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Screw assembly	1 OF 1	8880544, 8880545 or 880547 as applicable
			NEXT HIGHER ASSEMBLY: 8880543

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread		0.40%	3.1	Gage
102	Major diameter of thread		0.40%	3.1	Gage
103	Total length		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8880549
4.4.2.8	Stud				NEXT HIGHER ASSEMBLY 8880543
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total length		0.40%	3.1	Gage
102	Pitch diameter of thread		0.40%	3.1	Gage
103	Minor diameter of thread		0.40%	3.1	Gage
104	Small outside diameter		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

(9d) 9

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Gasket	1 OF 1	8880558
			NEXT HIGHER ASSEMBLY: 8880543

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Angularity, max.		0.40%	3.1	Gage
102	Inside diameter		0.40%	3.1	Gage
103	Height (11/16")		0.40%	3.1	Gage
104	Large width (3/8")		0.40%	3.1	Gage
105	Height from base to edge of large width		0.40%	3.1	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

PAGE 10

4.4.3.7 Weld of nut to spider. (see dwg. 8880554) : Delete in its entirety.

PAGE 11

4.4.3.9 Add new paragraph as follows:

"4.4.3.9 Tensile stress of gasket (see dwg. 880558), Major Defect. Five (5) gaskets shall be randomly selected from each lot for this test. If any gasket fails to meet the requirement, the lot shall be rejected."

PAGE 12

4.5.7 Weld of nut to spider. Delete in its entirety.

4.5.9 Add new paragraph as follows:

"4.5.9 Tensile strength of gasket. The tensile stress shall be determined in accordance with ASTM-D412."

5. Delete in its entirety and substitute the following:

"5. PACKAGING

5.1 Unit packing. None required.

5.2 Packing. Packing shall be commercial. Propelling charge containers shall be prepared in accordance with ASTM D3951-82 (Standard Practice for Commercial Packing).

5.3 Marking. Shipping marking shall comply with ASTM D3951-82 and the following additional instructions. No shipping marking shall be placed directly on the containers. Commercial shipping tags attached with wire shall be used unless otherwise specified. The following information shall be shown: item name and model number, part number and revision, contract number, lot number and date, name and address of manufacturer. If containers are bundled, boxed or palletized, the gross weight and quantity shall be included. The above information may be placed on pallets or boxes by labeling or stenciling."

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

PAGE 14

Add new paragraph as follows:

"6.5 Superseded container designs. Containers and their components, whose designs have been superseded, are not acceptable for renovation (see Appendix) without prior approval of the procuring activity."

PAGE 15

* 30.4 Change title to "Air pressure of body and cover".

PAGE 16

* 40.1.2 Inspection No. 3, Air Pressure: Change "(see 30.4)" to "(see Note 1 below and 30.4)".

* 40.1.4 Cover after painting:

Inspection No. 3, Change to "Cover gasket missing or improper".

"4. Plugwasher missing or improper Visual

5. Air pressure (see Note 1 below and 30.4) Test, 100 percent".

* Bottom of page Add note as follows:

"1. The air pressure test may be conducted 100 percent on the assembled container (cover and body), after painting, in lieu of the individual body or cover."

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140-A788)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:57Z
Check the source to verify that this is the current version before use.