INCH-POUND

MIL-C-2439E
AMENDMENT 5
28 April 1992
SUPERSEDING
AMENDMENT 4
29 MAY 1991

MILITARY SPECIFICATION

CONTAINER, AMMUNITION, FIBER, SPIRALLY WOUND

This Amendment forms a part of Military Specification MIL-C-2439E, dated 25 April 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* 2.1.1 Under "SPECIFICATION, FEDERAL"
Delete "QQ-S-781 - Strapping, Steel and Seals"

PAGE 3

Parenthetical source (for 2.1.1). Delete and substitute:

"(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)"

* 2.2 Other publications - Under "AMERICAN SOCIETY FOR TESTING AND MATERIALS:"

Add "ASTM-D3953 - Strapping, Flat Steel and Seals, Standard Specification for (DoD Adopted)"

PAGE 5

* 3.5 Assembly. Add the following sentence to the end of the paragraph:

"All materials used in the construction of the containers shall be certified in accordance with the applicable specifications."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-16T14:56Z
Check the source to verify that this is the current version before use.

PAGE 7

3.7.1 Metal for ends. Add following sentence to end of paragraph:

"Any material changes to the metal ends mentioned in 3.7.1.1 and 3.7.1.2, shall require approval by the Procuring Agency."

3.7.2 Metal end marking. Delete the sixth sentence ("If necessary, the word. . .") and substitute:

"If necessary, the word "CONTAINER" may be abbreviated to "CNTNR". "CNTNR" shall be used for all new tooling. However, if tooling is already in existence with the abbreviation "CONT", it may be used in lieu of "CNTNR". Also, the embossing design shown on the drawing may be shifted circumferentially to provide additional space in the embossing circle."

PAGE 8

* 3.11 Resin content (applicable to Type IV containers). Change first sentence as follows:

"Unless otherwise indicated on the drawing, the resin content of the outer, cover and neck tubes shall be 12 percent min., by weight, when immersed in resin (see 6.10)."

PAGE 9

3.13 Workmanship.

a. Second sentence, Delete: "surface scuffing" and substitute "scuffs penetrating the outer layer, gouges, cuts, checks".

b. After second sentence, add new sentence as follows:

"Scuffs not penetrating the outer layers, shall be permitted on a container if they are not larger than one inch and there are not more than two scuffs on the container."

Source: https://assist.dla.mil -- Downloaded: 20260-16T14:56Z
Check the source to verify that this is the current version before use.

PAGE 10

* 4.3.1 Submission. Add the following sentence to end of paragraph:

"During production, any changes to the production processes, procedures or equipment which differs from those used to produce first article samples shall require approval by the Procuring Agency."

PAGE 11

4.3.2.1 Table III.First article inspection. At bottom of table, Change "Inner tubes" to "inner tube material".

PAGE 12

* 4.3.2.1 Table III. First article inspection.

Under "Cover tubes" and "outer tubes", add the following "b. Construction (per applicable figure) (see Note 3)"

Under Requirement Paragraph column, for Cover tubes and outer tubes, add "3.2"

Under Paragraph Reference/Inspection Method column, for cover tubes and outer tubes, add "4.5.12"

Under Notes, add the following:

"3. The samples which are used for the metal end pull test shall be utilized for the construction test."

PAGE 15

4.4.2.1 Container Assembly: Delete Minor Defect 215 in its entirety.

PAGE 16

4.4.2.1 Container Assembly.

Source: https://assist.dla.mil -- Downloaded: 202610-16T14:56Z
Check the source to verify that this is the current version before use.

Delete Minor Defect 218 in its entirety and substitute:

"218	Staple protruding through inner wall, mislocated, missing, broken or improperly clinched (as applicable)	0.65%	3.1	Visual"

Minor Defect 221 (workmanship). Delete AQL "0.65%" and substitute AQL "1.5%".

* Add Minor Defect 222 as follows:

"222	Crimp on either end of spacer ring assembly faulty or incomplete (when applicable).	0.65%	3.1	Visual/Manual"

PAGE 20

4.4.3.7, Inner tubes. Delete in its entirety.

* Add new paragraph as follows:

"4.4.3.10 Construction. (see 3.2). Major defect - Cover tubes and outer tubes from the sample drawn for 4.4.3.3 shall be tested in accordance with 4.5.12."

PAGE 22

4.5.7 Inner tube. Change "Inner tube" to "Inner tube material (First article inspection only)".

4.5.7.1, 4.5.7.2, 4.5.7.3 In all three subparagraphs, change "inner tubes" to "inner tube material".

* 5.2.2.2.1 Strapping. First sentence change to:

"Bundles shall be strapped with steel strapping not less than 3/8 inch wide by .015 thick, Type 1, Regular-duty, Finish A or C complying with ASTM-D3953."

Source: https://assist.dla.mil -- Downloaded: 20261O-16T14:56Z
Check the source to verify that this is the current version before use.

PAGE 24

* Add new paragraph as follows:

"4.5.12 Construction. The walls of the outer tube and the cover tube shall be cross-sectioned by cutting them with a knife or other sharp instrument. The layers of the outer tubes and the cover tube shall then be separated for identification purposes. Observations shall be made to insure that the materials and construction methods used are in accordance with Figure 1 (for Types I, II and III containers) or Figure 2 (for Type IV container) of this specification, whichever is applicable."

PAGE 26

6.2 Ordering data. Delete paragraph in its entirety and substitute:

"6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.
b. Drawing number of container.
c. Type and class of container (see 1.2).
d. Issue of DODISS to be cited in the solicitation and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
e. Provisions for submission of first article samples."

6.12 Resin material. Delete in its entirety and substitute:

"6.12 Resin material. Boler 1318 and Boler 1633 "Fully Refined Waxes" manufactured by Boler Petroleum Company, 85 Old Eagle School Road, Wayne, PA 19087, have been found satisfactory for use in resin immersion containers."

The margins of this Amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Source: https://assist.dla.mil -- Downloaded: 20261O-16T14:56Z
Check the source to verify that this is the current version before use.