MIL-R-2461E
30 September 1977
SUPERSEDING
MIL-R-2461D
17 June 1970

MILITARY SPECIFICATION

ROLL, FIELD BREAKDOWN, COMMISSARY OUTFIT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a cotton duck roll equipped with twelve utensil pockets and a leather lined knife scabbard. The roll is a component of the types I and II Commissary Outfit, Field Breakdown.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

UU-P-268	-	Paper, Kraft, Wrapping
DDD-L-20	-	Label: For Clothing, Equipage, and Tentage (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Natick Research and Development Command, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7360

Source: https://assist.dla.mil -- Downloaded: 20261O-16T14:59Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized and Containerized Unit Loads for 40" x 48" Pallets

DRAWINGS

US ARMY NATICK RESEARCH AND DEVELOPMENT COMMAND

5-7-148 - Roll, Field Breakdown, Commissary Outfit; Illustration and Assembly
5-7-149 - Details "A"
5-7-150 - Details "B"
5-7-151 - Details "C"
5-7-152 - Sections "D"
5-7-153 - Sections "E"

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:59Z
Check the source to verify that this is the current version before use.

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

* 3.1 First article. When specified (see 6.2) the contractor shall furnish a sample for first article inspection and approval (see 4.2 and 6.3).

* 3.2 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer in his commercial cotton duck products provided the completed field breakdown roll complies with all provisions of this specification.

3.3 Construction. The construction shall conform to the drawings listed in section 2 and as specified herein.

3.3.1 Stitching, machine. All stitching, except bartacking, shall conform to stitch type 301 of FED-STD-751 with 6 to 8 stitches per inch (25 mm).

3.3.1.1 Thread breaks. Thread breaks in stitching shall be overstitched not less than 1 inch (25 mm) at each break.

3.3.1.2 Stitching ends. Stitching ends shall be overstitched not less than 1 inch (25 mm) on stitch type 301 except where ends are turned under in a hem, held down by other stitching, or where stitching is performed automatically. When stitch patterns such as box, box with cross-stitch, "W" stitching, or straight-line tacking are performed automatically, at least 3 tying, overlapping, or backstitches shall be used for securing the ends of stitching.

3.3.1.3 Skipped stitches. Two or more consecutively skipped stitches occuring in type 301 stitching shall be overstitched not less than 1 inch (25 mm).

3.3.1.4 Thread treatment. The addition of any lubricant to the polyester thread prior to, or during, the sewing operation is prohibited.

3.3.1.5 Bartacking. Bartacking shall be 7/8 inch (22 mm) plus or minus 1/16 inch (1.6 mm) in length with a 1/8 inch (3.2 mm) bight and shall contain 42 stitches. Bartacking shall be free of thread breaks and loose stitching.

3.3.2 Setting of end clips. The webbing shall be inserted the full depth of the clips. The clips shall be attached without cutting the webbing and the webbing shall lie flat at the point of entrance.

Source: https://assist.dla.mil -- Downloaded: 202610-16T14:59Z
Check the source to verify that this is the current version before use.

* 3.3.3 Setting of snap fasteners and components. The hole for the male part of the style 1 snap fastener shall be formed when the fastener is driven into the material. The hole punched before insertion of the female part of the style 1 fastener shall be no larger than that made by a standard no. 10 round drive punch (5/16 inch or 8.3 mm diameter hole). Holes punched to receive the male or female part of the style 2 snap fastener and grommets, shall be smaller than the outside diameter of the fastener tube or grommet barrel, so that the tube or barrel must be forced through the hole. The snap fasteners and grommets shall be clinched sufficiently tight to prevent their turning in the hole but not so tight as to cut the material.

3.4 Marking. All marking and labels shall conform to the requirements of DDD-L-20.

3.4.1 Identification marking. Identification marking shall conform to the requirements for type IV, class 5 labels. The letters "US" shall be applied in the size characters and in the location shown on Drawing 5-7-148 and shall conform to type IV, class 9 labels. Fastness of class 9 marking shall be as specified for class 5 marking.

3.4.2 Contents label. The contents label shall be 12-3/4 inches (324 mm) long by 8 inches (203 mm) wide conforming to type II, class 9 labels and shall be stitched to the roll in the location shown on Drawing 5-7-148. The marking on the label shall be applied with a 12 point size antique or cheltenham style type face. Fastness of class 9 marking shall be as specified for class 5 marking. The information on the label shall be as follows:

Quantity	Contents	Pocket Number
1	Bar, wrecking, claw and pinch point, gooseneck, 24 inch (610 mm)	1
1	Brush, hand scrub	11
1 box	Crayon, marking, lumberman's black, 4-1/2 inches (114 mm) long, 12 per box	11
1	Cutter, steel strapping, 2 inch (51 mm) maximum cut	1
1	File, nail, 8 inch (203 mm)	3
1	Hammer, hand, carpenter's nailing, curved-claw, bell faced, 16 ounce (0.45 kg)	7

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:59Z
Check the source to verify that this is the current version before use.

Quantity	Contents	Pocket Number
1	Handle, hatchet, half, 14 inch (356 mm)	1
1	Hatchet, claw, handle, 4 inch (102 mm)	4
1	Knife, carton opening	1
1	Knife, steak, scimitar, 10 inch (254 mm) blade	5
1	Lubricating oil, general purpose, light, 4 ounce (0.11 kg) spout can	10
1	Opener, crate, double-faced, hammer-head type, 3 inch (76 mm) head length, 8-1/2 inches (216 mm) long	1
1	Pliers, lineman's side cutting, 8 inches (203 mm) long	2
1	Saw, hand, crosscut, 10 point 24 inch (610 mm)	12
1	Screwdriver, common, normal duty, single grip, 8 inch (203 mm) blade, 3/8 inch (9.5 mm) tip, 14 inches (356 mm) long	9
1	Shears, metal cutting, 3 inch (76 mm) straight cut, 12-1/2 inches (318 mm) long	6
1	Stone, sharpening, mounted, artificial, rectangular, coarse and fine combination, 1 by 2 by 8 inches (25 by 51 by 203 mm)	8

3.4.3 Numbering of pockets. Each pocket in the roll shall be numbered in the size characters and in the location shown on Drawing 5-7-148. The marking shall conform to type IV, class 9. Fastness of class 9 marking shall be as specified for class 5 marking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:59Z
Check the source to verify that this is the current version before use.

3.5 Workmanship. Cloth components shall be clean and free of holes, cuts, tears or cloth defects such as multiple floats or broken or missing yarns. Webbing and tape shall not have frayed or scalloped edges and rope components shall be free of cuts or breaks. Thread tension shall be maintained so that there is no loose stitching and seam allowances shall be maintained with seams properly sewed so that no run-offs, twists, pleats, or open seams shall result. Care shall be taken in sewing to see that no needle chews occur. All thread ends shall be trimmed to 1/2 inch (13 mm) or less. Metal components shall be free of burrs, sharp edges, and corroded areas, and shall not be broken or malformed.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3)
2. Quality conformance inspection (see 4.4)

* 4.3 First article inspection. When a first article is required, it shall be examined for defects listed in tables I and II. Any visual defect or any dimension not within specified requirements shall be cause for rejection of the first article.

* 4.4 Quality conformance inspection. Except as otherwise specified herein sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

* 4.4.2 In-process inspection. Examination shall be made of the following operations to establish conformance to specified requirements. Whenever nonconformance is noted, correction shall be made to the items affected and to the operation.

Source: https://assist.dla.mil -- Downloaded: 202610-16T14:59Z
Check the source to verify that this is the currentversion before use.

4.4.2.1 Visual examinations of operations.

a. There shall be no lubrication of polyester thread prior to or during sewing operations for compliance with 3.3.1.5.

b. Holes punched to receive female part of style 1 snap fasteners or male and female part of style 2 snap fasteners are in compliance with 3.3.3 or 3.3.4, as applicable.

c. Holes punched to receive grommets are in compliance with 3.3.5.

* 4.4.3 End item inspection. The lot shall consist of all completely fabricated field breakdown commissary rolls offered for inspection at one time. The sample unit shall be one completely fabricated roll.

* 4.4.3.1 Visual examination. The completely fabricated roll shall be examin for defects in table I. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects, 6.5 for major and minor A defect combined, and 15 for major and minor A and B defects combined, expressed in te of defects per hundred units.

TABLE I. Classification of visual defects

Examine	Defect	Classification Major	Minor A	Minor B
Fabric	Any hole, cut, or tear	X		
	Broken or missing yarn; multiple floats visible at normal inspection distance (approximately 3 feet or 1 meter)	X		
	Shade bar			X
	Fine or coarse filling bar			X
Webbing, tape components	Not firmly and tightly woven, edge frayed, or scalloped	X		
	Misplaced	X		
Leather component	Knife scabbards finished with flesh side on the inside	X		
	Deep cuts, damaged grains, grub holes, or brand marks	X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:59Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Hardware	Broken	X		
	Malformed:			
	- Fails to perform intended function	X		
	- Will perform intended function		X	
	Protective finish omitted	X		
	Corroded area	X		
	Burr or sharp edge which may cause injury in handling or damage to fabric	X		
Grommets	Improperly set or loosely clinched allowing grommet to rotate in hole		X	
	Clinched excessively tight, cutting fabric, or insecurely clinched, (i.e. grommet and washer become disengaged)	X		
	Set with rim even with or extending beyond outer edges of hem		X	
Buckles	Not assembled to strap as specified, (i.e. reversed, failing to effect fastening of straps)	X		
Clip ends	Loosely clinched, webbing not flat at point of insertion			X
	Clinched excessively tight (cutting webbing)	X		
Seams and stitching	Open seam:			
	- For more than 1/4 inch (6 mm) but not more than 3/4 inch (19 mm)			X
	- For more than 3/4 inch (19 mm) but not more than 1 inch (25 mm)		X	
	- For more than 1 inch (25 mm)	X		

Source: https://assist.dla.mil -- Downloaded: 202610-16T14:59Z
Check the source to verify that this is the currentversion before use.

TABLE I. Classification of visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Seams and stitching (cont'd)				
	NOTE: A seam shall be classified as open when one or more skipped or run-off stitches occur. On double-stitched seams, a seam shall be considered open when either one or both sides of a seam are open.			
	Raw edge:			
	- More than 1/2 inch (13 mm) but not more than 1 inch (25 mm)			X
	- More than 1 inch (25 mm)		X	
	Thread break overstitched less than 1 inch (25 mm)			X
	NOTE: Thread breaks not overstitched shall be classified as open seams.			
	Skipped stitches overstitched less than 1 inch (25 mm)			X
	NOTE: Skipped stitches not overstitched shall be classified as open seams.			
	Needle chew resulting in hole, cut or tear (see any hole, cut or tear)			
	One or more required rows of stitching omitted (except on boxstitching)	X		
Boxstitching	Incomplete:			
	- one row of stitching omitted			X
	- Two or more rows of stitching omitted		X	
	Less than specified length by more than 1 inch (25 mm)			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:59Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Seams and stitching (cont'd)				
Bartacking	Less than specified length by more than 1/16 inch (1.6 mm)			X
Stitching ends	Overstitched less than 1 inch (25 mm) (except where ends are held down by other stitching or where stitching is performed automatically)		X	
Seam type	Wrong seam type	X		
Stitch type	Wrong stitch type	X		
Stitch tension	Loose, resulting in loosely exposed bobbin or top thread for more than 2 inches (51 mm)		X	
	Tight, as evidenced by puckering on fabric for more than 2 inches (51 mm)		X	
Stitches per inch (25 mm)	One stitch less than minimum specified			X
	Two or more stitches less than minimum specified		X	
	One or more stitches in excess of maximum specified			X
Stitching gage	Not as specified		X	
Stitching margin	Variation from specified margin by more than ± 1/16 inch (1.6 mm):			
	- For more than 2 inches (51 mm) but not more than 4 inches (102 mm) in length			X
	- For more than 4 inches (102 mm) in length		X	
Components and assembly	Any component part not fabricated of applicable referenced material	X		
	Any component part or required operation omitted (unless otherwise classified)	X		
	Mend, darn or patch	X		

Source: https://assist.dla.mil -- Downloaded: 202610-16T14:59Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Components and assembly (cont'd)				
Hems	Variation from specified width by more than ± 50% of width specified			X
Reinforcements	Improperly applied, causing excessive fullness in reinforcements or reinforced parts		X	
	Not stitched to reinforcements as indicated on drawings		X	
Marking: "US" nomenclature and identification	Omitted, incorrect, illegible or misplaced			X
Label of contents	Omitted, incorrect, illegible or misplaced		X	
Numbering of pockets	Any pocket not numbered or incorrectly numbered		X	
Cleanness	Noticeable grease or oil stains			X
	Thread ends not trimmed to 1/2 inch (13 mm) or less			X
Binding	Loosely or improperly applied		X	
Construction details				
Pockets	Any pocket misplaced, i.e. not set on location specified		X	
Pocket 1	Any part of pocket or flap single-ply construction	X		
Pockets 1 through 12	Not constructed as specified	X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:59Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Construction details (cont'd)				
Pockets 1, 11 and 12	Male or female portion of snap fasteners misplaced, failing to effect a closure, or not functioning properly	X		
	Fastener parts reversed, i.e. stud portion attached to flap		X	
Pocket 5	Leather scabbard omitted or fails to fit pocket	X		
Carrying strap	Spliced, i.e. made from more than 1 piece of webbing		X	
	Grip portion of handles not bartacked, or not constructed as specified		X	
	Length or bight of bartacks not as specified; loose stitching		X	
	Ends of strap not finished as specified			X
	Edge of outer reinforcements uneven with edge of case by 1/8 inch (3 mm) or more			X
Securing straps	Less than 3 straps provided	X		
	Any strap attached to body with less than 2 cross boxstitching	X		
	Buckle edge of straps uneven with edge of case by 1/8 inch (3 mm) or more		X	

* 4.4.3.2 Dimensional examination. The completely fabricated roll shall be examined for defects in table II. The inspection level shall be S-2 with an AQL of 4.0 for major defects, 10.0 for major and minor A defects combined, and 25.0 for major and minor A and B defects combined expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:59Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of dimensional defects

Examine	Defect	Classification Major	Minor A	Minor B
Overall dimensions	Smaller than specified dimensions less applicable minus tolerance indicated on drawings	X		
	Larger than specified dimensions and applicable plus tolerance indicated on drawings			X
Component and location dimensions	Not within specified tolerance		X	

* 4.4.4 Inspection of packaging. An examination shall be made to determine that preservation-packaging, packing, and marking are in compliance with the requirements of section 5. Defects shall be as specified in table III. The sample unit shall be one shipping container fully prepared for delivery except it need not be closed. The lot shall be the number of shipping containers offered for inspection at one time. The inspection level shall be S-2 with an AQL of 2.5, expressed in terms of defects per hundred units.

TABLE III. Inspection of packaging

Examine	Defect
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged or otherwise defective
Workmanship	Bulged or distorted containers
Contents	Number per container is more or less than required

4.4.5 Inspection of shipping containers. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in closure, waterproofing, and reinforcing shall be in accordance with the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:59Z
Check the source to verify that this is the current version before use.

* 4.4.6 Inspection for palletization. When applicable, an examination shall be made to determine that palletization is in compliance with section 5. Defects shall be as specified in table IV. The sample unit shall be one palletized unit load ready for shipment. The lot shall be the number of palletized unit loads submitted for inspection at one time. The inspection level shall be S-1 with an AQL of 6.5, expressed in terms of defects per hundred units.

TABLE IV. Inspection of palletization

Examination	Defect
Finished dimensions	Length, width, or height exceeding specified maximum requirements
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded with straps as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A. Each roll, with the leather scabbard placed in its pocket, shall be folded and secured by the straps provided for that purpose with the center strap passing over both handles.

* 5.1.2 Level C. Rolls shall be packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The package and the quantity per package shall be the same as that normally used by the contractor for retail distribution.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:59Z
Check the source to verify that this is the current version before use.

* 5.2.1 Level A, packing. Ten rolls, preserved-packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each PPP-B-636 shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A packages shall be packed flat one in length, two in width, and five in depth within a shipping container. Inside dimensions of each shipping container shall approximate 36 inches (915 mm) in length, 20 inches (508 mm) in width, and 11-1/4 inches (286 mm) in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound (50 gm/m^2) minimum basis weight kraft paper conforming to grade B of UU-P-268. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636.

5.2.2 Level B, packing. Ten rolls, preserved-packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-C, type CF, (variety DW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A packages shall be packed flat, one in length, two in width, and five in depth within a shipping container. Inside dimensions of each shipping container shall approximate 36 inches (915 mm) in length, 20 inches (508 mm) in width, and 11-1/4 inches (286 mm) depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound (50 gm/m^2) minimum basis weight kraft paper conforming to grade B of UU-P-268. Each shipping container shall be closed in accordance with method II as specified in the appendix of the container specification.

* 5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

* 5.2.3 Level C, packing. Rolls, preserved-packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the supplier for retail distribution. Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Palletization. When specified (see 6.2) rolls, packed as specified in 5.2, shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:59Z
Check the source to verify that this is the current version before use.

5.4 Marking. In addition to any special marking required by the contract or order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The roll covered by this specification is a component of field breakdown commissary outfits and serves to carry and store, when not in use, various tools and utensils required to break down rations in the field.

* 6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) When a first article is required for inspection and approval (see 3.1, 4.3, and 6.4).
(c) Selection of applicable levels of preservation-packaging and packing (see 5.1 and 5.2).
(d) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(e) When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be examined and approved under the appropriate provisions of 7-104.55 of the Armed Services Procurement Regulations. The first article should be a preproduction sample consisting of one complete unit. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for examination and approval of the first article.

6.4 Changes from previous issue. The margins of this specification have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) were made to previous issue. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - MC

Review activities:

Army - MD
DLA - GS

Preparing activity:

Army - GL

Project No. 7360-0104

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:59Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-R-24612 -- Roll, Field Breakdown, Commissary Outfit

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

3. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202610-16T14:59Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRXNM-TD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314

Commander
US Army Natick Research and Development Command
ATTN: DRXNM-TD
Natick, MA 01760

NATICK OP 1 JUL 77

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T14:59Z
Check the source to verify that this is the current version before use.