MILITARY SPECIFICATION SHEET

COUPLING HALF, QUICK DISCONNECT, PNEUMATIC STARTER, EXTERNAL, LOW PRESSURE, DIRECT RELEASE

This specification is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

Envelope dimensions for the coupling shall be as specified in MIL-C-25531, Figure 1.

There is no lanyard attachment to the coupling half.
Except for all references in Section 3 related to the lanyard and all test procedures in section 4 related to the lanyard, the complete requirements for acquiring the coupling described herein shall consist of this document and the latest issue of MIL-C-25531.

Coupling Disconnect Design Requirements

The design shall be such that a direct push force is required to install the coupling half onto an airframe nipple. It shall not be necessary to slide the outer sleeve back to release the balls prior to being installed on the airframe nipple.

Removal from airframe niple shall be accomplished by a direct pull on the ring handle. The coupling when removed from the aircraft shall be in the ready to install position, with no additional action required by personnel.

Part number: The part number consists of the basic number of this specification sheet.

EXAMPLE OF PART NUMBER:

M25531/1

Custodian:
Navy - AS

Preparing activity:
Navy - AS
(Project No. 4730-N591)

FSC 4730

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T06:38Z
Check the source to verify that this is the current version before use.