COMMERCIAL ITEM DESCRIPTION

BELT, SAFETY (LINEMAN'S)

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification KK-B-151H, Type I.

The lineman's belt covered by this description is intended for use by linemen or electricians in the installation or repair of transmission, distribution or communication lines.

The belts shall be furnished in the following sizes, as specified:

Size 34 - 34 inch (+) or (-) 1/2 inch waist, D size 18
36 - 36 inch (+) or (-) 1/2 inch waist, D size 19
38 - 38 inch (+) or (-) 1/2 inch waist, D size 20
40 - 40 inch (+) or (-) 1/2 inch waist, D size 21
42 - 42 inch (+) or (-) 1/2 inch waist, D size 22
44 - 44 inch (+) or (-) 1/2 inch waist, D size 23
46 - 46 inch (+) or (-) 1/2 inch waist, D size 24
48 - 48 inch (+) or (-) 1/2 inch waist, D size 25

Salient Characteristics

The lineman's belt shall consist primarily of a body pad, "D" ring strap, waist strap and tool loops.

Body Pad. The body pad backing shall be harness leather, nylon fabric or webbing of piled construction and of a color furnished commercially by the manfacturer. The nylon fabric or webbing shall be impregnated with neoprene. The body side shall be lined with chrome leather or a synthetic of proven quality, equal or superior strength and durability, having rolled edges and no exposed rivets. The body pad shall have a width not less than 4 1/2 inches and a length not less than the "D" size (as specified) plus the "D" rings. If circle "D" rings are used, the "D" rings may extend a maximum of 1 inch beyong the body pad on each end.

Integral Tabs. The body shall be provided with two integral tabs for the attachment of tool carriers, one on the left side and one on the right side.

"D" Ring Strap. The "D" ring strap shall be made of piled nylon cloth or webbing and shall be either treated with polyvinyl butyral or neoprene impregnated. The individual plies shall be folded so that no cut edges are exposed and shall be impregnated and vulcanized so that the piles are not readily separable except by chemical means.

Circle "D" Rings. The "D" rings shall be made of forged steel and either zinc or cadmium plated. The "D" rings shall have no sharp edges.

"D" Size. Distance between "D" ring heels. Tolerance shall be (+) or (-) 1/2 inch.

Waist Strap. The waist strap shall be made of plied nylon cloth and shall be secured to the body pad "D" ring assembly by a loop or loops. The length from the buckle end to the center adjustment hole of the other end of the belt shall equal the waist size designation (as specified).

Buckle. Body strap buckle frames shall be fabricated of a forging quality steel by the forge process. The buckles shall be either cadmium or zinc plated. They shall be reasonably smooth and no sharp edges will be permitted. The buckles shall be free from any defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:18Z
Check the source to verify that this is the current version before use.

Keeper. A suitable keeper shall be affixed to the buckle end of the belt strap overlap extending from the buckle.

Suspension "D" Rings. When specified, four "D" rings shall be attached at appropriate locations for attaching a suspender or belt type supporter.

Tool Loops. The tool loops shall be made of leather or neoprene impregnated cloth, riveted to the belt strap. The length shall be adequate for forming four tool loops, with no loops in the center.

Accessories. A tape thong, a glove bag ring and a knife snap shall be attached to the belt strap at points of attachment of the tool loops.

Maintenance Instructions. The manufacturer shall provide instructions for the care of the belt.

Marking. Each body belt shall have a metal marker attached, on which the manufacturer's name, the month and year of manufacture and the manufacturer's model number shall be permanently stamped.

Workmanship. Belts shall be free of defects which may affect durability, appearance or serviceability.

Conformance. Belts shall be approved by a nationally recognized testing laboratory as having been tested in accordance with and meeting the requirements of Title 29, Code of Federal Regulations (CFR), Part 1910.268 (g) (2) (i) and (ii) and 1926.959, latest revision on the date of the solicitation. This approval will remain in effect if no material substitutions or changes have been made.

Regulatory Requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Preservation, Packaging, Packing, Labeling and Marking. The preservation, packaging, packing, labeling and marking shall be as specified in the contract or order.

The Code of Federal Regulations (CFR) is for sale by the Superintendant of Documents, U.S. Government Printing Office, Washington, DC 20402.

NOTE: When this commercial item description is used for procurement the commercial item certification clause must appear in the solicitation.

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:18Z
Check the source to verify that this is the current version before use.