[Metric]
A-A-2116B
November 29, 1993
Superseding
A-A-2116A
June 1, 1989

COMMERCIAL ITEM DESCRIPTION

# FILING CABINETS, SHELF (STEEL, CONTEMPORARY STYLE)

General Services Administration has authorized the use of this Commercial Item Description in preference to Interim Federal Specification AA-F-00330.

Salient Characteristics. These characteristics concisely describe the essential physical and functional/performance characteristics of the commercially available items.

Design The filing cabinets shall be contemporary style, designed for heavy duty office use

Types and sizes.

Type I Adjustable shelves, no doors, closed base
Size 1 - Five openings

Type II. Retractable doors, fixed shelves, closed base
Size 1 - Five openings

Dimensions. Minimum inside clear dimension of openings 864 mm W x 305 mm D x 312 mm H.

Case The cabinet shall have solid panel sides, back and top, and adjustable glides. Type I cabinets shall have continuous adjustment increments of 38 mm on center, maximum, for shelf height. A 75 mm non-adjustable span in the vertical center of the cabinet is allowed for reinforcement Shelf supports shall be provided. Adjustable devices shall not be visible on outside of case. Cabinets shall be shipped set-up. Knock-outs shall be provided to allow cabinets to be bolted to each other and to the wall.

Shelves. The shelves shall be formed on all sides. Two



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

dividers shall be provided with each shelf. The shelf shall adjustment of dividers, with continuous adjustment spacing of 76.2 mm maximum on center

Doors. The doors shall be overhead retractable type, equipped with a hand grip. There shall be no metal to metal contact between doors and door guides Doors shall retract flush or recessed with the face of the cabinets.

Finish. The finish shall be semi-gloss baked enamel. Color shall match Federal Standard No. 595, black (27040), gray (26134), and parchment (within the range delimited by 26586 and 26405). Alternatively, the manufacturer may provide his commercial black or gray baked enamel finish subject to contracting officer approval

Identification label. The label shall have the contractor's name or trade mark, contract number, National Stock Number (if specified), and month and year of manufacture legibly marked with permanent dark ink The label shall be affixed to the back of the cabinet and shall not be removable by hand without defacement after being affixed for 4 hours.

Workmanship. The workmanship shall be of the quality to produce finished filing cabinets acceptable in appearance, function and serviceability and prevent potential hazard to personnel or their clothing.

Quality Assurance Provisions Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Sampling for inspection shall be performed in accordance with MIL-STD-105, unless an equal or better plan is approved by the contracting officer or his/her representative A lot shall consist of units of one type, size, style and color The sample shall be one each Inspection levels and AQL's shall be as follows:

For fit, finish and all other workmanship - Level II, AQL 6.5 defects per hundred units.

For packaging, packing and marking - Level S-2, AQL 4 0 percent defective.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

Any failure to meet the dimensions, color, identification label or performance requirements shall cause rejection of the lot.

Performance. Cabinets shall comply with the following requirements. Tests shall be performed in the sequence listed.

Rigidity. Test all types of cabinets. The cabinet shall be placed on a hard level surface and the base shall be restricted from lateral and vertical movement. All shelves shall be empty and all doors retracted (when applicable). A force of 178 N shall be applied perpendicular to the side of the cabinet within one inch of the top front corner The cabinet shall have failed the test if the deflection is in excess of 9.5 mm while the force is being applied The deflection measurement shall be taken along the top front edge of the cabinet

Door test Test only type II cabinets. The cabinet shall be placed on hard level surface. An evenly distributed load of 13.6 Kg per linear foot shall be placed on each shelf. The bottom edge of the closed door shall be grasped with the thumb and forefinger, with the thumb placed within four inches of the side The door shall be raised to a horizontal position where it shall engage the track The door shall then be pushed until it travels the full length of the track to the rear of the cabinet. The movements shall then be reversed by withdrawing the door the full distance of travel in the track and returning it to the closed position. This cycle shall be repeated at least five times The above procedures shall be duplicated with door grasped as specified herein, but with the thumb within four inches of the other side. The cycle shall be repeated at least five times A door shall be considered as having failed the test should it bind at any point in any cycle.

Static load. Test both type cabinets The cabinet shall be placed on a hard level surface A soft load (sand or shot) of 45.3 Kg shall be uniformly distributed over the shelf loaded or has any permanent deflection in excess of 5 5 mm after the load is removed, the cabinet shall be considered as having failed the test.

Regulatory requirement. The offeror/contractor is encouraged to use recovered material in accordance with Public Law 94-580 to the maximum extent practicable.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

Packaging, packing and marking. Packaging, packing, and marking shall be as specified in the Solicitation.

Notes.

Ordering options Purchasers should specify type

Finish sample A sample panel of the baked enamel finish is obtainable from the Business Services Administration, Washington, DC 20407, or from the Business Service Center in the nearest General Services Administration Regional Office.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.