A-A-2296
October 18, 1984

COMMERCIAL ITEM DESCRIPTION

LADDER, SAFETY STEP (STEEL, ROLLABLE)

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification RR-L-100.

This description covers safety steel rolling ladders with casters furnished in the following classes and sizes as specified.

Class 1 - Wide Base (25-1/2 to 36-1/2 inches)
Sizes - 1 to 12 steps inclusive, in one step increments.

Class 2 - Narrow Base (17-1/2 to 24 inches wide)
Sizes - 1 to 7 steps inclusive, in one step increments.

Salient characteristics.

Material. Shall be constructed of either plain carbon or alloyed steel.

Casters. Ladders 1 step to 7 step shall have four 2-inch or 3-inch diameter spring-loaded casters that retract when a person's weight is applied. Ladders 8 step to 12 step shall have one or two 3-inch or 4-inch diameter swivel casters on the front of the ladder with a level or foot pedal locking device and two 3-inch or 4-inch diameter rigid casters on the rear. Casters shall have a bolt rivet or bushing axle. The swivel type caster shall have a ball bearing race. All casters are to have a load rating of 250 pounds each.

Ladder Tips. Slip resistant, replaceable tips shall be part of the bottom of all ladder legs to prevent slipping after the casters are disengaged.

Steps. Shall be provided with slip resistant threads.

Finish. Shall be painted either aluminum, silver-gray, or gray.

Ladder Frame Construction. When partially assembled ladders are furnished, they shall consist on no more than seven sub-assemblies, sufficient bolts and self-locking nuts, and a clear set of instructions.

Conformance. Ladders shall be approved by a nationally recognized testing laboratory as having been tested in accordance with and meeting the requirements of Title 29, COde of Federal Regulations (CFR), Parts 1910.29 (a) and (f), latest revision on the date of the solicitation. This approval will remain in effect if no material substitutions or design changes have been made.

FSC 5440

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:21Z
Check the source to verify that this is the current version before use.

Workmanship. All exposed metal surfaces shall be free from sharp edges, burrs, or other safety hazards. There shall be no structural defects including deformed steps, handrails, frames, or frame and handrail sections. Welds shall be free of cracks and closely spaced in-line surface porosity. The ladders shall be free of defects which may affect durability, appearance, or serviceability.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

The Code of Federal Regulations (CFR) is for sale by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.

Note. 1) When this commercial item description is used for procurement, the commercial item certification clause must appear in the solicitation.

2) Users shall specify class and size desired.

Military Coordinating Activity
None. DoD has waived coordination on this commercial item description until further notice.

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.