A-A-2305
November 9, 1984

COMMERCIAL ITEM DESCRIPTION
COPYING MACHINE, INDIRECT ELECTROSTATIC PROCESS (PLAIN PAPER)

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers indirect electrostatic process copying machines having specific characteristics as hereinafter specified.

Classification. Copiers furnished under this commercial item description shall be of the following styles as specified:

Style 1 - no reduction capabilities required.
Style 2 - minimum of one reduction mode required.

Salient characteristics:

Copy machines shall be newly manufactured (not rebuilt or remanufactured).
Copy speed - 8 letter-size (8 1/2" X 11") copies per minute, minimum.
Maximum delivery time for first copy (after warmup) - 12 seconds.
To operate on 120 volts AC 60 Hz electrical current.
Self-diagnostic system consisting of a minimum of three (3) lighted indicators which identify (a) needing toner, (b) needing paper, and (c) paper misfeed or jam.
Paper tray (minimum of one to be furnished) capable of handling the paper sizes described below.
Capability to copy on the following mediums, as a minimum:
- (a) Plain cut sheet paper conforming to the requirements of commercial Item Description A-A-1912, two sizes; 8 1/2" X 11" and 8 1/2" X 14".
- (b) Self-adhesive labels.
- (c) Transparencies

Capability to copy pages of bound documents.
Shall be in accordance with U.L. Standard No. 114.
Multiple copy switch (minimum of 1-19 copies).
Capability to copy carbonless blues (see test procedure II).
Flat-bed platen capable of handling originals of up to 8 1/2" X 14".
Operator activated control which provides for darkening or lightening of copies.
Shall copy to within 7mm of the edge of the paper.
In style 2 machines the reduction mode shall produce copies that are 74 $\pm$ 4 percent the size of the original.

FSC 3610

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.

Performance requirements. The machine shall provide copies which have the following minimum qualities when tested as specified in Test Procedure I. Paper used for testing shall conform to the requirements of Commercial Item Description A-A-1912, issue in effect on the date of the Request for Proposal(RFP). Copies of the test targets presented as Figures I and II are for illustrative purposes only. Actual targets should be obtained from the sources referenced.

Resolution. The resolution shall equal or exceed 4.0 line pairs per millimeter.

Half-tones. The finished copy shall show at least three(3) distinct gray shades(excluding background).

Blackness, density. The solid darkest area on the finished copy shall show a reflectance of 10 percent or less. Adjacent background areas shall show a reflectance of 80 percent or greater.

Carbonless blue. The average reflectance shall be 50.0 percent or less.

Test procedure I. The copiers shall be installed in accordance with the manufacturer's normal commercial practice. Copies shall be made in accordance with the following procedure:

1. Turn on and warm up machine.
2. Place the resolution test target (Figure I) in position for reproduction.
3. Set the darkness/lightness control per the manufacturer's operating instructions. If no instructions are provided, the control shall be set at the middle of its range.
4. Make twelve(12) runs of 10 copies each. Runs shall be made at ten minute intervals so that the total copies are produced within a 2 1/2 hour period.
5. Remove the 11th, 55th, and 120th copies for evaluation.
6. Repeat steps 2 through 5 using the IEEE Test Chart (Figure II).

Evaluation: Evaluation of resolution shall be performed on copies produced from Figure I test target. Evaluation of half-tones and blackness shall be performed on copies produced from Figure II test target.

Resolution: Using a magnifier between 5X and 10X, determine the smallest line pair target in each target set which can be resolved. The line pair target is considered resolved when the lines (and spaces) are visibly separate. The resolution of the copiers shall be the lowest resolution value obtained from the 15 target sets on the three copies removed for evaluation.

Half-tones. Each of the three copies removed for evaluation shall be visually examined to determine that at least three distinct shades of gray are visible in both patterns 7 and 8 of the Test Chart. The white background shall not be considered a shade; the darkest step shall be considered a shade.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.

Blackness. The copies used for the half-tone evaluation also shall be visually examined to determine blackness of solid areas and whiteness of the background. Using a standard gray scale such as a "Munsell Neutral Value Scale", the observer shall visually compare patterns 7 and 8 on each copy to the gray scale, the observer shall determine the reflectance of the background by determining the reflectance of the first step of pattern 7 and the 15th step of pattern 8.

All six(6) dark area reflectance determinations shall comply with the reflectance requirement for the solid darkest area on the copy.

All six(6) background reflectance determinations shall comply with the reflectance requirement for the background area of the copy.

Test procedure II (Copying Carbonless Blues):

1. Turn on and warm up the machine.
2. Make five (5) copies each of the color standard charts - Hue symbol 5PB, 7.5 PB, and 10 PB from the "Munsell Book of Color, Matte Finish Collection" with the darkness/lightness control set to make the darkest copies .
3. From each group of 5 copies, choose the 5th copy and perform the evaluation.

Evaluation:

Take the 5th copy of the 5PB Hue Color Chart and, using visual evaluation, match the lightest symbol in the 7 Value(V) line wiht one of the neutral grays of the "Munsell Neutral Value Scale" and record the reflectance value.

Repeat the above using the 7.5PB and 10PB Hue symbols.

Take the average of the three reflectance values and use it to determine compliance with the performance requirements under Carbonless Blue.

Identification. Each copier shall have the manufacturer's serial number permanently and legibly stamped or affixed on a major component in a readily accessible location. In addition, each copier shall be permanently and legibly marked in a conspicuous location with the manufacturer's name or trademark.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practical.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.

Document Availability

U.L. Standard No. 114 is available from Underwriters Laboratories(UL) Inc., 333 Pfingsten Road, Northbrook, IL 60062.

Commercial Item Description A-A-1912 is available from General Services Administration, 7th and D Streets, S.W., Room 6039, Specification Section, Washington, DC 20407.

IEEE Standard 167A-1980, Facsimile Test Chart is available from the Institute of Electrical and Electronic Engineers, 50 East Huron Street, Chicago, IL 60017.

Microcopy Resolution Test Chart, Standard Reference Material 1010a is available from the Office of Standard Reference Materials, National Bureau of Standards, Washington, DC 20234.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:21Z
Check the source to verify that this is the current version before use.