[METRIC]
A-A-2610B
January 4, 1991
SUPERSEDING
A-A-2610A
July 18, 1989

COMMERCIAL ITEM DESCRIPTION

PULVERIZING MACHINE, PAPER, CLASSIFIED WASTE

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification FF-P-00810A.

This description covers paper pulverizing machines for use as specified by the user activity. The pulverizing machines shall be of the following sizes, as specified:

Size 0 - up to 8 sheets at a time. (Office use)
Size 1 - up to 34 Kg./hr.
Size 2 - up to 68 Kg./hr.
Size 3 - up to 136 Kg./hr.
Size 4 - up to 181 Kg./hr.
Size 5 - up to 363 Kg./hr.
Size 6 - up to 544 Kg./hr.
Size 7 - up to 726 Kg./hr.
Size 8 - up to 1089 Kg./hr.

Salient characteristics.

Machine type. Shall be either a rotary scissor knife mill or a dual hammer-mill.

Particle size. Shall not be larger than 2.4 mm.

Security screen. All pulverizers shall be equipped with a 2.4 mm security screen.

Electric motor. The pulverizers and pumps shall be powered by electric motors which are in compliance with the standards of the National Electrical Manufacturer's Association (NEMA). All motors shall be capable of developing sufficient power for the efficient operation of the machine at full load without overload. With the exception of Size 0 which requires 110 volts, single phase, 60 cycles the machines shall require 460 volts, three phase, 60 cycles.

Dust collector. A dust collector shall be provided that shall be capable of keeping the dust level in the operator's area below 1750 particles per cubic centimeter and below the explosion level.

Switches. Machine shall have on/off switches for both the disintegrator and pneumatic waste collection system.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.

Safety switch. Machine shall have a safety limit switch to insure "open circuit" condition during inspection and maintenance.

Instructions. Operating/maintenance manual and spare parts list shall be included.

Sound suppression options. Optional sound reduction enclosures or sound treatments shall be available from the manufacturer for all pulverizers, unless the specific pulverizer operates below 85 dBA. Such sound enclosures and treatments must reduce sound levels at the normal operator's work station to below the OSHA maximum level of 90 dBA.

Safety feed station design. The machine shall have a feed throat or hopper design that protects the operator(s) from any possible flying debris that may be ejected in the event of any rotor/cutter damage, or if it is fed improper materials such as metals. This should consist of a self-closing feed door design and/or baffling to catch flying debris ejected from the feed opening. In addition, the feed station shall be of such a design that users cannot reach the cutter mechanisms of the pulverizer through the feed opening.

Workmanship. All parts and accessories shall be fabricated and finished in accordance with good workmanship practices and the machine shall be free of any defects which might affect its durability, appearance or serviceability.

Conformance. Pulverizers shall be in compliance with the following:

1. OSHA Specification #1910.212A "machine guarding".
2. NEMA Standards.
3. Army Regulation #380-5.
4. DoD/NSA Requirements for destruction of all levels of classified paperwork, including COMSEC.
5. Underwriters Laboratories (UL) standards on all motors and electricals. Test reports or labels from a testing laboratory recognized by OSHA under Appendix A to 29 CFR 1910.7 are acceptable.
6. ISM (Industrial Security Manual for Safeguarding Classified Information).
7. OPNAVINST 5510.IG

QUALITY ASSURANCE PROVISIONS

Responsibility for inspection and testing. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. The supplier may use his own or any other test facility. Inspection records of the examinations and tests shall be kept complete and available to the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.

First article testing and approval. As prescribed by Federal Acquisition Regulation (FAR), Chapter 9, Part 3, the contractor shall furnish one or more machines as specified for examination and testing within the time frame specified to prove prior to starting production that his production methods and choice of design detail will produce machines that comply with the requirements of this document. Examination and tests as specified shall be subject to surveillance and approval by the Government.

Any changes or deviations of subsequently produced machines from the approved machine during production will be subject to the approval of the contracting officer. Approval of the first produced machine will not relieve the contractor of his obligation to furnish machines conforming to this document.

Performance requirements.

Acceptance test. The completely assembled machine shall be subjected to 2 hours of continuous operation. During this period typical paper filings material shall be fed into the machine. During the final hour of operation, the overall performance of the machine shall be determined. The machine shall function as intended by this specification; the amount of paper processed shall be not less than the capacity specified for its size; the particle size of the processed material shall not exceed the size specified; and the dust level in the operator's area shall not exceed the level specified.

Test conditions. The machine shall be connected to an appropriate electrical source in a suitable area with normal ventilation and of a size permitting freedom of movement for personnel attending the machine in the operator's area. The operator's area is from the point where the material is to be processed is fed into the machine to the point where the processed material is discharged into a collector bag. The machine may be vented to the outside and the pulverized material may be discharged through pipes or vents to an adjacent area provided that fittings and connections do not permit the escape of dust or pulverized material, and provided that the dust level at the point where the material is discharged into a bag does not exceed the level specified.

Visual inspection. The finished item shall be visually inspected to determine conformance to the machine description, salient characteristics and workmanship requirements of this document.

Failure to meet all provisions of this document shall provide reason for rejection of all machines in the lot.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.

level of competition without adversely affecting performance requirements or exposing supplier's employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling and marking. The preservation, packaging, packing, labeling and marking shall be as specified in the contract or purchase order.

Note: Purchaser shall specify Size Number and NSN when ordering.

Size 0	3615-01-298-2506
Size 1	3615-01-298-5585
Size 2	3615-01-298-2507
Size 3	3615-01-298-2508
Size 4	3615-01-298-2509
Size 5	3615-01-298-2510

UL standards may be obtained from Underwriters Laboratories, 333 Pfingsten Road, Northbrook, IL 60062.

NEMA standards may be obtained from the National Electrical Manufacturers Association, 2101 L Street, NW, Washington, DC 20037.

OSHA specifications may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

Army regulations may be obtained from the US Army Intelligence & Security Command, Arlington Hall Station, Arlington, VA 22212.

DOD/NSA requirements may be obtained from the NSA Agency, Communications Security Organization, Attn: Y263, Fort George Meade, MD 20755-6000.

Navy requirements may be obtained from the Chief of Naval Operations, Attn: Physical Security, Naval Institute, 55101F, Navy Department, Washington, DC 20350.

ISM requirements may be obtained from the Defense Investigative Services, Headquarters, 1900 Half Street, Washington,DC 20324.

The Code of Federal Regulations (CFR) is for sale by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(MAS 36-II, SIN 51-125)

MILITARY INTERESTS:

NONE

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.