[METRIC]
A-A-2855
October 19, 1995

COMMERCIAL ITEM DESCRIPTION

BLADE, RAZOR

The General Services Administration has authorized the use of this commercial item description, for all federal agencies

1 Scope. This commercial item description covers two types of razor blades for use in removing hair from human skin

Type I - Single edge, carbon steel

Type II - Double edge, stainless steel

2 Salient Characteristics:

2.1 Type I blades shall be single edge carbon steel with a carbon content of not less than 0.90 percent and no more than 1.05 percent

2.2 Type II blades shall be double edge stainless steel and meet the composition requirements in Table I

Table I. Type II blade composition requirements.

Element	% Minimum	% Maximum
Carbon	0.60	1.05
Chromium	12.0	---
Manganese	0.60	---
Silicon	0.15	---
Phosphorus		0.04
Sulfur		0.04

2.3 Hardness. The hardness of Type I and Type II blades, tested at the edge of the blade adjacent to the beveled cutting edge, shall not be less than 85 nor more than 93 on the Rockwell N superficial scale

2.4 The included angle of each cutting edge shall not be less than 17 degrees nor more than 27 5 degrees The cutting edge of Type I and both cutting edges of Type II blades shall be ground, honed,

Beneficial comments, recommendations, additions, deletions, clarification, etc., and any date which may improve this document, should be sent to: GSA, Paints and Chemicals Commodity Center, 400 15th Street, SW, Auburn, WA 98001

Distribution Statement: Approved for public release.
Distribution is unlimited.

FSC 8530

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.

and polished to razor sharpness and shall be free from cracks, bent edges, jagged ends, honed edge gouged out, or one side not honed Blades shall average not more than three each 0 0004 inch (1/100 mm) long nicks per edge (when viewed at 100 power magnification) and shall not be closer than 1/4 inch (6 4 mm) apart For the purpose of this description, a nick is defined as a chipped out, broken out, indented, bent out, semi-circular projection, or any similar gap, indentation, or projection, having a dimension greater than 0.0004 inch (1/100 mm) Nicks 0 0004 inch (1/100 mm) or smaller, or any nick appearing in the chamfered or curved portion at the ends of the cutting edge shall not be counted Type I blades shall be a minimum of 0.008 inch thick Type II blades shall be a minimum of 0 004 inch thick

2 5 Type I blades shall be equipped with a metal backing strip securely attached to the side opposite the cutting edge

2 6 When viewed on top of the cutting edge along the full length of the blade, each cutting edge shall be straight to within 0 0015 inch (0 04 mm) full indicator reading (FIR). The cutting edge shall be parallel to the opposite side to within 0 003 inch (0 08mm) FIR, when measured from the cutting edge to the opposite edge of the blade and at three equally spaced intermediate locations The blade surface shall be flat to within 0 003 inch (0 08 mm) FIR, when measured from one end of the blade to the other end

2 7 The finished surface of each blade, including the beveled cutting edges, shall be coated with a protective film that will prevent corrosion The protective film shall not have any ingredient which will cause skin irritation

2 8 The finished blade shall exhibit no evidence of jagged or rough work The blade shall be free from defects which may affect its serviceability durability or appearance

3 Certification The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices and is the same product offered for sale in the commercial marketplace The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract

4. Preservation, packaging, packing, labeling, and marking Unless otherwise specified, preservation packaging and packing shall be to the degree of protection to preclude damage to containers and/or contents thereof under normal shipping conditions, handling, etc., involving shipment from the supply source to the receiving activity, plus reshipment from receiving activity, and shall conform to applicable carrier's rules and regulations. Intermediate and external package quantities and labeling and marking shall be specified in the contract or order.

Preparing Activity

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.