[INCH-POUND]
A-A-2882
January 3, 1995

COMMERCIAL ITEM DESCRIPTION

DRAIN, LAVATORY

The General Services Administration has authorized the use of this commercial item description as a replacement for Type I of Interim Federal Specification WW-D-001991 for all federal agencies.

1. SCOPE

1.1 Scope. This commercial item description covers lavatory drains with tailpiece for use with domestic type lavatories.

2. CLASSIFICATION

2.1 Classification. The lavatory drains shall be of the following size, as specified (see 7-1) .

Size 1 - 2 inch (50.8 mm) outside diameter drain flange with 1-1/4 inch (31.7 mm) outside diameter tailpiece.

Size 2 - 2-1/4 inch (57.1 mm) outside diameter drain flange with 1-1/4 inch (31.7 mm) outside diameter tailpiece.

3. SALIENT CHARACTERISTICS

3.1 Standard product. Except as otherwise specified, lavatory drains covered by this commercial item description shall be the manufacturer's standard commercial product. Materials not specifically specified shall be the quality used in commercial practice

3.2 Construction. The lavatory drain tube shall be of copper alloy or stainless steel. The drain tube shall have crossbars, an overflow opening, and component parts consisting of a washer, jamnut, stopper, and chain. The tailpiece shall be a minimum of 6 inches (152.4 mm) in length measured from the bottom of the drain flange to the end of the tube.

3.2.1 Drain flange and tailpiece. The outside diameter tolerance of the drain flange and tailpiece shall be ± 1/16 inch (1.58 mm) .

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Engineering Group (7FXEE), 819 Taylor St., Fort Worth, Tx 76102

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

FSC 4510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

3.2.2 Jamnut and washer. The jamnut shall be provided with wrench flats and the washer shall be of a suitable elastomeric material designed to cushion the jamnut and form a water-tight joint between the lavatory and drain tube.

3.2.3 Stopper and chain. The stopper shall be of a one-piece solid rubber or suitable elastomeric material molded with a rubber post and provided with a copper alloy or stainless steel ring for attaching the chain. The stopper shall be compatible with the size of the lavatory drain specified (see 7.2) . The chain shall be of copper alloy or stainless steel not less than 10 inches (254.0 mm) in length, consisting of 1/8 inch (3.1 mm) or larger beads. The chain shall be provided with chain couplings attached to each end. One end shall be coupled to the stopper ring and the free end shall be for attaching to a chain stay.

3.2.4 Finish. The lavatory drain, chain, and stopper ring shall be finished in accordance with the manufacturer's commercial practice for stainless steel, or nickel plated for copper alloy.

3.3 Workmanship. Metal surfaces shall be free of sharp edges, burrs, and dents that may affect function and serviceability.

3.4 Measurement system. The values stated in inch-pound units are to be regarded as the standard. The metric values stated in parentheses are for information purposes only.

3.5 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within the tolerances specified and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

3.6 Commercial item. The use of the term "commercial item" in this document does not imply that any item or items offered are not required to conform with all requirements specified herein.

4. REGULATORY REQUIREMENTS

4.1 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR) .

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

5. QUALITY ASSURANCE PROVISIONS

5.1 Contractor Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

6. PACKAGING

6.1 Packaging. preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES

7.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable) .

Title, number and date of this commercial item description.
b. Size (see 2.1).
c. The preservation, packing, and marking desired.

7.2 National Stock Numbers (NSNS): The following is a list of NSNS that reference this CID. The list may not be indicative of all possible NSNS associated with this CID.

4510-00-202-7775 - Size 1 - 2 inch drain flange (see 2.1)
4510-00-252-3154 - Size 2 - 2-1/4 inch drain flange (see 2.1)

MILITARY INTERESTS:

Preparing Activity:
GSA-FSS

Review Activity:

DLA - CS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.