[METRIC]
A-A-421A
November 4, 1993
SUPERSEDING
A-A-421
April 21, 1980

COMMERCIAL ITEM DESCRIPTION

PITCHER, VACUUM

The General Services Administration has authorized the use of this commercial item description (CID) as a replacement for Federal Specification RR-P-375 which has been canceled.

1. SCOPE

1.1 Scope. This commercial item description covers a one-liter vacuum pitcher.

2. SALIENT CHARACTERISTICS

2.1 Design and construction.

2.1.1 Outer shell. The outer shell shall be formed of modified polystyrene or other suitable plastic.

2.1.2 Inner shell. The replaceable glass filler shall be formed of clear lime or borosilicate glass, fully annealed and shall be securely held within the body by means of a rubber retainer at the neck and a shock absorber at the bottom. The pitcher shall have a capacity of 1 liter, plus 0.25 liter, minus 0.1 liter.

2.1.3 Lip and handle. The lip and handle when not an integral part of the outer shell shall be formed of acrylonitrile-butadiene-styrene (ABS), clear acrylic plastic, or other suitable plastic.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Engineering Group (7FXEE), 819 Taylor St., Fort Worth, TX 76102

DISTRIBUTION STATEMENT A : Approved for public release; distribution is unlimited.

FSC 7350

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

2.1.4 Lid or float closure. The lid or float closure shall be double wall (airspace) watertight construction and shall fit closely over the neck to form a neat closure. The lid, if hinged, shall be operable by thumb pressure on a lid extension and shall be securely attached to the outer shell and lid. The hinge pin shall be made of corrosion-resisting steel or brass. When equipped with a float closure, there shall also be a removable outer lid to control the opening of the float closure.

2.2 Marking. The pitchers shall be marked with the manufacturer's name, trade name, or trademark of such known character that the source of manufacture may be readily determined.

2.3 Workmanship. The pitcher shall be clean, free from foreign matter and defects which may affect appearance or serviceability. The pitcher shall be free from mold marks, rough or sharp edges, scratches or deformities.

2.4 Commercial item. The use of the term "commercial item description" in this document does not imply that any item or items offered are not required to conform with all requirements specified herein.

3. REGULATORY REQUIREMENTS

3.1 FDA requirements. The material used in the pitcher shall meet the applicable requirements of 21 CFR 121, Federal Food, Drug, and Cosmetic Act.

3.2 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor certification. The contractor shall certify that the item meets the salient characteristics and the requirements of this commercial item description, and, except for any government unique requirements specified, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product offered for sale in the commercial marketplace, or is the same product that has been successfully been delivered to the government on a previous contract or purchase order. The government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

4.2 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.3 Sampling. The levels of inspection and acceptable quality levels (AQL's) shall be in accordance with MIL-STD-105.

4.4 Lot formation. All pitchers from the same manufacturer offered for delivery at one time shall be considered a lot for purposes of inspection.

4.5 Sampling for visual and dimensional examination. A random sample of pitchers shall be selected from each lot in accordance with inspection level S-4, AQL 4.0 expressed in terms of defects per hundred units. The sample unit shall be one pitcher. The sample pitcher shall be visually and dimensionally examined to verify compliance with table I and the remainder of this commercial item description. All dimensions are absolute as defined in ASTM E 29.

TABLE I - Examination for defects

Examine	Defect
Construction and Workmanship	Plastic materials not as specified. Inner glass missing or not as specified. Capacity not as specified. Lid or float closure not as specified. Evidence of mold marks, rough or sharp edges, scratches or deformities. Marking missing or illegible.

4.6 Examination for preparation for delivery. A random sample of shipping containers shall be selected from each lot for examination of the unit, intermediate, and shipping containers (as applicable) for conformance with the packaging, packing, and marking required in the contract or order. Samples shall be selected in accordance with inspection level S-2, AQL 6.5, expressed in terms of defects per hundred units. The sample unit shall be one shipping container.

5. PACKAGING

5.1 Preservation, packing, and marking. The preservation, packing, and marking shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Purchasers should include the following information in procurement documents (if applicable):

a. Title, number and date of this commercial item description.
b. The packaging, packing, and marking required.

6.2 National Stock Number (NSN). The following NSN corresponds to this CID: 7350-00-044-0653.

6.3 Sources of documents.

6.3.1 Sources of non-Government association documents.

ASTM E 29 - Standard Practice For Using Significant Digits In Test Data To Determine Conformance With Specifications is available from:

ASTM
1916 Race Street
Philadelphia, PA 19103

6.3.2 Sources of Governmental documents. Copies of Federal standards are available from the General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA, and the GSA Specifications Unit (3FBP-W), Suite 8100, 470 E. L'Enfant Plaza, S.W., Washington, DC 20407.

Copies of military standards are available from:

Standardization Documents Order Desk
Building. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094.

Copies of the Code of Federal Regulations (CFR) are available from:

Superintendent of Documents
US Government Printing Office
Washington, DC 20402.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

Military Coordinating Activity:

Army - GL

Custodians:
Army - GL
Navy - SA
Air Force - 99

Review Activities:
Army - MD, QM
Air Force - 84, 50

User Activity:
Navy - MC

Civil Agency Coordinating Activity:

VA - OSS

PREPARING ACTIVITY:

GSA - FSS

(DoD Project 7350-0265)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.