
MILITARY SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR-107/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the crystal unit described herein shall consist of this specification and the latest issue of MIL-C-3098.

Pertinent characteristics: 50 to 125 MHz; fifth mechanical overtone; noncontrolled; series resonance.



INCHES	MM
.002	.05
.008	.20
.017	.43
.150	3.81
.183	4.65
.192	4.88
.402	10.21
.435	11.05
.50	12.7
.530	13.46

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1 inch = 25.4 mm.
3. The type designator, frequency, and manufacturer's code shall be not less than .038 (.97 mm) in height and not less than .027 (.69 mm) in width.

FIGURE 1. Crystal unit - CR-107/U.

© denotes changes

FSC 5955

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:44Z
Check the source to verify that this is the current version before use.

© TABLE I. Requirements.

Requirement	Specified value or condition
Holder	HC-18/U or HC-43/U (MIL-H-10056/9)
Dimensions, marking, and configuration	See figure 1.
Frequency range	50 to 125 MHz, inclusive
Capacitance, shunt	6.0 ±0.5 pF
Mode of oscillation	Fifth mechanical overtone
Government reference standard test sets	TS-683/TSM and AN/TSM-15
Rated drive level	2.0 ±0.4 mW
Calibration values:	
Equivalent resistance	30 ohms
Voltage drop	.25 volts
Resonance	Series
Operating temperature range	-55°C to +105°C, inclusive
Frequency tolerance	±50 ppm
Equivalent resistance	60 ohms, maximum
Unwanted modes 1/	Method II
Shock:	
Frequency change permitted	±5 ppm
Equivalent resistance change permitted	±10 percent
Vibration: 2/	
Frequency change permitted	±5 ppm
Equivalent resistance change permitted	±10 percent
Thermal shock:	
Frequency change permitted	±5 ppm
Equivalent resistance change permitted	±10 percent
Aging:	
Frequency change permitted	±5 ppm

1/ The minimum unwanted mode effective resistance shall be at least three times that of the main mode, or 75 ohms, whichever is greater.

2/ Method 204 of MIL-STD-202, test condition A.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Air Force - 11, 99
DLA - ES

User activities:
Air Force - 17

Agent:
DLA - ES

Preparing activity:
Army - ER

(Project 5955-0623-17)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:44Z
Check the source to verify that this is the current version before use.