INCH-POUND
MIL-PRF-3098/84E
16 January 2006
SUPERSEDING
MIL-PRF-3098/84D
27 August 1997

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR108/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-3098.

Pertinent characteristics: 50 MHz to 93 MHz; fifth mechanical overtone; controlled; series resonance.

Inches	mm
.002	.05
.008	.20
.017	.43
.150	3.81
.183	4.65
.192	4.88
.402	10.21
.435	11.05
.500	12.70
.530	13.46



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Crystal unit - CR108/U.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:44Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1. 1/

Frequency range: 50 MHz to 93 MHz, inclusive.

Capacitance, shunt: 5.5 pF, maximum.

Frequency stability: ±2.5 ppm.

Mode of oscillation: Fifth mechanical overtone.

Operating temperature range (controlled): +80°C to +90°C, inclusive.

Frequency tolerance: ±10 ppm (including frequency stability).

Equivalent resistance: 50 ohms, maximum.

Operable temperature range: -55°C to +80°C and +90°C to +105°C.

Reference temperature: +85°C ±1°C.

Rated drive level: 1.0 mW, maximum.

Resonance: Series.

Shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Vibration high frequency: Method 204, MIL-STD-202, test condition A.

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Thermal shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Aging:

Frequency change permitted: ±3 ppm.

1/ These crystal units were previously fabricated using Air Force Technical Order 12-1-20 and/or Collins drawing numbers 289-2844 through 2858-00.

* Reference documents. In addition to MIL-PRF-3098, this document references the following:

MIL-STD-202

* The margins of this specification sheet are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:44Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Air Force - 11
DLA - CC

Review activities:
Air Force - 99

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5955-0811-19)

* NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:44Z
Check the source to verify that this is the current version before use.