INCH-POUND
MIL-PRF-3098/84G
1 November 2017
SUPERSEDING
MIL-PRF-3098/84F
6 March 2013

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR108/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-3098.

Pertinent characteristics: 50 MHz to 93 MHz; fifth mechanical overtone; controlled; series resonance.




FIGURE 1. Crystal unit - CR108/U.

AMSC N/A
FSC 5955

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:44Z
Check the source to verify that this is the current version before use.

Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.402	---	10.21
B	---	.183	---	4.65
C	---	.435	---	11.05
D	.184	.200	4.67	5.08
E	---	.530	---	13.46
F	.50	---	12.7	---
G	---	.150	---	3.81
H	.015	.019	0.38	0.48

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Type CR108/U, crystal unit - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:44Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1. 1/

Frequency range: 50 MHz to 93 MHz, inclusive.

Capacitance, shunt: 5.5 pF, maximum.

Frequency stability: ±2.5 ppm.

Mode of oscillation: Fifth mechanical overtone.

Operating temperature range (controlled): +80°C to +90°C, inclusive.

Frequency tolerance: ±10 ppm (including frequency stability).

Equivalent resistance: 50 ohms, maximum.

Operable temperature range: -55°C to +80°C and +90°C to +105°C.

Reference temperature: +85°C ±1°C.

Rated drive level: 1.0 mW, maximum.

Resonance: Series.

Shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Vibration high frequency: MIL-STD-202-204, test condition A.

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Thermal shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Aging:

Frequency change permitted: ±3 ppm.

1/ These crystal units were previously fabricated using Air Force Technical Order 12-1-20 and/or Collins drawing numbers 289-2844 through 2858-00.

Reference documents. In addition to MIL-PRF-3098, this document references the following:

MIL-STD-202-204

The margins of this specification sheet are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:44Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Air Force - 99

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5955-2017-007)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:44Z
Check the source to verify that this is the current version before use.