INCH-POUND
MIL-PRF-3098/85B
1 October 1997
SUPERSEDING
MIL-C-3098/85A (USAF)
11 April 1995

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR109/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-3098.

Pertinent characteristics: 10 MHz to 11.5 MHz; fundamental; controlled; antiresonance.



Inches	mm	Inches	mm
.002	.05	.150	3.81
.003	.08	.170	4.32
.005	.13	.175	4.45
.010	.25	.192	4.88
.025	.64	.250	6.35
.028	.71	.400	10.16
.030	.76	.420	10.67
.040	1.02	.460	11.68

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for ge neral information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Crystal unit - CR109/U.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:45Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 10 MHz to 11.5 MHz, inclusive.

Frequency tolerances:

Operating temperature range: ±0.002 percent.

Reference temperature: ±0.002 percent.

Room temperature: ±0.008 percent.

Frequency stability: ±0.0005 percent.

Mode of oscillation: Fundamental.

Reference temperature: 85°C ±2°C.

Temperature ranges:

Operating (controlled): +80°C to +90°C, inclusive.

Operable: -55°C to +80°C, inclusive.

Capacitance, load: 32.0 pF ±0.5 pF.

Rated drive level: 1.0 mW, maximum.

Calibration values:

Resistance: 11 ohms.

Crystal current: 15 mA.

Capacitance, shunt: 7 pF, maximum.

Equivalent resistance: 22 ohms, maximum.

Frequency change permitted: ±0.0004 percent.

Equivalent resistance change permitted: ±10 percent.

Vibration: Method 201, MIL-STD-202; double amplitude 0.036 inches or 10 gravity units, whichever is the limiting value. Frequency shall be cycled between 10 Hz and 500 Hz in 15-minute cycles.

Frequency change permitted: ±0.0004 percent.

Equivalent resistance change permitted: ±10 percent.

Aging:

Frequency change permitted: ±0.0005 percent.

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:45Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force -85

Review activities:
Air Force - 11, 17, 19, 99

Preparing activity:
DLA - CC

(Project 5955-0697-54)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:45Z
Check the source to verify that this is the current version before use.