NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/128C
27 September 1996
SUPERSEDING
MIL-L-11484/128B
14 January 1994

DETAIL SPECIFICATION SHEET

# LAPEL BUTTON, EXCEPTIONAL SERVICE MEDAL, UNIFORMED SERVICES, UNIVERSITY OF THE HEALTH SCIENCES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11484 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL: Red Brass

DIMENSIONS:
DIAMETER: 5/8 inch (1.59 cm) (REF)
THICKNESS (At Edge): 0.070 inch ± 0.010 inch (0.178 cm ± 0.025 cm)

FINISH: Nickel Plated, Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:52Z
Check the source to verify that this is the current version before use.

2. Attaching device shall be prong with pick and flat ball clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

3. The design of the lapel button is identical to the design on the obverse of the miniature size medal except the lug shall be removed during the trimming operation.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 45
Navy - NU

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
Navy - MC
Coast Guard - CG
DLA - CT

(Project No. 8455-0858)


Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:52Z
Check the source to verify that this is the current version before use.