NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/131C
27 September 1996
SUPERSEDING
MIL-L-11484/131B
14 January 1994

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, CIVILIAN SERVICE MEDAL, OFFICE OF THE SECRETARY OF DEFENSE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11484 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL: Red Brass

DIMENSIONS:
DIAMETER: 11/16 inch (1.75 cm) (REF)
THICKNESS (At Edge): 0.065 inch ± 0.010 inch (0.165 cm ± 0.025 cm)

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 4.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:53Z
Check the source to verify that this is the current version before use.

2. Attaching device shall be prong with pick and ball type clutch. The prong shall be 3/8 inch (0.95 cm) long and shall be centered on the reverse side and fused or soldered to the lapel button.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0858)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:53Z
Check the source to verify that this is the current version before use.