NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/137E
3 December 2020
SUPERSEDING
MIL-DTL-11484/137D
19 October 2015

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, COMMENDABLE SERVICE MEDAL, UNIFORMED SERVICE, UNIVERSITY OF THE HEALTH SCIENCES

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Copper, Flashed, Oxidized, Relieved, Matte Finish.

DIMENSION:
DIAMETER: 5/8 inch (REF)
THICKNESS (At edge): 0.070 inch $\pm$ 0.010 inch

ATTACHING DEVICE:
1. The attaching device shall be prong with pick and flat ball type clutch.

2. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:56Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the obverse Government furnished hub or die.

2. The design of the lapel button is identical to the design on the obverse of the miniature size medal except the lug shall be removed during the trimming operation.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Navy - MC
Air Force - 11

Preparing activity:
Army - IH

Review activities:
Navy - CG1
DLA - CT

(Project No. 8455-2021-067)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:56Z
Check the source to verify that this is the current version before use.