MIL-B-13207/2(ME)
12 August 1976

MILITARY SPECIFICATION SHEET

BODY, VAN, VEHICLE-MOUNTED,

ISO SIZE 20

This specification sheet is approved for use by the USA Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the ISO Size 20 van body described herein shall consist of this document and the latest issue of Specification MIL-B-13207.

REQUIREMENTS:

1. The van body shall be an ISO/ANSI Series 1, reefer freight container, designated 1C, having a nominal length of 6000 mm (20 ft.).

2. The maximum gross weight of both basic van body and its operating equipment payload shall not exceed the ISO/ANSI maximum of 20 tonnes (SI units) (44,800 lb.).

3. The basic van body shall mount on any vehicle and be handled by any ISO materials handling equipment having ISO bayonet twist locks compatible with ISO 1C, freight containers.

4. The van body shall be air transportable (see 3.9.1) in C-130, C-133, C-141, and C-5A aircraft. When necessary, the van body may be demounted from its vehicle component and air transported in two units.

5. The van body shall be equipped with 2 each combination air conditioner and heater units (see 3.10, Table II, (o) and 3.17).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:11Z
Check the source to verify that this is the current version before use.

6. ISO Size 20, semitrailer mounted:	
a. Semitrailer Payload Rating	Min. 20 tonnes (Ref. 44,800 lb.).
b. Semitrailer GVWR (TTMA RP No. 39)	Min. 20 tonnes plus semitrailer curb weight.
c. Overall Length (OAL)	Max. 318 in.
d. Suspension	Tandem (2-axle) type having a Min. 40,000 lb. rating.
e. Axles	2-ea. having Min. 46,000 lb. GAWR, total tandem hub ratings.
f. Tires and Wheels Assys	Total, Min. 5 ea.
g. Running Lamps	Total, Min. 9 ea.
h. Leveling Jacks	Total, Min. 4 ea.
7. ISO Size 20, truck mounted:	
a. Truck Payload Rating	Min. 100 percent of ISO/ANSI 1C Container Max. weight.
b. Truck GVWR per DOT	Min. 69,000 lb. GVWR.
c. Overall length	Max. 324-in.
d. Container Subframe	Compatible with any ISO/ANSI 1C container.

Custodian:
Army – ME

Preparing activity:
Army – ME

Review activity:
Army – AT

User activity:
Army - GL

Project 2510-A087-2

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:11Z
Check the source to verify that this is the current version before use.