MIL-C-13212B (MU)
15 November 1968
SUPERSEDING
MIL-C-13212A (MU)
4 September 1964

MILITARY SPECIFICATION

COMPONENTS, MOLDED, ASPHALT-ASBESTOS FILLED (FOR USE IN AMMUNITION SHIPPING CONTAINERS)

1. SCOPE AND CLASSIFICATION

1.1 Scope.- This specification covers components molded from asphalt-asbestos filled molding material and used in shipping containers for ammunition (see 6.1).

1.2 Classification

1.2.1 Grade and Color.-The components shall be of one grade, and shall be black in color unless otherwise specified.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons, General Specification for
MIL-P-43090 - Plastic, Asphalt, Asbestos Filled, Molding Material.

STANDARDS

FEDERAL

FED-STD-406 - Plastics, Methods of Testing.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection By Attributes (ABC-STD-105).
MIL-STD-109 - Quality Assurance Terms and Definitions.
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components.
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes.

FSC: 8140

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:12Z
Check the source to verify that this is the current version before use.

DRAWINGS

ARMY

8799117 - Stop, Packing for Fiber Container, for 90MM and 105MM Ammunition
9216180 - Support Assembly

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.-Components covered by this specification shall be molded of asbestos-asphalt material conforming to MIL-P-43090.

3.2 Dimensions and tolerances.-The dimensions and tolerances of the molded components shall be in accordance with the applicable drawings, specifications, contract, or purchase order. Draft angles, not to exceed 2 degrees (°) will be permitted where required to facilitate removal from the mold. Fillets, at the juncture of joining surfaces and edge radii, (not to exceed 0.035 inch), may be used if the fit of the component, as shown in the applicable assembly drawings, is not affected. Chamfers of 45 degrees, on sharp edges and corners not exceeding 0.10 inch, or 25 percent of the thickness of the area to which applied, (whichever is less), are permitted, providing the fit of the component, as shown on the applicable assembly drawing, is not affected.

3.3 Inserts.-Inserts shall be formed, finished, and located in accordance with the applicable drawings. Exposed surfaces of the inserts shall be free of irregularities, nicks, burrs, rust and distortions when examined visually, or as otherwise specified. Exposed surfaces shall not be contaminated with molding material.

3.4 Workmanship.-Molded components shall be free from dirt, chips, grease, surface moisture, any large voids or blisters. Components shall not be warped, chipped or cracked. Flash shall be removed and the area under former flash deposits made level with the surrounding surface. Molded components shall be essentially smooth, free from ridges, pits and grooves; however, occasional minor marks from knockout pins, finishing operations or sink marks are acceptable. Drilled, cut and machine areas shall be smooth and clean. Finished components shall be uniform in composition and color when examined visually.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:12Z
Check the source to verify that this is the current version before use.

3.5 Specific gravity.-The specific gravity of the molded components shall be 1.30, plus or minus 0.05, when determined in accordance with 4.4.1.

3.6 Marking on components.-Each molded component shall have molded thereon, the molder's trade mark, part or drawing number, and such other molded markings as may be required on the applicable drawings, specifications, contract or purchase order. Compliance shall be determined visually.

3.7 First article inspection.-This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:12Z
Check the source to verify that this is the current version before use.

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.
b. Number of units of product inspected.
c. Results obtained, by defect code, for all inspections performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.
f. Number of items in the lot.
g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission.-The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.3. The first article sample shall consist of 25 assemblies and 25 complete sets of parts (i.e., 25 each of every component and every subassembly) which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including statements of findings for materials, processes and tests. A sample containing known defects will not be submitted unless specifically authorized by the contracting officer. A first article sample, or portion thereof, as directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification as to significantly affect product uniformity as determined by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:12Z
Check the source to verify that this is the current version before use.

4.2.2 Inspections to be performed.-Assemblies and components will be subjected by the Government to any or all of the examinations or tests specified in 4.3 and 4.4 of this specification and any or all requirements of the applicable specifications.

4.2.3 If any assembly or component fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component to comply with any of the stated requirements.

4.3 Inspection provisions.

4.3.1 Lot formation.-The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer in one unchanged process, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. Changes to the process, specification, or drawings not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105. Unless otherwise approved by the contracting officer, the inspection lot size of end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period nor more than the largest monthly quantity contractually scheduled for delivery during the contract period. Inspection lots of components or subassemblies, other than the items of delivery, shall be homogeneous and of a size mutually convenient to both the contractor and the Government inspector.

4.3.2 Examination.-Inspection for Critical defects, (and Major defects, when so specified), shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with Standard MIL-STD-105 except that continuous sampling plans in accordance with Standard MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to individual characteristics listed, using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect, except where 100 percent inspection is specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:12Z
Check the source to verify that this is the current version before use.

4.3.3.1 Sampling.-The sampling plan for the following tests shall be in accordance with Standard MIL-STD-105. Random samples of molded components shall be selected at Level S-4.

TABLE I
Table of Defects (1)

Categories		Defects	Method of Inspection	Code No. (See 6.3)
Critical: None defined.				
Major:	AQL			
101.	1.0	Dimensions not as specified (see 3.2).....	Gage	01001
102.	0.40	Inserts not properly located (see 3.3) or fixed	Gage	01002
Minor:				
201.	1.5	Color incorrect (see 1.2.1).....	Visual	01003
202.	1.5	Evidence of poor workmanship (see 3.4).....	Visual	01004
203.	1.5	Component marking incorrect or missing.....	Visual	01005

(1) Applicable to components not procured to drawing.

4.3.3.2 Support assembly (see dwg. 9216180).

Categories	Defects	Method of Inspection	Code No. (See 6.3)
Critical: None defined.			
Major:	AQL 0.65 percent		
101.	Large outside diameter.....	Gage	02001
102.	Thickness at large diameter....	Gage	02010
103.	Packing stop missing or inverted	Visual	02002
104.	Core support missing.....	Visual	02003

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:12Z
Check the source to verify that this is the current version before use.

Minor:	AQL 2.5 percent		
201.	Small outside diameter.....	Gage	02004
202.	Location of core support from forward face.....	Gage	02006
203.	Inside diameter at forward face.....	Gage	02007
204.	Crimp of metal components incorrect.....	Gage	02008
205.	Evidence of poor workmanship (see 3.4).....	Visual	02009
206.	Draft angle incorrect.....	Visual	02011

4.3.3.3 Core-support (see dwg. 9216180)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Outside diameter	Gage	03001
Minor:	AQL 1.50 percent		
201.	Inside diameter.....	Gage	03002
202.	Thickness	Gage	03004
203.	Lugs missing or incorrect in number.....	Visual	03003
204.	Notches missing or incorrect in number.....	Visual	03005

4.3.3.4 Stop packing (see dwg. 8799117).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Inside diameter.....	Gage	04001
102.	Angle missing or incorrect....	Gage	04002

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:12Z
Check the source to verify that this is the current version before use.

Minor:		AQL 2.5 percent	
201.	Outside diameter	Gage	04003
202.	Diameter over curls	Gage	04004
203.	Thickness of flange	Gage	04007
204.	Protective coating missing or damaged	Visual	04005
205.	Surface finish	Visual	04006

4.3.4 Testing

4.3.4.1 Specific gravity (see 3.5), Major defect, Code No. 05001.-Sampling plans for this test shall be in accordance with MIL-STD-105, using inspection level S-2 and an AQL of 2.5 percent. Failure to meet the applicable requirement when tested as specified in 4.4.1 shall be cause for rejection of the lot.

4.3.5 Inspection Equipment.-The contractor shall have available and utilize correctly, gages, measuring and test equipment of the required accuracy and precision to perform inspection required. The Contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment and verification of its accuracy shall be supplied by the contractor for the performance of examination or test by the Government. The contractor will have available a set of master gages, standards and appropriate instruments for regularly scheduled calibration of his inspection equipment.

4.4 Test methods and procedures

4.4.1 Specific gravity.-The specific gravity of the molded components shall be determined in accordance with Method 5011 of FED-STD-406.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking.-Packaging and packing of molded components for shipment and storage shall be in accordance with the requirements of MIL-STD-1169, unless otherwise specified. Marking of containers shall be in accordance with MIL-STD-1169.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:12Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Color, if other than black is required (see 1.2.1).
c. Level of packaging and packing required (see 5.1)
d. Provisions for submission of first article samples.

6.2 Intended use.-Molded components covered by this specification are intended for use in packaging ammunition items. Some applications are: nose supports for artillery cartridges, holders for artillery ammunition primers, fuze supports.

6.3 Inspection code numbers.-The five-digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis.

Custodian:
ARMY-MU

Preparing Activity:
ARMY-MU

Project Number: 8140-A-158

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:12Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:12Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:12Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
PICATINNY ARSENAL
DOVER, NEW JERSEY 07801

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARM

COMMANDING OFFICER
United States Army
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:12Z
Check the source to verify that this is the current version before use.