MIL-P-13232B(Ord)
4 December 1959
SUPERSEDING
MIL-P-13232A(Ord)
22 January 1958

MILITARY SPECIFICATION

POST, AIMING, M1A2

1. SCOPE

1.1 This specification covers the Aiming Post M1A2, used to establish a line of sight for indirect fire with field artillery weapons.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

Military

MIL-F-13926	Fire Control Materiel: General Specification Governing the Manufacture and Inspection of
MIL-F-14619	Fire Control Parts, Equipment and Tools; Packaging of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

Ordnance Corps

F7687114	Post Aiming, M1A2

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Applicable requirements.- Unless otherwise specified herein, applicable requirements common to all fire control instruments, as specified in Specification MIL-F-13926, shall apply.

FSC 1290

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:15Z
Check the source to verify that this is the current version before use.

3.2 Materials.- Materials shall be in accordance with drawings and general specifications forming a part of this specification.

3.3 Alinement.- When assembled, the tubular length of the aiming post (approximately 90 inches) shall be parallel to a plumb line within 0.4 inch when the aiming post is rotated through 360 degrees.

3.4 Interchangeability.- Sections of the aiming posts shall be interchangeable with any mating sections submitted for acceptance. Assembly and disassembly shall be nonrestrictive and sections shall engage smoothly and be firmly secured under spring compression when in the locked position.

3.5 Temperature.- The assembled aiming post shall be subjected to temperatures of plus 150 degrees Fahrenheit and minus 40 degrees Fahrenheit for a period of three hours at each temperature and shall meet the requirements of 3.4 at these temperatures.

3.6 Workmanship.- The aiming post shall reflect the best quality of workmanship and shall be in accordance with applicable workmanship requirements in Specification MIL-F-13926.

4. QUALITY ASSURANCE PROVISIONS

4.1 Procedures.- The inspection and test procedures specified in this section are the minimum that shall be conducted to determine acceptability by the Government for Aiming Post, M1A2. The final Government tests shall be accomplished by the contractor or his agent and witnessed by the Government inspector, using contractor's equipment except where Government equipment is supplied.

4.2 Sampling.- Sampling, including lot size, shall be in accordance with Standard MIL-STD-105 and the acceptable quality levels as specified herein.

4.3 Inspection.- The Government inspector shall ascertain, prior to and during assembly, as well as after final assembly, that production components are in accordance with visual and dimensional requirements of this specification.

4.4 Materials.- A visual inspection of component parts shall be made during in-process production to determine compliance with 3.2. Where defects or inferior quality is evident, and the Government deems a material analysis necessary, the contractor will be requested to submit samples or specimens to the contracting officer for analysis and approval.

4.5 Acceptable Quality Levels (AQL's) and Classification of Defects (CD's).- The inspection shall be in accordance with AQL's and CD's specified in table 1 for all visual and dimensional inspection and functional tests. AQL's as specified in table 1 are expressed in percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:15Z
Check the source to verify that this is the current version before use.

TABLE 1

CLASSIFICATION OF DEFECTS

MAJOR AQL 1.5	Reqt Par.	Test Method
1. Alinement	3.3	Standard Measuring Equipment
2. Interchangeability	3.4	Manual
3. Temperature	3.5	Deep Freeze Chest and Oven
4. Workmanship	MIL-F-13926	Visual

4.6 Test methods and procedures.

4.6.1 Alinement.- This test is performed by placing the aiming post in a vertical position and rotating it 360 degrees. The tubular length of the aiming post shall be parallel with the plumb line within the specified tolerance of 3.3. Any error of alinement shall be measured with a scale or standard measuring equipment.

4.6.2 Interchangeability.- This test is conducted by changing sections of any mating section submitted for inspection and checking for smooth fit while engaging and disengaging sections. Each section shall be held firmly in position when locked under the compression spring.

4.6.3 Temperature test.- Temperature test consists of subjecting the assembled aiming post to temperatures as indicated in 3.5, and while at these temperatures, performing the interchangeability test indicated in 4.6.2.

4.7 Disposition of rejected lots.- All rejected lots shall be returned to the contractor for screening of defective characteristics. After corrections have been made, the lot shall be resubmitted for acceptance inspection as outlined in MIL-STD-105.

5. PREPARATION FOR DELIVERY

5.1 Packaging and packing.- The case shall be cleaned, preserved, packaged, packed, and marked in accordance with Specification MIL-P-14619 and the applicable packaging data sheet. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Applicable packaging data sheet number (see 5.1).
(c) Selection of applicable levels of preservation, packaging and packing (see 5.1).
(d) Applicable stock number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:15Z
Check the source to verify that this is the current version before use.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government incurs no responsibility nor any obligations whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any invention that may in any way be related thereto.

Custodian:

Army-Ordnance Corps

Preparing Activity:

Army-Ordnance Corps

GPO 886900

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:15Z
Check the source to verify that this is the current version before use.