MIL-C-60683(OS)
AMENDMENT 2
15 JULY 1986
SUPERSEDING
AMENDMENT 1
27 JULY 1973

MILITARY SPECIFICATION

CATAPULT, AIRCRAFT EJECTION SEAT: M4A1 REMANUFACTURED METAL PARTS ASSEMBLY

This amendment forms a part of Military Specification MIL-C-60683(MU), dated 17 February 1971, and is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.2 Delete in its entirety and substitute:

"2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the document which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

ANSI B46.1-78 Surface Texture (Surface Roughness, Waviness and Lay)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization Branch (5241), Indian Head, MD 20640-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of the specification or by letter.

AMSC N/A FSC 1377

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:55Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, NY 10018.)

(Nongovernment standards and other publications are normally available from the organization which prepares or which distributes the documents. These documents also may be available in or through libraries or other informational services.)"

PAGE 5

4.2.1.2, delete in its entirety and substitute:

"4.2.1.2 Size of lot. A lot shall consist of an identifiable group of metal parts assemblies provided the homogeneity of the remanufacture process has been retained throughout the inspection lot."

* 4.2.2, line 2, change "ASA B46.1" to "ANSI B46.1-78".

4.2.2, add to the end of the paragraph, "Ring, Tube, Stop P/N D8593673 shall be visually examined 100% for groove at internal threaded end. Rings without groove shall be modified and reprocessed."

PAGE 6

4.2.2.3, delete C.D. "101" in its entirety.

PAGE 7

4.2.2.5, delete C.D. "102" in its entirety.

PAGE 8

4.2.2.6, delete C.D. "104" in its entirety

delete C.D. "105" in its entirety and substitute "105. Depth of internal thread cavity, min., . . . Gage".

delete C.D. "204" in its entirety and substitute "204. Depth of internal thread cavity, max., . . . Gage".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:55Z
Check the source to verify that this is the current version before use.

PAGE 9

4.2.2.8, delete C.C. "102" in its entirety.

PAGE 10

4.2.2.10, delete C.D. "102" in its entirety.

PAGE 11

4.2.2.12, delete C.D. "102" in its entirety.

PAGE 12

4.2.2.14, delete C.D. "102" in its entirety.

4.2.2.16, delete C.D. "102" in its entirety.

PAGE 13

4.2.2.17, delete C.D. "102" in its entirety.

* Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Preparing Activity:
Navy - OS
Project No. 1377-N822

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:55Z
Check the source to verify that this is the current version before use.