MILITARY SPECIFICATION

CARTRIDGES, DELAY, MARK 4 MOD 2, MARK 5 MOD 2
AND MARK 6 MOD 2

This amendment forms a part of Military Specification MIL-C-81788(AS) of 6 August 1970, and has been approved by the Naval Air Systems Command, Department of the Navy.

Pages 9 and 10

4.7.7.1, delete and substitute:

"4.7.7.1 The number of cartridges selected from each production lot for the ballistic test shall be in accordance with the requirements of MIL-STD-105, Inspection Level II, for an AQL of 0.15, single sampling plan for normal inspection. The sample shall be randomly divided into three equal groups. If the sample does not divide evenly, the odd cartridges shall be placed in the third group. Samples in Group 1 inserted in the sleeve (Drawing 2838190), of the test set (Drawing 2838183), shall be conditioned at -65° ± 5°F for not less than six nor more than twenty-four hours and fired in the test set within two minutes after removal from conditioning. Samples in Group 2 inserted in the sleeve (Drawing 2838190), of the test set (Drawing 2838183), shall be conditioned at +160° ± 5°F for not less than six nor more than twenty-four hours and fired in the test set within two minutes after removal from conditioning. Samples in Group 3 inserted in the sleeve (Drawing 2838190), of the test set (Drawing 2838183), shall be conditioned at +70° ± 5°F for a minimum of six hours and fired in the test set within two minutes after removal from conditioning. In addition to the sample of cartridges for the above tests, ten additional cartridges shall be furnished from the production lot for investigative purposes."

Project No. 1377-N494

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:09Z
Check the source to verify that this is the current version before use.