MIL-G-62176(AT)
AMENDMENT 1
28 March 1979

MILITARY SPECIFICATION

GUN, TWIN 40 MM, SELF-PROPELLED M42 AND M42A1
(OVERHAUL)

This amendment forms a part of Military Specification MIL-G-62176(AT), dated 13 August 1973.

PAGE 2

2.1, under "STANDARDS, MILITARY"; Delete the following:

"MIL-STD-417 - Rubber Compositions, Vulcanized, General Purpose, Solid (Symbols and Tests)."

2.1, under "STANDARDS, MILITARY"; Add the following:

"MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of."

"MIL-STD-1474 - Noise Limits for Army Materiel."

2.1, Following "Master Lists," add the following:

"TECHNICAL BULLETINS

ARMY

TB-MED-251 - Noise and Conservation of Hearing.
TB-MED-269 - Carbon Monoxide Symptoms, Etiology Treatment and Prevention of Overexposure."

PAGE 3

3.2.1, Delete entire paragraph, and substitute;

"Ozone resistance. When rubber components are required to be ozone resistant, the degree of resistance shall be as specified in applicable specifications or drawings."

FSC 2350

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:21Z
Check the source to verify that this is the current version before use.

PAGE 4

3.3.5, Delete entire paragraph and substitute:

"Exhaust system. Concentrations of toxic fumes in the crew compartment shall not exceed 50 parts per million (ppm) for carbon monoxide (CO) and not more than 5 ppm for oxides of nitrogen ($NO_X$). $NO_X$ is a term used to describe all compounds containing oxides of nitrogen. The exhaust system, as installed, shall be gas tight and leak proof as stated in TB-MED-269. The toxic fume limitation considers operation of heater when installed."

PAGE 11

Add new paragraphs as follows:

"3.9 Vibration and noise. With sound level meter located in the vicinity of the driver's right ear, and with the vehicle traveling at 30 mph in a 1-2-3 gear range on a hard-surfaced straight road, with all hatches and door closed, the sound level shall not exceed the following values:

a. When using the "C" weighting position of the sound level meter, the noise level shall not be more than 128 decibels (db).
b. When using the "B" weighting position of the sound level meter, the noise level shall not be more than 124 db.
c. When using the "A" weighting position of the sound level meter, the noise level shall not be more than 119 db.

3.9.1 Noise hazard caution sign. The vehicle driver and passenger compartments shall be posted as noise hazardous areas as specified in MIL-STD-1474. While vehicle is in operation, driver and all passengers shall be provided hearing protection as specified in TB-MED-251."

PAGE 19

Table IV, Add the following test after "Carbon dioxide distribution test":

"

| Title | Paragraph No. | Government Proving Grounds |
|---|---|---|
| Vibration and noise test | 4.5.3.13 | X |

"



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:21Z
Check the source to verify that this is the current version before use.

PAGE 29

4.5.3.3, Delete entire paragraph and substitute:

"Exhaust system and carbon monoxide test. To determine conformance to 3.3.5, the exhaust system shall be examined for proper installation and absence of leaks. Carbon monoxide and $NO_x$ levels shall not exceed that specified."

PAGE 30

4.5.3.11, Line 2: Add "in accordance with MIL-STD-462" after "test".

Add the following new paragraph:

"4.5.3.13 Vibration and noise test. To determine conformance to 3.9, the vehicle noise level measured at the location indicated shall not be more than the specified db, when measured with a sound level meter which meets the requirements of MIL-STD-1474. Driver and passenger compartments shall have signs posted indicating noise hazard, as specified in 3.9.1."

5.1: Delete entire paragraph, and substitute;

"Vehicle processing. Preservation/processing shall be in accordance with MIL-G-45178 for the level(s) specified by the procuring activity (see 6.2)."

6.2: Delete subparagraph (b) in its entirety and substitute;

"(b) Selection of level(s) of preservation/processing for shipment and storage (see 5.1)."

Custodian:
Army - AT

Preparing activity:
Army - AT

Project No. 2350-A284



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:21Z
Check the source to verify that this is the current version before use.

1 DoD contractors, government activities, or manufacturers' vendors who are prospec...