MIL-K-81786/5A(AS)
21 MAY 1986
SUPERSEDING
MIL-K-81786/5(AS)
20 April 1972

MILITARY SPECIFICATION SHEET

KIT TUBING, PLASTIC, IRRADIATED POLYOLEFIN, FLEXIBLE ELECTRICAL INSULATION, HEAT SHRINKABLE: SHRINK RATIO 4 TO 1

The complete requirements for procuring the plastic tubing described herein shall consist of this document and the issue in effect of MIL-K-81786(AS).

REQUIREMENTS: The tubing shall meet the requirements of MIL-I-23053/5

Sizes - See table I
Type - tubular
Material - Polyolefin
Color - Black
Length - See Table I

TABLE I. Dimensions.

Part No.	Dimensions (inch)				
	As Supplied		After Heating		Length
	I.D. min	I.D. max	Nominal Wall Thickness	Wall Thickness Tolerance	(ft)
M81786/5-1	1.000	.275	.045	± .005	8
M81786/5-2	2.000	.550	.045	± .005	4
M81786/5-3	3.000	.810	.045	± .005	4
M81786/5-4	4.000	1.050	.045	± .005	4

Preparing Activity:
Navy - AS
(Project No. 4940-N512)

AMSC N/A

FSC 4940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:09Z
Check the source to verify that this is the current version before use.