MILITARY SPECIFICATION

LAUNCHER, ROCKET, AIRBORNE, LAU 61 A/A

This specification has been approved by the Naval Air Systems Command, Department of the Navy.

1. SCOPE

1.1 Scope- This specification covers a dual purpose, airborne, external store type, rocket launcher capable of shipping, storing and launching nineteen 2.75 inch Folding Fin Aircraft Rockets (FFAR). This launcher is used in two configurations as follows:

(1) Shipping Configuration - Drawing Number 30003-356AS223. The center section of this package conforms to Drawing Number 30003-356AS224 for nineteen 2.75 inch FFAR and shall be identical with the center section of the Flight Configuration.

(2) Flight.Configuration A reusable, streamlined, airborne launcher utilizing the center section of the rocket Shipping Configuration, Drawing Number 30003-356AS223 plus two (2) fairings as specified in paragraph 3.3.2.

2* APPLICABLE DOCUMENTS

2.1 The following documents of this issue in effect on the date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-N-18307	Nomenclature and Nameplates for Aeronautical Electronic and Associated Equipment
MIL-E-5400	Electrical Requirements
MIL-P-116	Preservation, Methods of

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:12Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-143	-	Specifications and Standards, Order of procedure for the selection of
MIL-STD-109	-	Inspection Terms and Definitions
MIL-STD-810	-	Environmental Test Methods
MIL-STD-129	-	Marking for shipment and storage
MIL-sTD-889	-	Metals, Dissimilar
MIL-STD-1322	**-**	Palletizing Domestic Unit Loads of Weapon Components

DRAWINGS

NAVAL AIR SYSTEMS COMMAND

IL356AS228	Drawing Index List, Launcher, Rocket LAU 61 A/A

PUBLICATIONS

NAVAL AIR SYSTEMS COMMAND

AS-1142	Intervalometers, Purchase Description
WR-54	Naval Weapons Requirements Palletizing Fleet Issue Unit Loads
wR-54/174	Naval Weapons Requirements, Palletizing

Copies of Specifications, Standards, Drawings and Publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.

3. REQUIREMENTS

3.1 Samples

3.1.1 Preproduction Samples - Prior to beginning quantity production, preproduction samples shall be subjected to preproduction testing as specified herein.

3.1.2 Production Lot Samples - Production Lot Samples shall be submitted to a laboratory designated by a government agency for tests in accordance with the requirements specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T06:12Z
Check the source to verify that this is the currentversion before use.

3.2 Parts and Materials - Parts and Materials used in the manufacture of the rocket launcher package shall conform to the applicable specifications as set forth herein and as listed on the pertinent drawings.

3.2.1 Dissimilar Metals - Unless suitably protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MIL-sTD-889.

3.2.2 Selection of Materials - Specifications and Standards of all materials and parts and Government Certification and approval of processes and equipment, which are not specifically designated herein, and which are necessary for the execution of this specification, shall be selected in accordance with MIL-STD-143.

3.2.3 Standard Parts - Standard parts (MS, AN or JAN) shall be used wherever they are suitable for the purpose, and shall be identified on the drawing by their part number. Commercial utility parts such as screws, bolts, nuts, cotterpins, etc., may be used provided they possess suitable properties and are replaceable by the standard parts (AN, MS, JAN) without alteration, and provided the corresponding standard part numbers are referenced in the parts list and, if practicable, on the contractor's drawings. In the event there is no suitable corresponding standard parts in effect on date of invitation for bids, commercial parts may be used provided they have been certified, accompanied by objective quality evidence (as defined under MIL-STD-109) that the parts are to all the requirements of this specification.

3.2.4 Interchangeability - All parts having the same part number shall be completely interchangeable with each other with respect to installation and performance. Parts joined together as by welding or riveting shall be interchangeable as assemblies.

3.3 Design and Construction

3.3.1 General - The design and construction of the launchers shall conform to drawings listed on IL356AS228 No departure from, revision or change to the drawings specified herein shall be permitted without prior approval of the procuring agency. In the event changes are approved, the contractor shall furnish the procuring activity with reproducible drawings covering the change. Conformance to the drawings will not relieve the contractor of the requirements of paragraph 3.2.4.

3.3.2 Forward and Aft Fairings - The launcher shall have a streamlined Forward Fairing which shatters upon rocket impact. The Aft Fairing shall have an open end and shall be capable of being used for several firings.

3.3.2.1 Fairing Design - Fairings shall remain intact on the launcher center section without crushing under flight conditions of 600 knots IAS at 1000 feet altitude above sea level at 9,0g's positive and 2.Og's negative loading. The Forward Fairing shall also withstand a 435 pound side load and a 1390 pound axial load without crushing. Fairing frangibility shall not be adversely effected by exposure to 100 percent relative humidity at 38 degrees C for 24 hours.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T06:12Z
Check the source to verify that this is the currentversion before use.

3.3.2.2 Fairing Rings - The Forward Fairing Ring and Aft Fairing shall remain Attached to the' launcher after firing.

3.3*3 Nomenclature and Nameplates - Nomenclature assignment and name plate approval for equipment identification shall be in accordance with specification MIL-N-18307.

3*3.4 Manufacturing and Finishes - Manufacturing processes and finishes other than shown on applicable drawings shall receive prior approval of the procuring activity. The responsibility for any malfunction or failure of the component parts or the assembled equipment to pass the requirement tests due to fits, proper application of process, clearances, tolerances or internal stress shall be assumed by the contractor.

3.3.5.1 Intervalometer - Reusable, selective capability single or ripple fire; ripple approximately 60 millisecond intervals and shall conform to the requirements of drawing number 30003 356AS172.

3.3.5.2 Detents - Each launcher shall be checked to ensure that each detent projects into the tube 0.200 + 0.037 or -0.023 inch.

3.3.5.2.1 Detent Pull Release - A detent pull test shall be performed on each tube of the launcher. The pull load required to release the rockets from their detents shall not be less than 290 pounds foward load and shall not be pull tested above 325 pounds foward load applied at a linear rate to peak in 10 to 45 seconds.

3.3.5.3 Tube WarPage - The tube shall accept a 2.800 +.002 -.000 inch diameter by 8 inch long gauge in the forward end of the tube and shall pass thru the tube freely to the detent assembly.

3.3.6 Radiation Hazard Protection - An R.F. Barrier Assembly shall be fixed on the Forward and Aft Bulkhead. A switch with pull pin shall be included in the electrical system to provide safety when loading or off-loading rockets.

3.3.7 Launcher Firing Circuit - The launcher shall function properly with 20-30 volts direct current supplied through a 5 ohm resistance provided in the aircraft rocket firing circuit.

3.3.7.1 Grounding- The resistance between negative firing contacts (detents) and the suspension lug inserts and pin E of the receptacles shall not exceed 0.1 ohms.

3.3.7.2 Circuit Resistance- The resistance of any wire in the launcher firing circuit shall not exceed 0.1 ohms.

3.3.7.3 Circuit Continuity- There shall be no loss of circuit continuity owing to the handling or environmental conditions specified in Section 4.5.4. A continuity check shall be made with the safe-arm switch "on" and "off" to determine whether the switch is operating.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T06:12Z
Check the source to verify that this is the currentversion before use.

3*3.7.4 Simulated Firing Test - The intervalometer shall be operated once each in the "ripple" and "single" modes with an input voltage of **20** to 30 volts.DC through a 5 ohm 200 watt resistor. A Dummy Load consisting of a 1.0 ohm resistance for a 10 ± 2.0 ms duration shall be connected between each tube firing contact and ground. The firing and stepping times in each mode shall be within the tolerances specified by As1142.

3.3.8.1 Rough Handling- The launcher package shall be prepared and tested in accordance with paragraph 4.5.3.

3.3.8.1.2 Pressure Retention - The launcher shall be prepared and tested in accordance with 4.5.3.1.

3.4 Reliability and Performance - The launcher shall safely and reliably carry and launch nineteen 2.75 inch Folding Fin Aircraft Rockets from high performance-aircraft under combat environmental conditions without failure. The launcher shall meet the environmental requirements of section 4 of this specification and there shall be no failure to launch owing to malfunctioning of the launcher under any of the test conditions of section 4. The launcher shall be capable of being fired repeatedly if'it is not damaged by misuse or rough handling.

3.5 **Quality**

3.5.1 Workmanship - Workmanship shall be of sufficiently high grade to insure proper operation and service life and shall be acceptable to the procuring activity. All electrical components shall be installed in accordance with the workmanship requirements of MIL-E-5400.

3.5.2 Maintainability - The launcher shall be of-a design that maintenance and servicing requirements shall be held to a minimum.

3.5*3 Useful Life - The minimum useful service life of the launcher shall be determined by the firing of a single tube of a launcher and performing a Detent Pull Test, 4.5.5, after each firing. Twenty firings per tube shall be minimum.

3.6 Environmental Requirements - The Launcher shall be tested in accordance with paragraph 4.5.4 and shall meet the requirements of 3.3.7 after or during, as applicable, exposure to the following environmental conditions: (MIL-STD-810) .

a) Moisture Penetration Resistance Test (4.5.4.1)
b) High Temperature (4.5.4.2)
c) Low Temperature (4.5.4.3)
d) Salt Spray (4.5.4.4)
e) Waterproofness (4.5.4.5)
f) Vibration (4.5,4.6)
g) Shock Test (4.5.4.7)

3.7 Static Loading - The launcher shall be tested in accordance with 4.5.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:12Z
Check the source to verify that this is the current version before use.

3.8.1 Ground Firing - The launcher shall be mounted, loaded and fired in accordance with 4.5.7. All rockets must ignite and leave the launcher in a normal manner. The launcher shall remain intact and sustain no damage except for darkening of exposed surfaces.

3.8.2 Flight - A launcher shall be prepared and tested in accordance with 4.5.8.

3.9 Design Data - No data is required by this specification other than reports accompanying samples submitted for testing or by applicable documents referenced in section 2 unless specified in the contract or order (see paragraph 6.4).

4.0 Quality Assurance Provisions

4.1 Responsibility for Inspection - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Classification of Tests - Launchers shall be subjected to the following tests to determine compliance with all applicable requirements.

(1) Preproduction Tests (4.2)

(2) Quality conformance inspection (4.3)

4.2 Preproduction Tests - Preproduction Tests are those tests which are conducted by the contractor and the Government on the first ten launchers provided by production methods under contract. These preproduction samples shall have passed the individual test in 4.3.1, conducted by the contractor, prior to their delivery to a laboratory facility designated by the procuring activity.

4.2.1 Scope of Test - The Preproduction Tests shall include all tests of 4.5 arranged in the same order.

4.2.2 PreProduction Approval - Approval of the preproduction samples shall be by the procuring activity upon satisfactory completion of all tests. No production equipment of lot samples shall be delivered prior to approval of the preproduction samples. Prefabrication of production equipment prior to the approval of the production samples is at the contractor's own risk.

4.3 Quality Conformance Inspection - Acceptance of equipment shall be on a lot basis. Each lot shall be composed of equipment which has passed the individual tests. Acceptance Tests shall consist of the following:

(1) Individual Tests (4.3.1)

(2) Sampling Tests (4.3.2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:12Z
Check the source to verify that this is the current version before use.

4.3.1 Individual Tests - Individual tests shall be accomplished under the responsibility of the contractor, on each launcher submitted for acceptance under the contract. The contractor shall maintain test reports showing the quantitative results for individual tests. Such reports shall be signed by an authorized representative of the contractor and.this data shall be made available to the procuring activity upon request. Individual tests shall consist of the following:

(1) Examination of Product (4.5.1)

(2) Functional Tests (4.5.2)

4.3.2 Sampling Tests - Sampling Tests shall be conducted at a Government designated laboratory facility under the responsibility of the procuring activity. Sampling tests shall be conducted on samples selected from lots of equipment which have passed the individual tests, Samples to be tested shall be selected at random by the Government Inspector in accordance with the following lot schedule and forwarded to the designated laboratory facility for testing. Sampling tests shall consist of all tests of 4.5.

4.3.2.1 Lot - For inspection and test purposes, the quantities listed below shall comprise the lot sizes and the number of test samples to be inspected from each lot.

Quantity Offered for Lot Acceptance	to be tested
1-125	1
125-300	2
300-500	4

4.3.3 Reflection and Retest - If any sample fails to pass the tests specified herein, another random sampling of the same size will be submitted. Failure of the second sampling shall cause the entire lot to be rejected. Rejected lots may be reworked and resubmitted for retest upon approval by the Naval Air Systems Command.

4.4 Test Conditions - Except where otherwise specified, all tests required by this specification shall be made at normal room temperatures and barometric pressure, with a relative humidity of 80 percent or less.

4.4.1 Test Power - The power source for firing tests shall be 20-30 volts DC supplied through a 5-ohm resistor.

4*5 Test Methods

4.5.1 Examination of Product - Each launcher shall be examined for conformance to the drawings and this specification with respect to workmanship, dimensions, marking and examination of the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:12Z
Check the source to verify that this is the current version before use.

4.5.1.1 Detents - Each launcher shall be checked to insure that each detent projects into tube the required amount per 3.3.5.2 and Detent Release per 3.3.5.2.1.

4.5.1.2 Ignition System - Continuity of the electrical circuits comprising the ignition system shall be checked on each unit manufactured (3.3.7.3). Resistance readings shall conform to the values specified, (3.3.7.2). The grounding circuit resistance through the rocket detents shall also be checked (3.3.7.1). A simulated firing shall be performed with the results as specified in 3.3.7.4.

4.5.2 Functional Tests

4.5.2.1 Warpage and Fit Test - Each tube of each launcher shall be checked to assure that the rockets may be inserted without using force, The fit shall be free running per paragraph 3.3.5.3

4*5*3 Rough Handling Tests - The launcher package shall be loaded with nineteen 2.75 inch FFAR rockets and assembled as specified for the Shipping Configuration. (See 1.1). The loaded launcher package shall be dropped four times onto a solid concrete surface, falling freely through a vertical distance of 30 ± 1 inches and striking at an angle of 45 degrees (± 1 degree) on the flats of the end pans. The forward end of the launcher is to strike the concrete first on two of the drops (180 degrees between impact points on each drop); the aft end of the package is to strike the concrete first on the other two drops (180 degrees between impact points of each drop). The rocket launcher package must survive the rough handling tests sustaining only superficial damage. The shipping pan assemblies must remain tightly attached to the center section throughout the tests.

4.5.3.1 Pressure Retention Test - A suitable air connection shall be installed in the face of the test launcher shipping end. The launcher shall be immersed in water, not less than one inch or more than two inches, and air shall be introduced to produce an internal pressure of 5 psig for 30 seconds. Evidence of air leakage by escaping air shall be cause for rejection.

4.5.4 Environmental Tests

4.5.4.1 Moisture Penetration - An approximate one pound bag of completely reactivated desiccant shall be placed in a launcher in the Shipping Configuration. The launcher shall be conditioned for twenty four (24) hours at thirty eight (38) degrees plus or minus two degrees centigrade and 95 percent±5% relative humidity. After conditioning a freshly weighed, approximately one pound bag of completely reactivated desiccant shall replace the desiccant bag in the launcher. The launcher shall then be exposed for a period of 64 to 68 hours, after which the launcher opened and the bag of desiccant reweighed. The weight increase shall not exceed 0.07 grams per 100 square inches of external launcher surface area for 24 hours and shall be calculated as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:12Z
Check the source to verify that this is the current version before use.

$$\text{Transmission Rate} = \frac{(W2-W1)\ 2400}{T \times A}$$

W_1 = Weight (grams) at start Of exposure period

W_2 = weight (grams) at end Of exposure period

A = Area (total exposed in square inches)

T = Exposure period (64 to 68 hours)

4.5.4.2 High Temperature - The launcher, in the Shipping Configuration, shall be placed in a heated chamber and the internal temperature of the chamber raised, at a rate not to exceed 10°C (18°F) per minute, to 71° ±2.5°c (160° ±5°F) with a relative humidity of not more than 15 percent and remain at this condition for a period of 50 hours. At the end of the conditioning period, while still at elevated temperature, an electrical ignition system check shall be made in accordance with 3.3.7. The launcher shall then be allowed to cool to ambient temperature and the electrical ignition test 3.3.7 shall be performed.

4.5.4.3 Low Temperature - The launcher, in the Shipping Configuration, shall be placed in a cooling chamber and the internal temperature of the chamber reduced at a rate not to exceed 10°C (18°F) per minute until a temperature of -54.0 ± 2.5°C (-65 ±5°F) is attained. This condition shall be maintained for a period of twenty four hours. At the end of the conditioning period, while the launcher is still at condition temperature, an electrical ignition system check shall be performed in accordance with 3.3.7. The launcher shall then be allowed to return to ambient temperature and an Electrical Test shall be performed in accordance with 3.3.7.

4.5.4.4 Salt SPray - The launcher shall withstand, in the Shipping Configuration, a 5 percent salt spray period of fifty (50) hours in accordance with M1L-STD-810. At the end of the salt spray period, the electrical ignition system and grounding circuit continuity and resistance test shall be performed. (3.3.7.)

4.5.4.5 Watcrproofness - The sealed loaded launcher, in the Shipping Configuration, shall be submersed in water so that the uppermost surface of the launcher is beneath the waters surface not less than one inch nor more than two inches, for one hour or longer with the water at a temperature of not more than *40°F* below ambient temperature at which the unit was sealed. After submersion, the unit shall be dried and opened. The interior of the launcher shall be inspected for evidence of moisture. Any evidence of moisture and the area in which it is observed shall be recorded. The electrical ignition system check shall be performed in accordance with 3.3.7.

4.5.4.6 Vibration

4.5.4.6.1 Transportation Vibration - The launcher, in the Shipping Configuration, shall be loaded with inert 2.75″ Folding Fin Aircraft Rockets of correct weight and center of gravity. The launcher shall be subjected to the vibration tests of MIL-STD-810, Equipment Category g, Curve AB. The launcher shall withstand, without adverse effects, all loads induced or resulting from transportation vibration frequencies of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:12Z
Check the source to verify that this is the current version before use.

4.5.4.6.2 Captive Flight Vibration - Captive flight tests shall include sinusoidal and random vibration tests. The vibration environment shall be applied to the launcher through the normal launcher lug attachments and sway brace locations. The launcher shall be mounted on an Aero-7A Bomb Rack. Sway braces shall be torqued to 100 inch-pounds. The control for the vibration environment shall be from an accelerometer located on the strongback midway between the launcher lugs. The test unit is to be in its normal attitude during the test. The launcher shall be tested with a full load of inert rockets, with a hlaf load (or half load PLUS ONE when odd numbers of rockets are carried), and with no load. The test times shall be divided equally between the three conditions. The launcher shall withstand, without adverse effects, all loads induced or resulting from flight vibration frequencies without evidence of system failure or malfunction. The test details are as follows:

4.5.4.6.2.1 Sinusoidal - The launcher, in the Flight configuration, shall be tested in accordance with M1L-STD-81O, Method 514, Procedure I, Curve J and " Curve M (Parts 1, 2, and 3). Test times and sweep rates are defined in time Schedule 1, Time Table 514-11. The launcher's electrical circuits shall be checked (3.3.7) during each condition of resonance or complex motion. The loaded condition portion of the test shall be conducted using Inert 2.75 inch Folding Fin Aircraft Rockets having the same weight and center of gravity as loaded rockets.

4.5.4.6.2.2 Random Vibration with Loaded Launcher - The vibration test shall be conducted using inert 2.75 inch Folding Fin Aircraft Rockets having the same weight and center of gravity as loaded rockets. The launcher, in the Flight Configuration, shall be subjected to the vibration test of MIL-sTD-81O, Procedure II, Curve AE except the 0.02 G^2/Hz level shall be maintained over the frequency range of 10 to 2000 Hz. The electrical circuit shall be checked in accordance with 3.3.7 during and after the vibration test.

4.5.4.6.2.3 Random Vibration, Empty - The empty launcher, in the Flight Configuration, shall be subjected to the vibration test of MIL-STD-81O, Procedure II, Part 3, Curbe AH, except the 0.1 G^2/Hz level shall be extended over the frequency range of 10 to 2000 Hz. The electrical circuit shall be checked in accordance with 3.3.7 during and after the vibration test.

4.5.4.6.3 Vibration Release - There shall be no evidence of detent damage, or release of rockets from their detents when subjected to vibration in accordance with 4.5.4.6.

4.5.4.7 " Shock Test - The Launcher center section, Drawing Number 30003 356AS224, shall be loaded with inert 2.75" Fold Fin Aircraft Rockets of the correct weight and CG and shall be shock tested both forward and rearward to verify resistance to shock loads experienced during catapult take-off and arrested landing. The applied shock load shall be 13.5g in each longitudinal direction as measured on the bomb rack at a point midway between the hooks (Launcher attachment points). The duration of the applied shock load shall be 30 milliseconds **minimum to** one (1) **second maximum. The wave form shall** approach a half sine wave. The electrical system checks ***(3.3.7)*** shall be performed after ths shock test.

4*5.5 Detent Pull Test - Detent Pull Tests shall be performed on each tube of the launcher per 3.3.5.2.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:12Z
Check the source to verify that this is the current version before use.

4.5.6 **Static** Loading Tests - The launcher center section Drawing Number 30003 356AS224, shall be unloaded and suspended from a-pylon having 14 inch" suspension. Simultaneous application of a 3700 (+ or -10) pound load to the side (horizontal) and a 5660 (+ or -20) pound load downward shall be achieved in such a manner that the loads are equally divided among the seven launching tubes and are uniformly distributed over the length of each. The axes of the applied loads shall intersect on the centerline of the launcher package at a point midway between suspension hangers. The center section shall then be subjected to a force of 4430 (+ or -20) pounds acting from rear to front along the centerline of the launcher package. The load shall be evenly distributed over the face of aft bulkhead and the reaction to this load shall be evenly distributed-through both hanger lugs. Test samples shall withstand the specified loads without structural failure. Following thest tests, the launching tubes must be straight enough *to* permit easy loading and detenting of rockets. Refer to paragraph 4.5.2.1.

4.5.7 Ground Firing Test - The launcher, in the Flight Configuration, shall be mounted on a pylon with 14 inch suspension. A full complement of live rockets shall be successfully fired from the launcher with fairings installed. All rockets must ignite and leave the launching tubes in a normal manner. Widely separated rocket flight paths shall not be considered cause of rejection of the launcher package. The launcher package shall remain intact on the pylon and sustain no damage except darkening of the exposed surfaces.

4.6 Flight Tests - The launcher, in the Flight Configuration, loaded with nineteen 2.75 FFAR and fairings shall be installed on a bomb rack having 14 inch suspension and flown at high Q, maximum performance of the aircraft, to determine conformance with the requirements of 3.4 and demonstrate ability to withstand air loads imposed by high performance aircraft. Prior to the Flight Test, the launcher Shall be inspected to determine fit and compatibility with the aircraft. The fully loaded launcher shall then be flown and air fired. There shall be no damage to the aircraft from fairing disintegration or launcher debris which may require replacement of aircraft skin. The above tests apply to preproduction samples only.

5.0 . Preparation For Delivery

5.1 Preservation, Packaging, and Packing - Unless otherwise specified in the contract or order, preservation, packaging, and packing shall be in accordance with levels A, B, or C as defined herein, the applicable level to be specified in the contract or order (see 6.2).

5.1.1 **Levels A and B - If the contract** or order specified levels A or B, each launcher shall be preserved **and** packaged in accordance with method II of Specification MIL-P-116,

5.1.2 Level C - When level C is specified, each launcher shall be preserved and packaged in accordance with the manufacturer's commercial practice. It shall be the responsibility of the contractor to afford a level of protection adequate to prevent damage to the launcher during transit from the contractor's plant to the first destination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:12Z
Check the source to verify that this is the current version before use.

5.1.3 Packing

5.1.3.1 Level A - When level A is specified as the packing requirement> each launcher shall be packed in overseas containers conforming to Specification ' WR-54/174. These containers should be palletized in accordance with the general requirements of WR-54 (minimum of four containers in a palletized load).

5.1.3.2 Level B - When level B is specified as the packing requirement, each launcher shall be packed in domestic containers conforming to Specification issued by the Naval Weapons Handling Laboratory, Earle, New Jersey. These containers should be palletized in accordance with the general requirements of MIL-STD-l322 (mininimum of four containers in a palletized load).

5.1.3.3 Level C - When level C packing is specified, each launcher shall be packed in containers acceptable by the common carrier which will insure safe delivery at the lowest rate to the point of delivery. Containers shall comply with the carrier's rules and regulations applicable to the mode of transportation.

5.2 Marking - All marking for interior and exterior containers shall conform to MIL-STD-129 and shall include the following:

(a) Launcher, rocket LAU-61/A/A

(b) Name of supplier (and manufacturer if not the same)

(c) Date of preservation

(d) Specification number

(e) Contract number

(f) Lot number

(g) Weight

6.0 Notes

6.1 **Use -** The rocket launcher packages covered by this specification are intended for use as domestic and overseas shipping containers for 2.75 folding Fin Aircraft Rockets, Shipping Configuration, and for service launching of 2.75 Folding Fin Aircraft Rockets, Flight Configuration.

6.2 Adherence to Drawings and Specifications - Insofar as the contractor is required by provisions of this specification to comply with the drawings listed in Section 2, should compliance with these drawings conflict with the performance and test requirements specified herein, the contractor should promptly notify "procuring activity" of such fact and appropriate changes will be made in the applicable drawings, parts or performance requirements as authorized by the "procuring activity".

6.3 Availability of Dummy Stores for Testing - The contractor shall submit requests to the Air Systems Command for dummy and inert stores to be used for testing as required by this specification.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T06:12Z
Check the source to verify that this is the current version before use.

6.4 Ordering Data - Procurement documents should specify the following:

(1) Title, number and date of this specification.

(2) Selection of applicable levels of preservation, packaging and packing.

(3) Where the preproduction test samples and acceptance test samples should be sent, the activity responsible for testing, and instructions concerning the submittal of the test reports.

(4) Production sampling lot size.

Project No. 1055-NO37

*U. S. Government pRINTING 0FFIcE -433-692/2519

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:12Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the ification in procurement of products for ultimate use by the Department of Defense. This sheet is provt$e~b~o%f taining information On the use of this Specification which will insure that suitab e prod cts can be procured with minimum amount *Of* delay ● nd ● at the least cost. Comments and the return of this form wil l be ● apreciated. Fold onm lines. on reverse side, staple in corner, and send to preparing activity (●. indicated on reverse hcrcof).

SPECIFICATION

MIL-L-81795(AS) LAUNCHER, ROCKET, AIRBORNE, LAU 61 A/A

ORGAN I ZATI ION (Of Submittcr)

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

❑ DIRECT GPVERM,EMT CONTRACT SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REWIRED INTERPRETATION IN PROCUREMENT USE?

A, GIVE PARAGRAPH NUMBER AND WORDING,

S. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

COMMENTS ON ANY SPECIFICATION RETIREMENT CONSIDERED TOO RIGID

IS THE SPECIFICATION RESTRICTIVE?

YES O NO If 'YES", IN WHAT WAY?

REMARKS *(Attech any* pertinent data wh *ich may be of uae in impcoving* th is specification, If *there arc addi-* "tional papers, attac h to *form and place both* in an ● nvelope *addreaaed to preparing* activity)

SUBMITTED) BY *(Printed or typed name and* acttvtty) | DATE

DD, FORM 1426
APR 62

C-8370

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T06:12Z
Check the source to verify that this is the current version before use.