INCH-POUND

MIL-T-52958B(ME)
AMENDMENT 1
11 January 1989

MILITARY SPECIFICATION

TRUCK, FIRE, MINI-PUMPER,

COMMERCIAL CHASSIS

This amendment forms a part of MIL-T-52958B(ME), dated 31 August 1984, and is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 6

3.4.2, line 2, delete "13,000 pounds" and substitute "15,000 pounds".

PAGE 7

3.4.5.4, lines 2 thru 6, delete "In addition, an auxiliary.....provided with an independent shutoff valve."

PAGE 8

3.4.6.2, lines 1, 2, and 3, delete the first two sentences and substitute "A dual 12 V battery system shall be provided. Each battery shall have a cold crank rating of at least 540 amps and a reserve capacity of at least 115 minutes or of such size to be compatible with the electrical system of the truck chassis to be furnished."

PAGE 12

3.4.13, delete the last sentence in its entirety.

PAGE 15

3.10.3, lines 15 and 16, delete the 8th sentence in its entirety and substitute "Valves shall be operated and locked by individual controls and shall be of the single-handed operation, twist to lock type (Akron style 1488 or equal)."

AMSC N/A FSC 4210

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:42Z
Check the source to verify that this is the current version before use.

PAGE 17

3.11.2, line 6, delete "well-seasoned, selected hardwood" and substitute "space age plastic material to allow drainage and air circulation".

PAGE 18

3.11.3, line 9, delete "well-seasoned hardwood" and substitute "space age plastic material".

3.11.5, after a.2, add the following new subparagraph:

"3. One chest type compartment shall be provided and mounted to the top of the two curbside compartments. The compartment shall have a lift-up cover with full length stainless steel piano hinge and corrosion resistant cam-type latches. The cover shall not less than a two-inch vertical overlap lip with gasket to assure prevention of water from entering the chest compartment. The compartment and cover shall be fabricated from anti-skid polished aluminum. The size of the compartment shall be such as to have the capacity to stow not less than the total of: six fire rakes, six McLead Forestry tools, one gasoline powered chain saw with an 18-inch cutter bar, and one 3-gallon safety-type fuel can (the tools are not to be furnished as part of the truck)."

PAGE 19

3.11.7, line 3, delete "700 pounds" and substitute "800 pounds".

Line 7, delete "350 lbs" and substitute "500 lbs".

Line 8, delete the 7th sentence in its entirety and substitute "The rear platform and running boards shall be of polished aluminum with a 4-way anti-skid surface."

PAGE 21

3.14, item c, delete "Ammeter" and substitute "Voltmeter".

PAGE 22

3.18, line 5, delete the 2nd sentence in its entirety and substitute "The tread plates not fabricated from polished aluminum shall be painted gloss aluminum."

PAGE 23

3.21.a, line 5, add at the end of the paragraph "The hose shall be stored in the hose troughs."

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:42Z
Check the source to verify that this is the current version before use.

3.21.b, line 1, delete the first sentence and substitute "A hose trough shall be provided on each side of the truck and mounted above the compartments."

Line 7, delete the last sentence in its entirety.

3.21.c, line 1, delete the first sentence and substitute "One 12 foot, two-section, aluminum fire ladder."

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 4210-A228

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.