MIL-C-50600A(MU)
22 February 1977
SUPERSEDING
MIL-C-50600(MU)
24 November 1970

MILITARY SPECIFICATION

CARTRIDGE, 20MM: TARGET PRACTICE-TRACER, M206A1

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of percussion primed cartridge for use in Guns, 20mm, Automatic. (see 6.1)

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition, General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-644 - Visual Inspection Standards and Inspection Procedures for Inspection of Packaging, Packing, and Marking of Small Arms Ammunition
MIL-STD-651 - Visual Inspection Standards for 20mm Ammunition and Components
MIL-STD-1168 - Ammunition Lot Numbering
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC 1305

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Frankford Arsenal, ATTN: SARFA-MDM, Philadelphia, Pennsylvania 19137 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

2.1 (Cont)

DRAWINGS

ARMAMENT COMMAND

C10542736	- Classification of Firing Casualties for Case, Cartridge, 20mm, M204
F11731517	- Packing and Marking 62 Cartridges, 20mm, Bulk, Shipping and Storage Container, Cartridge, 20mm, M528, Box, Wirebound
F11731518	- Packing 31 Cartridges, 20mm, Bulk, Shipping and Storage Container, Cartridge, 20mm, M528
F11731519	- Marking 31 Cartridges, 20mm, Bulk, Shipping and Storage Container, Cartridge, 20mm, M528
F11731520	- Packing and Marking 50 Cartridges, 20mm, Linked, Shipping and Storage Container, Cartridge, 20mm, M528, Box, Wirebound
F11731521	- Packing 25 Cartridges, 20mm, Linked, Shipping and Storage Container, Cartridge, 20mm, M528
F11731522	- Marking 25 Cartridges, 20mm, Linked, Shipping and Storage Container, Cartridge, 20mm, M528
F11731523	- Packing and Marking 50 Cartridges, 20mm, Linked, Shipping and Storage Container, Cartridge, 20mm, M528, Box, Wirebound (Functional)
F11731524	- Marking 25 Cartridges, 20mm, Linked, Shipping and Storage Container, Cartridge, 20mm, M528 (Functional)
D10542656	- Projectile, Target Practice-Tracer, 20mm, M212A1
D10542655	- Cartridges, 20mm, Target Practice-Tracer, M206A1
LI 10542655	- Index of Inspection Equipment Lists for: Cartridge, 20mm, Target Practice-Tracer, M206A1

PUBLICATIONS

U.S. ARMY MATERIEL COMMAND

AMCR 715-505	- Ammunition Ballistic Acceptance Test Methods, Volume 8, Test Procedures for 20mm Cartridges

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General. The cartridge shall be in accordance with Drawing (Dwg.) D10542655, referenced specifications, and other requirements specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

3.2 Manufacturing process. All parts and assemblies shall be manufactured by a process approved by the contracting officer, and no deviations from that process shall be made without his prior approval. (see 6.3)

3.3 First article sample. Unless otherwise directed by the contracting officer, a first article sample shall be required.

3.4 Projectile extraction. The force necessary to extract the projectile from the cartridge case shall be as specified by Dwg. D10542655.

3.5 Velocity. The average velocity of the sample cartridges conditioned at 68 degrees Fahrenheit (^{o}F) to 72°F shall be 3430 $\pm$ 50 feet per second (fps) at 78 feet from the gun muzzle and the sample standard deviation shall not exceed 40 fps.

3.6 Pressure. The average chamber pressure of the sample cartridges shall be not greater than 49,500 pounds per square inch (psi) nor any individual pressure shall be greater than 54,000 psi maximum, conditioned at 68°F to 72°F.

3.7 Waterproofness. The average velocity (wet) of projectiles of the sample cartridges conditioned at 68°F to 72°F shall not vary from the average velocity (dry) by more than 100 feet per second.

3.8 Accuracy. The average mean radius of all targets of the sample cartridge projectiles shall not exceed 15 inches at a range of 600 yards.

3.9 Action time. The action time of the sample cartridges at ambient temperature shall not exceed 6.0 milliseconds.

3.10 Projectile trace. The sample projectile shall exhibit a visible trace, when viewed against a dark background, upon ignition of the trace mixture and continue to trace for a minimum of 3.4 seconds after cartridge ignition.

3.11 Function and casualty. The cartridge, at ambient temperature, shall function without casualty.

3.12 Workmanship. The requirements for workmanship are as specified on the applicable drawings, referenced specifications, and the following:

3.12.1 Process defects. The cartridge shall be free of defects such as folds, wrinkles, buckles, severe scratches, cracks, splits, cuts, dents, perforations, and other forms of substandard workmanship.

3.12.2 Cleanliness. The cartridge and its components shall be free of all foreign matter. (see 6.6)

4. QUALITY ASSURANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions. Reference shall be made to MIL-STD-109 for definition of quality assurance terms.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3).
2. Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 First article sample. The sample shall consist of 400 cartridges and shall be delivered for inspection in accordance with the first article approval provisions of the contract and MIL-A-2550. The sample cartridges shall be identified in accordance with the drawing and MIL-STD-1168.

4.3.1.1 Inspection. The first article sample will be subjected to the Quality conformance inspection provisions as stated herein, except that approval will be based upon the examination of the complete sample for visual and dimensional characteristics and the initial test sample in accordance with Table I. (see 6.4)

4.4 Quality conformance inspection.

4.4.1 Submission of product. The product shall be submitted in accordance with MIL-STD-105 or MIL-STD-1235, as applicable.

4.4.1.1 Lot. A lot shall consist of:

a. Cartridges loaded by one manufacturer, in one unchanged process, in accordance with the same drawings and drawing revisions, and the same specification and specification revisions.

b. Like parts and assemblies (cases; primers; projectiles) having one manufacturer's symbol and one interfix number.

c. Propellant from one lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

4.4.1.2 Lot identification. Each cartridge and each packed ammunition lot shall be identified in accordance with applicable drawings and MIL-STD-1168, supplemented as directed by the procuring activity. Each packed lot shall be further identified by a national stock number assigned by the procuring activity.

4.4.2 Examination. One hundred percent examination shall be performed by the contractor for all critical defects. Examination for major and minor defects shall be performed as specified herein. Any cartridge found to be defective shall be rejected.

4.4.2.1 Sampling and acceptance criteria. The sampling plans and procedures shall be in accordance with MIL-STD-105 or MIL-STD-1235. To determine product acceptability, major or minor defects as listed herein may be considered collectively on a class basis or they may be considered individually. However, where major defects are considered collectively on a class basis, the acceptance number for any individual defect of the class shall be limited by the assigned Acceptable Quality Level (AQL) for individual defect associated with the class. (see 4.4.2.1.1.c) In addition, where MIL-STD-1235 is used, sampling plans applicable to a class shall not be used for major defects. (see 6.5)

4.4.2.1.1 AQL's. The following AQL's are assigned to major and minor defects:

a. Individual:

Major	0.25%
Minor	0.40%

b. Class basis:

Major	1.50%
Minor	2.50%

c. Individual defects associated with the class basis:

Major	0.40%

4.4.3 Classification of defects 1/. The classification of defects shall be as follows:

4.4.3.1 Projectile (see Dwg. D10542656, a detail of Dwg. D10542655).

Categories and Defects	Method of Inspection	
Critical: None defined.		
Major:		
101. Missing or improper metering disc	Visual	
102. Loose metering disc	Manual	2/
103. Seal missing or perforated	Visual	
104. Foreign matter	Visual	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

4.4.3.1 (Cont)

Minor: None defined.

4.4.3.2 Cartridge (see Dwg. D10542655) 1/

Categories and Defects	Method of Inspection
Critical:	
1. Split or perforated case	Visual
2. Crack or split in projectile	Visual
Major:	
101. Cocked, loose, missing or inverted primer	Manual/Visual
102. Depth of primer seating	Gage
103. Overall length, max.	Gage
104. Missing or incomplete crimp (case-projectile)	Visual
105. Profile and alignment, max.	Gage 3/
106. Corrosion	Visual
107. Head configuration	Visual
Minor:	
201. Marking incorrect, incomplete, illegible or missing	Visual
202. Projectile protective coating damaged or incomplete	Visual
203. Waterproofing missing around primer	Visual
204. Scratch, dent, buckle, bulge, wrinkle or fold in case	Visual
205. Rotating band damaged	Visual
206. Primer crimp missing	Visual
207. Foreign matter, except corrosion	Visual
208. Incorrect type cartridge or components	Visual
209. Case protective coating damaged or incomplete	Visual
210. Upset (crooked) or deformed nose	Visual

1/ MIL-STD-651 shall apply in defining and evaluating cartridge visual defects.

2/ The projectile shall be classed defective if the metering disc can be moved laterally in its seat.

3/ A dead weight load of 60 pounds maximum may be used to insert the cartridge into the gage.

4.4.4. Tests. The tests listed in Table I shall be performed on each cartridge lot in accordance with the test methods prescribed in 4.5. Sample size and acceptance criteria for each test shall be as specified. Only cartridges having met the visual and dimensional requirements and having been selected in such a manner that the sample is representative of the entire lot shall be used in the tests. The selected cartridges shall be thoroughly mixed before being divided into samples for the various tests. The combining of tests is permitted. (see 6.8)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

4.4.4 (Cont)

TABLE I

Test 1/		Sample Size Production Lot	Requirement Paragraph
Projectile extraction	2/	20	3.4
Propellant contamination	3/	20	3.12.2
Velocity	4/	20	3.5
Pressure	5/	20	3.6
Waterproofness	6/	20	3.7
Accuracy	7/	40	3.8
Action time	8/	20	3.9
Projectile trace	9/	50	3.10
Function and casualty	10/	200	3.11

1/ The lot shall be rejected if in any firing test, one or more of the following malfunctions or casualties or Table II occur:

a. Projectile remaining in bore.

b. Metal parts separation, except rotating band separation (see Note 4/ of Table II).

Except as otherwise specified and in the function and casualty test where the occurrence of a firing defect listed in Table II prevents the obtaining of a reliable result for the characteristic being tested, an additional sample cartridge shall be fired.

2/ Projectile extraction

a. Failure of two or more sample cartridges to comply with the minimum requirement shall cause rejection of the lot. If one cartridge of the sample fails to comply with the minimum requirement, a second sample of 20 cartridges shall be tested. The lot shall be rejected if two or more cartridges of the combined samples fail to comply with the minimum requirement.

b. Failure of four or more cartridges to comply with the maximum requirement shall cause rejection of the lot. If more than one but less than four cartridges fail to comply with the maximum requirement, a second sample of 20 cartridges shall be tested. The lot shall be rejected if five or more cartridges of the combined samples fail to comply with the maximum requirement.

3/ Propellant contamination. The presence of foreign matter in the propellant of any of the test cartridges will cause rejection of the lot (see 3.12.2 and 6.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

4.4.4 (Cont)

4/ Velocity. If the sample fails to comply with either or both requirements, a retest sample of 40 cartridges shall be tested for the failing parameter(s) (average, sample standard deviation). The lot shall be rejected if the second sample fails to comply with the applicable requirements. (see 6.7.1)

5/ Pressure. If the sample fails to comply with the average pressure or if any individual pressure fails requirements, a retest sample of 40 cartridges shall be tested for failing requirements. The lot shall be rejected if the retest sample fails to comply with the applicable requirements.

6/ Waterproofness. If the average velocity (wet) of the sample fails to comply with the applicable requirement, a retest sample of 40 cartridges shall be tested. The lot shall be rejected if the average velocity (wet) differs by more than 100 fps from the average velocity (dry) of 40 additional sample cartridges fired to establish a new base for comparison. The lot shall not be penalized for failure of the last named sample cartridges to comply with the requirement of 3.7.

7/ Accuracy. If the average mean radius of the sample cartridge exceeds the applicable requirement, a retest sample of 80 cartridges shall be tested. The lot shall be rejected if the average mean radius of eight retest accuracy targets exceeds applicable requirements.

8/ Action time. If any sample cartridge fails to meet the requirements for action time, the lot shall be rejected.

9/ Projectile trace. Failure of 9 or more sample cartridges to comply with applicable requirements shall cause rejection of the lot. If more than 5 but less than 9 fail to comply, a second sample of 50 cartridges shall be tested. The lot shall be rejected if 13 or more cartridges of the combined sample fails to comply with the minimum requirement.

10/ Function and casualty. The lot shall be rejected if any malfunction or firing casualty of Table II occurs in number(s) equal to or greater than the applicable "Rej" number. Except as otherwise provided, if malfunctions or casualties occur in excess of the applicable "Acc" number, but less than the applicable "Rej" number, a second sample of 400 cartridges shall be selected. The lot shall be rejected if in the combined samples, malfunctions or casualties occur in numbers equal to or greater than the applicable "Rej" number.

4.4.4.1 Firing defects. Firing defects and associated criteria shall be as specified in Table II. For defect definitions, see AMCR 715-505, Volume 8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

4.4.4.1 (Cont)

TABLE II

Firing Defects	Acc	Rej
Cartridge:		
Misfire	0	2
Failure to chamber	0	1
Failure to extract	0	1
Projectile remaining in bore	0	1
Primer:		
Primer leak	9	25
Primer perforation	1	6
Loose primer	0	1
Blown primer	0	1
Case:		
Longitudinal split 1/		
I or S	10	31
J	4	11
K	0	2
L or M	0	1
Circumferential rupture, partial 1/		
S, J or K	4	11
L	0	1
Circumferential rupture, complete 1/	0	1
Detached metal 2/	0	1
Projectile:		
Rotating band separation 3/		
Complete or partial separation having band seat serration imprint	0	3
Separation having length greater than 0.5 inch, and without band seat serration imprint	1	6
Metal parts separation, except rotating band separation 4/	0	1

1/ See Dwg. C10542736 for classifying splits and ruptures in fired cartridge cases. If a longitudinal split or circumferential rupture (partial) extends into two or more defined areas, only the most severe defect criterion of Table II for the areas involved shall apply. If a rupture results in separation of the cartridge case into two or more portions, the defect shall be classified as a complete circumferential rupture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

4.4.4.1 (Cont)

2/ Metal sheared or missing from the fired cartridge case exterior, such as rim or neck shears, shall be classed as a defect. The lot shall not be penalized for shavings of metal from the interior wall of the case neck, in the crimped area.

3/ For classification as a defect, there must be evidence either by recovery of the band or portion thereof, or by hole(s) in the fragmentation screen(s). The lot shall not be penalized for normal band fringing, or the separation of band fragments having no evidence of band seat serration imprint and having length of 0.5 inch or less.

4/ Separation or breakup of projectile part(s), except rotating band separation, as evidenced by recovery of the part(s) or fragment(s), or hole(s) in the fragmentation screen(s), shall be classed as a defect.

4.4.4.2 Unlisted firing defects. The lot shall be suspended and referred to the contracting officer for disposition, if a malfunction or casualty not covered by this specification occurring in any firing test, indicates that the product is unsuited for the purpose intended.

4.4.5 Packaging, packing and marking inspection. Inspection for packaging, packing and marking shall be in accordance with MIL-STD-644, as applicable.

4.4.6 Inspection equipment. Index of Inspection Equipment List (LI) 10542655 identifies the applicable inspection equipment required to perform examination and tests prescribed herein. Equipment design(s) shall be in accordance with the applicable code designations. The code designations are defined on Dwg. B11075228, a detail of LI 10542655. The provisions of MIL-A-2550 shall apply.

4.5 Test methods and procedures.

4.5.1 Projectile extraction. The method of test shall be as prescribed in AMCR 715-505, Volume 8.

4.5.2 Propellant contamination. The propellant from each of the cartridges tested for projectile extraction shall be examined visually for contamination, as prescribed in AMCR 715-505, Volume 8.

4.5.3 Velocity, pressure and waterproofness. The methods of test shall be as prescribed in AMCR 715-505, Volume 8. Statistics necessary for testing of results against acceptance criteria shall be computed (see 6.7).

4.5.4 Accuracy. The method of test and measurement of targets shall be as prescribed in AMCR 715-505, Volume 8. The specified range may be shortened in decrements of 100 yards, to a minimum range of 200 yards. For ranges less than 600 yards, the average mean radius shall be reduced in direct proportion to the reduction in range.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

4.5.5 Action time. The method of test shall be as prescribed in AMCR 715-505, Volume 8.

4.5.6 Projectile trace. The method of test shall be as specified in AMCR 715-505, Volume 8, except that observation shall be from near the gun position and projectile trace time will begin at cartridge ignition and continue until the end of the tracer mixture burn.

4.5.7 Function and casualty. The method of test shall be as prescribed in AMCR 715-505, Volume 8. The test sample shall be fired in bursts of 25 cartridges. The weapon barrel shall be at ambient temperature at beginning of test and cooled to ambient after each two bursts. The cyclic rate of each burst shall not be less than 650 nor greater than 1000 shots per minute (SPM) in the M139 gun. The cyclic rate for each burst shall be recorded.

4.5.8 Defective weapon. If any test cartridge firing defect is found to have been caused by a defective test weapon, the firing defect shall not be valid for lot penalty. In such case, the defective test weapon shall be corrected or replaced and the test repeated in whole or in part, as indicated. If such firing defect is not found to have been caused by a defective weapon, it shall be valid for lot penalty.

5. PREPARATION FOR DELIVERY

5.1 Packing, Level A. The type of ammunition pack shall be in accordance with instructions from the procuring activity. Linked ammunition shall be packed in accordance with Dwgs. F11731520, F11731521 and F11731523. Bulk ammunition shall be packed in accordance with Dwgs. F11731517 and F11731518.

5.2 Marking. Marking on the packed container shall be in accordance with Dwgs. F11731519, F11731522 and F11731524, as applicable.

6. NOTES

6.1 Intended use. These cartridges are intended for use in various automatic gun systems that have been designed for firing cartridges with the M204 type case configuration.

6.2 Ordering data. Procurement documents should specify the following:

6.2.1 Title, number and date of this specification.

6.2.2 Place of inspection, if not at place of manufacture.

6.2.3 First article sample requirements. (see 3.3, 4.3 and 6.4)

6.2.4 Detailed packing and marking instructions. (see 5.1 and 5.2)

6.2.5 Provision for the submission and approval of the manufacturing process.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

6.2.6 Provision for the supply, maintenance and disposition of Government furnished test equipment for acceptance inspection purposes.

6.2.7 Provision for the shipment of first article and production lot samples.

6.2.8 Provisions for the inclusion of MIL-STD-1167, Ammunition Data Cards on DD form 1423, Contract Data Requirements List.

6.3 Process deviation. A process deviation is defined as a change in the approved basic method of manufacture, or an operational change which may alter the metallurgical or physical properties of the item.

6.4 First article sample. In order to minimize inspection costs, the firing test 4.3 will be performed after the sample has been provisionally accepted by the Government for all other requirements. Additional cartridges may be required by the test facility.

6.5 AQL's. The optional use of AQL values for either individual defects or classes of defects, with individual major defect limitation, is intended to minimize inspection agency administrative burden which might result from an exclusive assignment of individual defect AQL's. The option also permits flexibility where sampling inspection for acceptance is integrated into a manufacturing process.

6.6 Contamination of explosive components. Particular care should be exercised to avoid contamination of primers and propellant by oil, grease or other foreign matter since such contamination can cause misfire(s) or increase hangfire time to make the ammunition unsuitable for use.

6.7 Computations.

6.7.1 Standard deviation. Where computation of a sample standard deviation is specified for determination of lot acceptance, the method of computation will be:

$$S = \sqrt{\frac{\sum (X_i - \bar{X})^2}{n}}$$ or equivalent

6.8 Combining tests. With approval of the procuring activity, tests may be performed concurrently on the same sample cartridges provided that the test results are not affected by this procedure. The test facility should make maximum use of this procedure to minimize testing costs.

NOTE: Asterisks not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1305-A803

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-C-50600A(MU) Cartridge, 20MM: Target Practice-Tracer, M206A1

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Frankford Arsenal
ATTN: SARFA-MDM
Phila., PA 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.