MILITARY SPECIFICATION

CONTAINER AND CUSHION ASSEMBLY, AMMUNITION, METAL, FOR CARTRIDGE, 120MM, TANK AMMUNITION

This Specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements, quality assurance provisions and packaging for one type of metal container and cushion assembly used for 120MM tank ammunition.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-P-116	-	Preservation, Methods of.
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification for.

Beneficial comments (recommendations additions deletions) and any pertinent data which may be of use in improving this document should be addressed to Commander U S Army Armament Research Development and Engineering Center Attn AMSMC-QA Dover New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter

AMSC N/A FSC 8140
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1169	-	Packaging, Packing, and Marking for Shipment of Inert Ammunition Components.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS (see 6.4)

US ARMY ARMAMENT RESEARCH, DEVELOPMENT and ENGINEERING CENTER (ARDEC)

9386831	- Container, Ammunition, Metal.
9386832	- Container and Cushion Assembly, Cartridge, 120MM, APFSDS-T, M829.
9386833	- Container and Cushion Assembly, Cartridge, 120MM, HEAT-MP-T, M830.

(Copies of specifications, standards and other Government documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity).

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the non-government documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-D-3951	-	Commercial Packaging Standard Practice for.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this specification and the reference cited herein, (except for associated detial specifications, specification sheets, or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on drawings 9386832 or 9386833 and the drawings and specification referenced thereon.

3.3 Cover assembly. Upon assembly of the cover assembly to the body assembly (body weldment), the cover assembly shall freely engage and rotate within the body assembly. As the cover assembly is rotated with the "Y" handle in the open position, the "Y" handle shaft ends shall freely engage into the respective bayonet slots of the rim. When the "Y" handle is in the closed position (rotated 180°), the spring clip shall engage and lock the handle in place. When the spring clip is disengaged and the handle rotated to the open position, the cover assembly shall disengage from the body assembly.

3.4 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.5 Workmanship.

3.5.1 General. The components and assemblies shall be free from cracks, burrs, chips, dirt, grease, rust, or other foreign material. Any cleaning method used shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents. The components or assemblies shall not be damaged in any manner during the assembly operation.

3.5.2 Protective finish. The protective finish or marking shall be restored by the assembling contractor for any components furnished to him prefinished and marked, when such finish or markings have been marred or obliterated.

4. QUALITY ASSURANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First article inspection.

b. Quality Conformance Inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of ten (10) container assemblies and ten (10) each of every subassembly and component.

4.3.2 Inspections to be performed. See MIL-A-48078.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70472 (AR)

PARAGRAPH	TITLE: Assemblies and Components		SHEET 1 OF 1		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Container, Metal - (Drawing 9386831) Examination for Defects	10		3.2	4.4.2.1
	Container and Cushion Assembly - (Drawing 9386832 or 9386833) Examination for Defects	10		3.2	4.4.2.2

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of containers shall contain material from lots with the same interfix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70472 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Metal Container				9386831
					NEXT HIGHER ASSEMBLY
					12630717 or 12630718
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Missing, loose or damaged components		1.0%	3.2/ 3.5.1	Visual
102	Cover assembly test		1.0%	3.3	Visual/Manual/4.5.1
103	Examination of gasket for defects		1.0%	3.2	Visual
Minor					
201	Poor workmanship		1.0%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70472 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Container and Cushion Assembly		9386832 or 9386833
			NEXT HIGHER ASSEMBLY: 12630717 or 12630718

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Missing, loose or damaged internal cushion components		1.0%	3.2	Visual/Manual
102	Missing, loose or damaged metal container components		1.0%	3.2	Visual/Manual
103	Base cushion not aligned properly to cover assembly after adhering		1.0%	3.2	Gage
Minor					
201	Container paint scratched or chipped		1.0%	3.5.2	Visual
202	Components improperly adhered		1.0%	3.2	Visual/Manual
203	Poor workmanship		1.0%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.5 herein.

4.5 Methods of inspection. (See 6.5)

4.5.1 Cover assembly test. Upon assembly of the body and cover, the cover shall freely engage and rotate within the body. The Y-handle shall engage into the respective bayonet slots of the rim without interference when in the clamping position. The Y-handle when disengaged and in the open position shall disengage the cover from the body.

5. PACKAGING

5.1 Cleaning. The container assemblies shall be cleaned in accordance with C-1 of MIL-P-116, if required.

5.2 Drying. The container assemblies shall be dried in accordance with MIL-P-116, if required.

5.3 Preservation. Not applicable.

5.4 Unit and intermediate packaging.

5.4.1 Level A. The container assemblies shall be unit and intermediate packaged in accordance with Level A of MIL-STD-1169.

5.4.2 Level B. The container assemblies shall be unit and intermediate packaged in accordance with Level B of MIL-STD-1169.

5.4.3 Commercial. The container assemblies shall be packaged in accordance with ASTM-D-3951.

5.5 Packing.

5.5.1 Level A. The container assemblies shall be packed in accordance with Level A of MIL-STD-1169.

5.5.2 Level B. The container assemblies shall be packed in accordance with Level B of MIL-STD-1169.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

5.5.3 Commercial. The container assemblies shall be packed in accordance with ASTM-D-3951.

5.6 Marking.

5.6.1 Level A. The container assemblies shall be marked in accordance with Level A of MIL-STD-1169.

5.6.2 Level B. The container assemblies shall be marked in accordance with Level B of MIL-STD-1169.

5.6.3 Commercial. The container assemblies shall be marked in accordance with ASTM-D-3951 and the following additional instructions. Commercial shipping tags attached with wire shall be used unless otherwise specified. The following information shall be shown: Item name and model number, part number and revision, contract number, lot number and date, name and address of manufacturer. If containers are bundled, boxed or palletized, the gross weight and quantity shall be included. The above information may be placed on pallets or boxes by labeling or stenciling.

5.7 Shipping. When container assemblies from more than one lot are shipped at one time, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing lots in transit.

6. NOTES

6.1 Intended use. This container assembly is intended for use as the tactical packaging for the M829 APFSDS-T, 120MM Tank Cartridge and M830 HEAT-MP-T, 120MM Tank Cartridge.

6.2 Ordering data. See MIL-A-48078.

6.3 Definition of packaging and packing levels.

6.3.1 Level A. Full Military protection, for unrestricted (OCONUS) shipment and storage

6.3.2 Level B. Limited Military protection for limited storage and (OCONUS) shipment.

6.3.3 Level C. For interplant (CONUS) shipment and very limited storage.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as US Army Armament Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

6.5 Submission of inspection equipment for design approvals. See MIL-A-48078. Submit designs as required to: Commander, US Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-I(D), Dover, New Jersey 07801-5001.

6.6 Approval of equivalent test methods. Prior approval of the Contracting Officer is required for use of equivalent test methods. A description of the proposed method should be submitted through the Contracting Officer to: Commander, US Army Armament Research Development and Engineering Center, ATTN: AMSMC-QAT-I(D), Dover, New Jersey 07801-5001. This description should include but not be limited to the accuracy and precision and drawings of any special equipment required.

6.7 Subject term (key word) listings

Ammunition
Cannon
Cartridge
Container
Cushion assembly
Metal
Tank

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140-A637)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS F CUT ALONG THIS LINE)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1 DOCUMENT NUMBER	2 DOCUMENT TITLE
MIL-C-70472	CONTAINER AND CUSHION ASSEMBLY, AMMUNITION , METAL, FOR CARTRIDGE,

3a. NAME OF SUBMITTING ORGANIZATION 120MM, TANK AMMUNITION	4 TYPE OF ORGANIZATION *(Mark one)*
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)* _____

5 PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c. Reason/Rationale for Recommendation

6 REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT MUNITION & CHEMICAL COMMAND
ATTN: AMSMC-QA
DOVER, NJ 07801 5001

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.