MIL-C-60944A(AR)
15 SEPTEMBER 1980
SUPERSEDING
MIL-C-60944 (MU)
11 January 1968

MILITARY SPECIFICATION
CARTRIDGE, 40MM, PRACTICE, M385
LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the U.S. Army Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of cartridge designated as cartridge, 40MM, practice, M385.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116		Preservation, Method of
MIL-A-48078	-	Ammunition, Standard Quality Assurance, Provisions, General Specification For
MIL-P-60942	-	Primer, Percussion for 40MM

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-331	-	Fuze and Fuze Components, Environmental and Performance Test for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

DRAWINGS (See 6.9)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

PRODUCT AND PACKING DRAWINGS

8886326	Cartridge, 40MM, Practice, M385
9251995	Box, Wirebound, Packing, Ammunition for Cartridge, 40MM, Linked
9251996	Box, Fiber, Packing Ammunition for Cartridge, 40MM, Linked

INSPECTION EQUIPMENT DRAWINGS

9202253	Chamber Gage
9202255	Alignment Check
9202254	Limit Checks

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

CODE OF FEDERAL REGULATIONS

TITLE 49	Transportation, Parts 100-199

(The Code of Federal Regulations is available from the Superintendent of Documents, US Government Printing Office, Washingtio, D.C. 20402. Orders should specify "49 CFR 100-199 (latest revision)").

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Cartridge. The cartridge shall comply with all requirements specified on Drawing (Dwg. 88863261 all associated drawings, and with all requirements specified in applicable specifications.

3.3 Air pressure. The cartridge shall withstand an air pressure of three (3) pounds-per-square-inch (p.s.i.) for five (5) seconds minimum (min.) without a drop in pressure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

3.4 Functioning. The projectile shall have a mean velocity of 795 ± 20 feet-per-second (f.p.s.) and a standard deviation not exceeding 15.0 f.p.s. The action time of the cartridge when tested shall be 4.0 milliseconds, maximum.

3.5 Workmanship. All parts and assemblies shall be fabricated, loaded and assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust, and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following type of inspection shall be conducted on this item:

a. Quality Conformance Inspection

4.3 First article inspection. Not applicable.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with lot formation provisions of MIL-A-48078. Each inspection lot shall contain:

a. Cartridge case assembly metal parts from one interfix lot number from one manufacturer.

b. Primers from one lot number from one manufacturer.

c. Propellant from not more than one lot number from one manufacturer.

d. Metal parts from one interfix lot number from one manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

e. Cartridges in less than full belt quantities from any acceptable lot of cartridges shall be held until a cumulative amount of 3000 cartridges are obtained or until 1 year has elapsed. These cartridges shall be linked, packed and shipped in multiples of 50 as a conglomerate lot. No further ballistic firing need be performed on these cartridges since these cartridges came from acceptable lots. Acceptable lots are lots not accepted on waiver. If at the end of 1 year, 3000 cartridges are not obtained, the cumulative amount of cartridges shall be linked, packed and shipped in multiples of 50 and the remaining cartridges shall be destroyed. Inspection lots shall comply with MIL-STD-105 and shall be numbered in accordance with MIL-STD-1168. Unless otherwise approved by the contracting officer, the inspection lot size of major assemblies or end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period nor more than the largest quantity contractually schedules for delivery during any month of the contract period. Inspection lots for components or sub-assemblies, other than the items of delivery, shall be homogeneous and of size convenient to the contractor.

Data cards shall be annotated to show that this is a conglomerate lot and from what lots the cartridges were obtained.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Tests Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-60944A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Cartridge Case Assembly Prior to Loading				8886327
					NEXT HIGHER ASSEMBLY 8886326
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Closing cup missing		100%	3.2	Visual
MINOR:	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:07Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-60944 A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Cartridge Case Assembly Prior to Assembling Base Plug and Primer				8886327
					NEXT HIGHER ASSEMBLY 8886326
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL					
1.	Spilled powder from cartridge case		100%	3.2	Visual
2.	Propellant charge weight obviously incorrect (See 6.11)		100%	3.2	Visual
MAJOR					
101.	Propellant charge weight obviously incorrect (See 6.11)		100%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:07Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-60944A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8886327
4.4.2.3	Cartridge Case Assembly				NEXT HIGHER ASSEMBLY 8886327
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL					
1.	Primer above flush with base plug		100%	3.2	Gage
MAJOR					
101.	Base plug above flush		0.40%	3.2	Gage
102.	Depth of base plug, max		0.40%	3.2	Gage
103.	Depth to primer, max., from base plug		0.40%	3.2	Gage
104.	Excessive sealing compound on exterior surfacr of primer		0.40%	3.2	Visual
MINOR					
201.	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:07Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-60944A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Projectile prior to crimping cartridge case assembly				8886326
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:	None defined				
MINOR					
201.	O-ring missing in groove		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:07Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-60944A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Cartridge				8886326
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Chamber gage failure		100%	3.2	9202253 9202254 9202255
102.	Gap, rear of rotating hands		0.40%	3.2	Gage
103.	O-ring exposed		0.40%	3.2	Visual
104.	Pull test	80	0.65%	3.2	4.5.3
105.	Air pressure	800	0.015%	3.3	4.5.4
MINOR					
201.	Total length		0.65%	3.2	Gage
202.	Marking misleading or unidentifiable		0.65%	3.2	Visual
203.	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:07Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-60944A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Linked Ammunition Prior to Packing				8886405
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	All six (6) tabs of link not in groove		0.40%	3.2	Visual
102.	Link inverted		0.40%	3.2	Visual
MINOR:	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:07Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-60944 A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8865432
4.4.2.7	Unsealed Fiber Box				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Incorrect number of cartridges		0.40%	3.2	Visual
102.	Fillers missing		0.40%	3.2	Visual
103.	Separator missing		0.40%	3.2	Visual
MINOR:	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:07Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-60944A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.8	Sealed Fiber Box, Prior to Sealing Box		8865432
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Container damaged		0.40%	3.2	Visual
102.	Corners not blunted		0.40%	3.2	Visual
103.	Heat seal test of packing seals	*	*	3.2	4.5.1

NOTES:

* Sampling and rejection shall be in accordance with MIL-P-116.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:07Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-60944 A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Unsealed Wooden Packing Box				8865431
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Marking of bos misleading of unidentifiable		0.40%	3.2	Visual
102.	Bag torn or perforated		0.40%	3.2	Visual
103.	Bag improperly sealed		0.40%	3.2	Visual
MINOR:	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:07Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-60944A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Sealed Wooden Packing Box				8865431
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR					
101.	Box damaged		0.40%	3.2	Visual
MINOR					
201.	Contents loose		0.65%	3.2	Manual
202.	Can seal missing or improperly positioned		0.65%	3.2	Visual
203.	Marking misleading or unidentifiable		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Check test for deterioration of primers. If the total time between original acceptance of any lot and the assembly of that lot into the cartridge exceeds two years, or if the primers have been subjected to adverse conditions, however brief, at any time since previous tests, the primer lot shall be subjected to and must satisfactorily pass, the check test for deterioration specified in MIL-P-60942 immediately before the primer lot is assembled into the This test shall be performed by the contractor on primers selected by the Government inspector at the facility assembling the primers into the cartridge. (See 6.6)

4.4.3.2 Propellant weight of case, cartridge. The propellant weight shall be determined and then check weighed 100 percent. The check-weighing shall be accomplished independently of the original weighing or determination, using a different balance from what used to make the original weighing, and if performed manually, shall be performed by another operator. Any charge which fails to comply with the requirement specified on the applicable drawing shall be classified defective and removed from the lot.

4.4.3.3 Security of crimp of base plug and action time of cartridge case assembly. Five (5) base plug and primer assemblies shall be randomly selected every four (4) hours from each manual primer assembly machine or twenty (20) base plug and primer assemblies shall be randomly selected every four (4) hours from each automatic primer assembly. These assemblies shall be assembled to cartridge cases for test of Security of crimp of base plug and action time" determination. The base plug and primer assemblies produced by each primer machine shall be kept segregated and identified. They shall not be used in production until the above tests have been performed. If any base plug moves more than .005 above flush with rear of case, or the action time of any cartridge case assembly exceeds 4.0 milliseconds, the four (4) hours production from each manual primer assembly machine or each automatic primer assembly machine involved shall be rejected.

4.4.3.4 Rapid fire functioning. One hundred (100) cartridges shall be randomly selected from a completed lot and subjected to this test. If any gun stoppage occurs of if any projectile sticks in the gun bore, the lot shall be rejected.

4.4.3.5 Functioning. One hundred (100) cartridges shall be selected from each lot for this test. The sample cartridges shall be selected at random prior to linking and then linked with the same lot of links to which its respective end item has been assembled.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

4.4.3.5.1 Rejection. The lot shall be rejected if:

a. Mean velocity and/or standard deviation fail to meet the applicable requirement.

b. Any primer blows back (as evidenced by perforation of the primer cup or smoke deposit on base plug or cartridge case base).

c. Two (2) or more primers misfire.

d. Any projectile sticks in gun bore.

e. Three (3) or more base plugs are more than .005 above flush with rear of cartridge case (See 4.5.5 or one (1) or more base plugs exceeds .010 with rear of cartridge case or jams the automatic weapon.

f. If the action time of one (1) or two (2) rounds is over four (4) milliseconds, an additional 200 rounds shall be tested. The results for the 300 rounds shall be combined. If three (2) or more rounds are over four (4) milliseconds or if one (1) round is over ten (10) milliseconds, the lot shall be rejected.

4.4.3.6 Suitability test plan (Informational test only). Beginning with the first lot produced by each producer and continuing until that producer has submitted three (3) consecutive lots that are accepted in accordance with Paragraph 4.4.3.5, an extra sample of ninety (90) rounds shall be selected from each lot and pre-conditioned and tested as follows:

a. The ninety (90) rounds shall be packaged in their regular shipping containers and subjected to transportation vibration environment in accordance with MIL-STD-331, Test No. 119.

b. After transportation vibration, the rounds shall be unpacked and subjected to the JAN temperature and humidity cycle (14 days) specified in MIL-STD-331, Test No. 105.

c. After temperature and humidity cycle, the rounds shall be temperature conditioned and fired as follows:

30 rounds +165 degrees F ± 5 degrees.
30 rounds ambient (between +40 and +110 degrees F).
30 rounds -65 degrees F ± 5 degrees F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

d. Fire the rounds in accordance with Paragraph 4.5.7 and with TECOM Material test procedures, TECP 700-700 Volume 4. Test results, failure analysis reports and other information as required shall be forwarded to ARRADCOM, ATTN: DRDAR-QAA-S for evaluation.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method Column in the tables starting with Paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures.

4.5.1 Heat seal test of packing seals. This test shall be performed in accordance with Military Specification MIL-P-116. Samples so tested shall not be returned to the lot.

4.5.2 Security of base plug on cartridge case assembly. The cartridge case assembly shall be assembled to a projectile and fired. Measurement for base plug more than .005 above flush from the rear of the cartridge case, shall be measured from the highest point on the base plug to a point on cartridge case directly beside it, radially. Observation shall be made for action time using approved equipment.

4.5.3 Pull test of projectile. The cartridge shall be placed in an approved fixture and the tension specified on the drawing shall be applied. Cartridge case assemblies may be reused. The cartridge shall be pulled until separation occures and the data recorded.

4.5.4 Air pressure. The cartridge shall be placed in an approved fixture and a measured quantity of air applied to produce the required air pressure. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.5 Movement of base plug. The movement of the base plug shall be measured from the highest point on the base plug to a point on cartridge case directly beside it radially.

4.5.6 Rapid fire functioning. This test shall be conducted at a Government owned proving round. The cartridge shall be fired from an approved launcher in bursts of approximately ten rounds. Observation shall be made for gun stoppage and projectile stuck in the gun bore.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

4.5.7 Functioning. The rounds being tested, including the standard control rounds, shall be temperature conditioned at 70°F ± 5°F for a least eight (8) hours, then fired within fifteen (15) minutes after being removed from temperature soak. The test and standard control rounds shall be fired at a rate not to exceed one round per minute using an approved launcher. The launcher shall have been "broken-in" if new, with at least forty (40) rounds and placed on an approved mount for running the test. At least six (6) gun-warmers shall be rapid fired at the start of the test. After the gun-warmers have been fired, twelve (12) of the standard control rounds shall be fired. These shall be followed by the test samples and then twelve (12) more of the standard control rounds. Distances to impact 100 meters minimum. Impact media, a backstop suitable to provide safety to range personnel and the public. The velocity shall be measured at 30 feet from the muzzle of the launcher and check measured at the same base line. The monitoring devices and time recorders shall be a dual system set-up for recording two (2) separate readings and shall be within 3 feet per second. If the two (2) readings differ more than 3 feet per second (individual shots), the results shall be discarded and another round fired in its place. When proving ground reports results for mean velocity and standard deviation, the number of “no-test” rounds shall also be reported. Observations shall be made for functioning and results calculated and recorded for (a) cartridge acton time and (b) mean velocity and standard deviation (See 6.7). The mean velocity of the lot being tested shall be corrected by the correction factor determined for the particular test launcher being used on the day of the test firing. When velocity values are suspected to be outliers, they shall be tested using the statistical procedure approved by the Government proving ground and the mean velocity and standard deviation adjusted accordingly. However, nor more than four values consisting of nor more than two on the high side and no more than two on the low side, shall be considered for exclusion. The correction factor for the test launcher shall be determined by subtracting the mean velocity of the standard control rounds fired during the test from the standard velocity previously established for the standard control rounds. Either a positive or a negative correction factor will result depending on the mean velocity of the standard control rounds fired during the test. Algebraically add the resultant correction factor to the mean velocity of the test rounds.

5. PACKAGING

5.1 Preservation and packaging.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

5.1.1 Level C. The cartridge shall be preserved and packaged in accordance with 9251995.

5.2 Packing.

5.2.1 Level C. The cartridge, preserved and packaged as specified in 5.1.1, shall be packed in accordance with Dwg. 9251996.

5.3 Marking. Marking shall be in accordance with Dwg. 9251996 and Department of Transporation Regulations 49 CFR 100-199.

5.4 Shipping. When shipments from more than one lot are shipped as a carload, each lot shall be kept separate, and the devision between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. This specification covers the loading assembling and packing for Cartridge, 40MM, Practice, M385.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078(AR). Submit equipment designs as required to Commander, ARRADCOM, ATTN: DRDAR-QAA-I, Dover NJ 07801. Request letter of submittal state contractor, contract number, specification number, item nomenclature and classification of defects or test paragraph.

6.4 Submission of results of contractor-conducted examinations and tests. Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to Commander, ARRADCOM, ATTN: DRDAR-QAA-S.

6.5 Submission of test data. In addition to the normal distribution of records, when the cartridges are procured by ARRADCOM one (1) copy of all ballistic data and ammunition data cards shall be forwarded to: Commander, ARRADCOM, ATTN: DRDAR-QAA-S, Dover, NJ 07801.

6.6 Cost of check test. The Contracting Officer will arrange for the contractor to be reimbursed for the expense incurred in the performance of the check test for deterioration of the primer assemblies. The tests shall be conducted at Government expense without cost to the contractor who loaded the primer assemblies or

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

to the contractor assembling the primer assemblies into the cartridge and shall not constitute a basis for rejection against eight contractor except where deterioration, has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer assembly lot was under the jurisdiction of either contractor.

6.7 Standard deviation shall be calculated from the following formula.

$$S = \sqrt{\frac{\Sigma (X - \Sigma X)^2}{n-1}}$$

Where:

X = each individual value

$\bar{X}$ = sample arithmetic mean = $\frac{X}{n}$

$\Sigma (X - \bar{X})^2$ = The sum of squares of the differences between the sample mean and each individual value.

$n-1$ = one less than the sample

n = sample size

6.7.1 For a faster and easier method of arriving at the standard deviation, the following alternate method may be used.

$$S = \sqrt{\frac{n \Sigma X^2 - (\Sigma X)^2}{n (n-1)}}$$

Other approved standard deviation formulas may be used.

6.8 Combining or proving ground tests. When the contractor for the cartridge is also the contractor for one or more of the components thereof, the proving ground tests of the contractor may be combined with the proving ground tests of the cartridge, to save expense, upon agreement between the procuring activity and the contractor. In cases where the cartridge specification does not cover all the proving ground tests specified for component, the additional tests specified in the component specification shall be conducted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

6.8 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARMDCOM.

6.10 Proving ground test summary:

Test	Sample Size	Requirements
Functioning	100	See 3.4 and 4.4.3.5.1
Rapid firing	100	4.4.3.4

6.11 If any cartridge case, prior to insertion of the base plug and primer, is suspected of containing an underweight or overweight propellant charge, based on visual inspection, it will be removed from the lot and weighed on suitable scales. Any cartridge case found with less than 75 percent or more than 125 percent of the assessed propellant load will be classified as a critical defect and removed from the lot. Any cartridge case found to have a propellant weight out of drawing tolerance but within ± 25 percent of the assessed propellant load will be classified as a major defect and removed from the lot.

6.12 Charges from the previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
ARMY-AR

Preparing Activity:
ARMY-AR

Project Number: 1310-A 248

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-60944A Cartridge, 40MM, Practice, M385 LAP

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.