INCH-POUND

MIL-F-70807 (AR)
AMENDMENT 4
15 March 1991
SUPERSEDING
AMENDMENT 3
23 February 1990

MILITARY SPECIFICATION

FUZE, PD: M745
(LESS BOOSTER AND LEAD)

This amendment forms a part of Military Specification MIL-F-70807 (AR), dated 11 March 1988, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.2, DRAWINGS, Add "9347415 - Packing & Marking of Box Fiberboard for Fuze, Multi-Option, M734 and Fuze, PD, M745" and "9381685 - Packing & Marking of Container, M548 for Fuze, Multi-Option, M734 and Fuze, PD, M745."

* Delete old drawing number and substitute new drawing number wherever it appears in this specification as follows:

Old Dwg. No.	New Dwg. No.
11737001	11927103
11737000	11927102
11737007	11927120
11744131	11927094
11740827	11927066
11740828	11927087
11740824	11927137
11744134	11927095
11744135	11927116
11744136	11927117
11744145	11927118
11737030	11927109
11737031	11927125
11737029	11927108
11744139	11927141
11744140	11927142
11744133	11927140
11744152	11927146
11737024	11927124

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

PAGE 2

Old Dwg. No.	New Dwg. No.
11740823	11927136
11744129	11927093
11744128	11927092
11744147	11927144
11744146	11927143
11744126	11927139
11737016	11927122
11740821	11927084
11744127	11927091
11737012	11927106
11744137	11927096
11744138	11927097
11744130	11927115
11744141	11927098
11737020	11927079
11737021	11927080
11737027	11927081
11740819	11927134
11744125	11927138
11737013	11927121
11740806	11927130
11744121	11927067
11737010	11927105
11737026	11927107
11737016	11927122
11744148	11927074
11737023	11927123
11744151	11927145
11737000	11927102
11740826	11927086
11740828	11927087
11740829	11927088
11744120	11927090
11737030	11927109
11737001	11927103

PAGE 3

3.1.1: Change "458" to read "436," and change "428" to read "406."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

PAGE 4

3.1.4: Delete in its entirety and substitute the following:

"3.1.4 Ballistic sample.

3.1.4.1 Initial production lot. Select at random ballistic lot acceptance samples from first production lot. Ballistic lot acceptance test plan is shown in figure 2.

3.1.4.2 Production lot. Select at random ballistic lot acceptance samples from each production lot. Ballistic lot acceptance test plan is shown in figure 3."

3.2: Change "(Figure 3)" to read "(Figure 4)."

PAGE 5

3.3: Change "-25°F" to read "-50°F"

PAGE 7

3.3.2.4: Line 4, Change "low" to read "low (-50°F)"

PAGE 9

* 4.4.1.d Delete in its entirety and substitute the following:

"The lot size shall be a maximum of 50,000 fuzes or one month's production, whichever is smaller. Minimum lot size shall be 1,000 fuzes for lots 1 and 2 and 5,000 fuzes thereafter."

PAGE 10

4.4.3.1: Change "Figure 2" to read Figure 2 and 3."

4.4.3.2: Change "Figure 2" to read "Figure 2 and 3."

4.4.3.2: Delete the last sentence of the paragraph.

PAGE 13

4.5.1.1.2.1: Delete the words "high explosive of the."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

PAGE 15

4.5.1.2.1.5: Change "Test 101.3, Procedure I" to read "Test 101.2, Procedure II."

4.5.1.2.1.6: Change "Test 102.2" to read "Test 102.1."

4.5.1.2.1.7: Change "Test 103.2" to read "Test 103.1."

* 4.5.2.1: Change "The S&A Device shall be loaded with a conductive dummy detonator and placed in the tester of 4.4.4.1.2." to "The S&A Device shall be placed in the tester of 4.4.4.1.2."

PAGE 17

6.2.2: Delete last sentence of paragraph.

PAGE 21

Table I: Delete "11740827 Pad, Booster 10"
"11740828 Cap, Booster 10"

PAGE 27

4.4.2.4: Major 102, Change ".040" to read ".042."

PAGE 34

4.4.2.11: Minor 201, Change ".264" to read ".268."

PAGE 36

* 4.4.2.13: Change Note A:

From: "Two-thirds of the sample shall be conditioned to -50°F and one-third to +145°F for two hours minimum. The barrier shall be assembled into a loaded S&A (11737010). The S&A explosives shall be initiated electrically with the rotor in the safe position. There shall be no evidence of fragmentation, cracking or breakthrough of the barrier, bulging in excess of .015 inch on booster side face, or scorching of lead charge explosives after the M61 detonator has fire."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

TO: "Two-thirds of the sample shall be conditioned to -50°F and one-third to +145°F for two hours minimum. The barrier shall be assembled into a loaded S&A (11737010). The S&A explosives shall be initiated mechanically by stabbing the delay primer with the rotor in the safe position. There shall be no evidence of fragmentation, cracking or break-through of the barrier, bulging in excess of .015 inch on booster side face, or scorching of lead charge explosives after the M61 detonator has fired."

Note A, Add: "Special inspection level S-4 shall be applied for selecting sample size."

PAGE 46

4.4.2.22: Delete paragraph in its entirety and substitute new paragraph included.

PAGE 55

4.4.2.31: Delete Major 101 in its entirety and substitute "None defined."

PAGE 64

Delete in its entirety and substitute included pages 64 and 64a.

PAGE 64a

* Change Duds "3/4" to "6/7"

PAGE 65

Delete in its entirety and substitute per included sheet.

PAGE 66

Delete in its entirety and substitute per included sheet.

PAGE 67

Figure 4: Add new figure per included sheet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS


PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
4.4.2.22	Cam				11744137
					NEXT HIGHER ASSEMBLY 11737016
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Insufficient strength of arm		0.40%	3.1	Force test (Dwg. Note 5)
102	.203 arm height or perpendicularity out-of-tolerance		0.40%	3.1	Gage
103	.140 arm length out-of-tolerance		0.40%	3.1	Gage
Minor					
201	.125 diameter out-of-tolerance		0.65%	3.1	Gage
202	.500 length out-of-tolerance		0.65%	3.1	Gage
203	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

FIGURE 1

FIRST ARTICLE INSPECTION FLOW CHART



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

FIGURE 1 (continuation)

CONT.

CONT.

CONT.

FUZE M745
(WITH INERT BOOSTER AND LEAD)

ENVIRONMENTAL REQ.	REQ. PARA.	TEST PARA.	N	SAFE AC	SAFE RE	OPER AC	OPER RE	
TEMP. AND HUMIDITY	3.3.1.3.1	4.5.1.2.1.1	14	0	1	2	3	14
SALT FOG	3.3.1.3.1	4.5.1.2.1.2	8	0	1	0	1	4
DROP TEST (1.5 M)	3.3.1.3.1	4.5.1.2.1.3	20	0	1	2	3	10
T.V. TEMPERATURE	3.3.1.3.1	4.5.1.2.1.4	16	0	1	2	3	16
JOLT	3.3.1.3.2	4.5.1.2.1.5	12	0	1	NA	NA	
JUMBLE	3.3.1.3.2	4.5.1.2.1.6	8	0	1	NA	NA	
40 FT. DROP	3.3.1.3.2	4.5.1.2.1.7	10	0	1	NA	NA	

TO GROUP C
BALLISTICS
TEST PLAN

44

294

FUZE PD, M745
LOADED 11737000

44

BALLISTIC TEST PLAN
REQ. PARA. 3.3.1.1 & 3.3.1.2
TEST PARA. 4.5.1.1
N=338

GROUP	CHG.	QE	+145F	+70F	-25F	-50F	TOTAL
A **	0	85	25	25	25	25	100
B	4	45	25	163	–	–	188
C *	4	45	25	–	25	–	50
TOTAL			75	188	50	25	338

ACCEPT/REJECT CRITERIA
1. BY DEFECT CATEGORY

	AC/RE
DUDS	6/7
PREMATURES	0/1***

ENGINEERING
CONTROL
SAMPLES

*Rounds from drop test (1.5M) that fail to function will not count towards the accept/reject dud criteria.


**M720 body (H.E. Fill) must be substituted for M722 body in this group.


***Test suspended immediately for failure analysis.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

FIGURE 2

INITIAL LOT PERFORMANCE INSPECTION FLOW CHART







** M720 body (H.E. Fill) must be substituted for M722 body in this group.


OVERALL CRITERIA	N	ACPE	APPLICABLE PARA
DUDS	210	3/4	4.5.1.1.2.1
PREMATURES	210	0/1*	4.5.1.1.2.2


* TESTS SUSPENDED IMMEDIATELY FOR FAILURE ANALYSIS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

FIGURE 3

LOT PERFORMANCE INSPECTION FLOW CHART






OVERALL CRITERIA	N	AC/RE	APPLICABLE PARA
DUDS	108	2/3	4.5.1.1.2.1
PREMATURES	108	0/1*	4.5.1.1.2.2

* TESTS SUSPENDED IMMEDIATELY FOR FAILURE ANALYSIS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.



NOTES

1. WEIGHT OF FULLY LOADED FUZE IS 50 +.00/-.10 LBS
2. .1715 DIA HOLE SHALL BE ADJACENT TO SCALLOP IN BOOSTER CAVITY SUCH THAT LEAD CAN BE INSERTED
3. S & A ROTOR SHALL BE IN SAFE POSITION (DWGS 11737010 AND 11737007). M61 DETONATOR (MASS5M) IN DRIVER HOUSING ASSY (11737036) SHALL NOT BE VISIBLE THROUGH BARRIER LEAD HOLE IN AFT END OF FUZE
4. FUZE SHALL BE PERMANENTLY MARKED PER DWGS 11760810
5. FUZE SHOWN IS NOT FULLY LOADED. SEE DWG NO. 11737000 FOR LOADED ASSEMBLY AND COMPLETE INTERFACE DIMENSIONS

FIGURE 4 INTERFACE CONTROL DRAWING

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1390-A710)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.