MIL-W-63389 (AR)
7 January 1980

MILITARY SPECIFICATION

WARHEAD, GUIDED MISSILE, HE, M207E1
LINER FOR

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the quality assurance provisions and special requirements not covered by the drawings for the fabrication and packing of liner for M207E1 Warhead.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposals form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

FSC: 1336

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

DRAWINGS (SEE 6.4)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

9332524 Liner

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with applicable drawings and specifications.

3.2 Parts. The parts shall comply with all requirements specified on Drawing 9332524, all associated drawings and with requirements of applicable standards and specifications.

3.3 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.4 Workmanship. All parts shall be fabricated in a thorough, workmanlike manner. The parts shall be free of burrs, chips, sharp edges, cracks, unblended radii, dents, tool marks, chipped edges, warpage, gouges, surface defects, dirt, grease, corrosion products, burn marks, and other foreign matter. The cleaning method used shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance Provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detailed specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The following types of inspection shall be conducted.

a. First article inspections

b. Quality conformance inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following item in sample quantities as indicated.

Part Description	Drawing	Quantity
Liner	9332524	20

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-63389 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Liner				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Liner, (Dwg. 9332524)				
	Examination for Defects	20		3.2	4.4.2.1

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of warhead metal parts shall contain:

a. Liner 9332524 from not more than one interfix lot number from one manufacturer.

4.4.2 Examinations. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-63389 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Liner		9332524
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Runout of base with datums A&B		0.40%	3.2	Gage
102	Length from base to datum B		0.40%	3.2	Gage
103	Length from datum A to datum B		0.40%	3.2	Gage
104	Straightness on large outside surface		0.40%	3.2	Gage
105	Wall thickness variation in any axial plane		0.40%	3.2	Gage
106	Wall thickness variation in any transverse plane		100%	3.2	Gage
107	Depth to spherical radius		0.40%	3.2	Gage
108	Length from datum B to datum at nose end		0.40%	3.2	Gage
109	Length of datums at nose end		0.40%	3.2	Gage
110	Wall thickness at large datum, nose end		0.40%	3.2	Gage
111	Wall thickness at small datum, nose end		0.40%	3.2	Gage
112	Outside diameter		0.40%	3.2	Gage
113	Runout of outside diameter with datums A&B		0.40%	3.2	Gage
Minor					
201	Surface finish improper		0.65%	3.2	Gage
202	Evidence of poor workmanship		0x100%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in First Article and Quality Conformance inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection

4.5.1 Materials, components and processes. Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspection. The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Section 3 and 5 of this specification in accordance with 4.4.2 herein and Table 1.

5. PACKAGING

5.1 Packaging and packing. The parts shall be packaged and packed in accordance with the requirements of MIL-STD-1169.

5.2 Marking. Marking shall be in accordance with the requirements of MIL-STD-1169.

NOTES

6.1 Intended use. The liner covered by this specification is a component of the Improved TOW Warhead Section, Guided Missile, HE, M207E1.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, NJ 07801.

Custodian:
ARMY-AR

Preparing Activity:
ARMY-AR

Project Number: 1336-A337

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.