MILITARY SPECIFICATION

HANDLE, BEADED, INFLATION ASSEMBLY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for two types of inflation assembly beaded handles.

1,2 Classification. The inflation assembly beaded handles shall be of the following types (see 6.2):

TYPE	APPLICATION
I	FLU-8A/P Inflator LPU-21B/P Life Preserver
II	LRU-18/U Life Raft

2. APPLICABLE DOCUMENTS

2.1 Issue of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

PPP-B-636 Boxes, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Engineering Specifications and Standards Department (Code 93), Naval Air Engineering Center, Lakehurst, NJ 08733, by using the self-addressed Standardization Document Improvement proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:55Z
Check the source to verify that this is the current version before use.

STANDARDS

Federal

FED-STD-751	Stitches, Seams, and Stitchings

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Markings for Shipment and Storage

DRAWINGS

Naval Air Systems Command

975AS121	Handle, Beaded, Inflation Assembly

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific acquisition functions should be obtained from the acquiring activity or as directed by the contracting officer.)

3. REQUIREMENTS

301 First article. When specified (see 6.2), the contractor shall furnish sample units for first article inspection and approval (see 4.3 and 6.3),

3.2 Materials and components. Materials and components shall conform to the applicable specifications and drawings as listed or required herein.

3.3 Design and construction. The beaded handles shall be constructed in accordance with NAVAIR Drawing 975AS121.

3.3.1 Stitching. All the machine stitching shall be accomplished with Stitch Type 301 of FED-STD-751. There shall be eight to ten stitches per inch. Unless otherwise specified, the ends of the stitching shall be backstitched by overlapping on itself, a minimum of 1/2 inch. Thread breaks shall be backstitched, back of the break, a minimum of 1/2 inch. The thread tension shall be maintained so that there shall not be any loose or tight stitching and the lock shall be embedded in the materials sewn together. All the thread ends shall be trimmed to a length of 1/4 to 3/8 inch.

3.4 Breaking strength of the lanyards. When tested as specified in 4.5.3, the lanyards breaking strength shall conform to Table III.

3.5 Workmanship, The beaded handle shall be uniform in quality and free from defects and irregularities which could adversely affect performance, reliability or durability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:55Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3).

2. Quality conformance inspection (see 4.4).

4.3 First article.

4.3.1 First article samples. Unless otherwise specified, as soon as practicable after award of the contract or order, the manufacturer shall submit three beaded handles. The samples shall be representative of the construction, workmanship, components, and materials to be used during production. When a manufacturer is in continuous production of these beaded handles from contract to contract, submission of further first article samples on the new contract may be waived at the discretion of the acquiring activity (see 6.2d). Approval of the first article samples or the waiving of the first article inspection does not exempt the requirements for performing the quality conformance inspection. The first article samples shall be forwarded as specified in the contract or order (see 6.2e).

4.3.2 First article sample approval. Upon completion of the first article inspection program, recommendations and comments pertinent for use in monitoring production, will be forwarded by the Government activity responsible for the inspection program (see 6.2e) to the contracting officer. One approved beaded handle will be returned to the manufacturer for use in monitoring production. One beaded handle will be consumed or destroyed in the first article inspection and shall not be considered as part of the quantity to be delivered under contract. The other beaded handle will be retained by the inspection laboratory for reference.

4.4 Quality conformance inspection. The sampling and inspection levels shall conform to MIL-STD-105. The quality conformance inspection shall consist of the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:55Z
Check the source to verify that this is the current version before use.

Visual Inspection
Dimensional Inspection
Breaking Strength of the Lanyards
Preparation for Delivery

4.4.1 Sampling.

4.4.1.1 Inspection lot. The inspection lot size shall be expressed in units of one beaded handle made from the same material and under the same conditions. The sample unit shall be one beaded handle.

4.4.1.2 Preparation for delivery. The inspection lot size shall be expressed in units of one fully prepared shipping container, containing one type of beaded handle. The sample unit shall be one shipping container fully prepared for delivery except that it need not be sealed.

4.5 Inspection methods. The inspection methods, sample size and acceptance criteria shall conform to Table I.

4.5.1 Visual examinations, Each beaded handle shall be examined for critical defects to determine conformance *to* this specification. Each beaded handle, selected as a sample unit from a lot, shall be examined visually for minor defects to determine conformance to this specification. The classification and list of defects, Table II, shall be used to classify and enumerate the defects found.

4.5.2 Dimensional examination, Each of the beaded handles selected as a sample unit from the lot, shall be thoroughly checked dimensionally by use of any suitable measuring device to determine conformance to this specification. The list of defects, Table II', shall be used to enumerate the defects found.

4.5.3 Breaking strength of the lanyards. The breaking strength of the lanyard shall be determined by testing in a suitable inspection apparatus with a no-load speed of 12 $\pm$ 1/2 inches per minute. The test will be completed when failure occurs, The inspection apparatus shall have jaws to secure the webbing of the beaded handle and a 1/2 inch diameter mandrel for the lanyard. The jaws shall grasp the beaded handle webbing at the end opposite the 975AS121-2 lanyard. For the Type I handles, only the lanyard under test shall be looped on the mandrel, and neither the releasing pin, over-hand knot nor lark's head knot will be installed on the 975AS121-5 lanyard. Test results shall conform to requirements set forth in Table III.

4.5.4 Preparation for delivery. Each of the fully prepared shipping containers shall be visually examined to determine that the packaging, packing, and marking conform to this specification. The list of defects, Table II, shall be used to classify and enumerate defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:55Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. Packaging shall be level A or minimum protection, as specified (see 6.2f),

5.1.1 Level A. Each beaded handle shall be placed into a clear polyethylene bag along with an identification label.

5.1.2 Minimum protection. The beaded handle of one type shall be packaged to afford the minimum degree of protection necessary *to* prevent damage during shipment under normal environmental conditions and commercial modes of transportation.

5.2 Packing. Packing shall be level A or minimum protection as specified (see 6.2f).

5.2.1 Level A. Fifty beaded handles, packaged as specified in 5.1, shall be packed in a fiberboard shipping container. except that the fiberboard container shall be weather-resistant class, variety SW, grade V3C and V3S. In addition, each container shall be reinforced with flat steel strapping or tape banding in accordance with the appendix to PPP-B-636.

5.2,2 Minimum protection. The packaged beaded handles shall be packed in a manner that will insure safe transportation at the lowest rate to the point of delivery, Containers shall conform to the minimum requirements of the rules and regulations applicable to the mode of transportation selected.

5.3 Marking. Unit and shipping containers shall be marked in accordance with the requirements of MIL-STD-129.

6. NOTES

6.1 Intended use. Beaded handles together with the appropriate inflation device are intended for use as emergency and life support equipment by personnel forced down at sea.

6.2 Acquisition requirements. Acquisition documents shall specify the following:

a. Title, number, type and date of this specification.

b. Government part number.

c. Quantity desired.

d. Whether first article inspection is waived (See 4.3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:55Z
Check the source to verify that this is the current version before use.

Name and address of the first article inspection laboratory (see 4.4.1); including the Government activity responsible for conducting the inspection program (see 4.3.2).

f. Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 First article. When a first article is required, it shall be tested and approved under the appropriate provisions of 7-104.55 of the Defense Acquisition Regulations. The first article shall be a first production item. The first article shall consist of three units. The contracting officer shall include specific instructions in all acquisition instruments, regarding arrangements for examinations, test and approval of the first article.

Preparing activity
Navy - AS
(Project No. 4220-N286)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:55Z
Check the source to verify that this is the current version before use.

TABLE I. Quality conformance inspection.

Inspection	Paragraph		Sample Size 1/	Acceptance Criteria
	Requirement	Method		
Visual	Section 3 and Applicable Drawings	4.5.1	Level II for minor defects	AQL of 15.0 defects per 100 units
Dimensional	Section 3 and Applicable Drawings	4.5.2	Inspection Level S-3	AQL of 10.0 defects per 100 units
Preparation for Delivery	Section 5	4.5.4	Inspection Level S-2	AQL of 2.5 defects per 100 units
Breaking Strength of Lanyard	Para 3,4	4*5.3	Inspection Level S-1	ACC 0 REJ 1

1/ The sample size shall be based on the applicable sample size code letter corresponding to the specified level in MIL-STD-105,

TABLE II. Classification of defects for visual examination.

CRITICAL
1. Stitching on beaded handle not as specified. 2. Any non-specified hole, cut or burn. 3. Any missing or extra beads on handle. 4. Any snap fastener missing, improperly oriented or clinched or otherwise defective.
MINOR
1. Any cut edge of webbing not seared or containing sharp edge. 2. The snap fasteners will be checked for proper function, position and alignment,

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:55Z
Check the source to verify that this is the current version before use.

TABLE III. Breaking strengths,

Handle	Cord	
	975AS121-2	975AS121-5 1/
975AS121-11	140 lbs	100 lbs
975AS121-12	140 lbs	N/A

l_/ Test shall be performed without Releasing Pin, Overhand Knot and Lark's Head Knot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:55Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-H-85478A(AS) HANDLE, BEADED, INFLATION ASSEMBLY

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2 REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

Replaces edition of 1 Jan 72 which may be used.

S/N 0102-LF-001-4260

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:55Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE AIR FORCE

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 73236 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE AIR FORCE

Naval Air Engineering Center
ESSD Code 9312
Lakehurst, NJ 08733

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:55Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:55Z
Check the source to verify that this is the current version before use.