MIL-C-60987 (AR)
Amendment 1
15 September 1981

MILITARY SPECIFICATION

CARTRIDGE, 40MM, PRACTICE, M407A1;
BALL AND SKIRT ASSEMBLY AND
OGIVE FOR METAL PARTS FOR

This amendment forms a part of Military Specification MIL-C-60987 (MU), dated 11 January 1968, and is approved for use by the US Army Armament Research and Development Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

Page 1

Add the following preamble underneath the title:

"This specification is approved by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 7

4.3.2.1: Add Major Defect 103 under Major Defect 101 as follows:

"103: Any foreign matter prior to assembling to skirt... Visual 01009."

4.3.2.2: Add Major Defect 116 as follows:

"Major AQL 2.50 percent
116. Gap, max. (see note) . . . Gage 02020
The lot shall be rejected if any item in the sample has a gap exceeding .035 or the number of defective over .020 exceeds the acceptance number."

PAGE 9

4.3.2.4: Delete in its entirety.

Add new paragraph 4.3.2.5 as follows:

"4.3.2.5 Ball and skirt, prior to applying adhesive (See Dwg. 8865604)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

FSC: 1310

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major	AQL 0.40 Percent		
101.	Evidence of protective coating . ..	Visual	10001
Minor:	None defined"		

PAGE 11

4.3.3.4: Delete in its entirety and substitute the following:

"4.3.2.4 Push test of ball and ball and skirt assembly (See Dwg.8865604), Major defect, Code No. (11001). Fifty (50) ball and skirt assemblies shall be selected from each lot and subjected to this test. If two (2) or more ball and skirt assemblies fail to comply with the requirement specified on the applicable drawing, or if one (1) or more is below a reading of 1000 lbs., the lot shall be rejected. The reading used shall be the adhesive separation, not the crimp separation reading. The test shall be performed as specified in 4. 4.2 using equipment in accordance with 4.3.4."

Add new paragraph 4.3.3.6 as follows:

"4.3.3.6 Pot life of adhesive (See 6.5), (See Dwg. 9247217), Major defect, Code No. (11001). Each batch of adhesive mixed for use in assembly of ball and skirts shall be subjected to this determination. If any material fails to comply with the applicable requirement, it shall not be used for assembly of ball and skirts. Ball and skirts which have been assembled with adhesive which exceeded the pot life requirement shall be rejected. The test shall be performed as specified in 4.4.5."

Add new paragraph 4.3.3.7 as follows:

"4.3.3.7 Curing temperature of ball and skirt assembly before removed from oven, (See Dwg. 9247217), Major defect, Code No. (12001). Five (5) ball and skirt assemblies shall be selected from each four (4) hours production or portion thereof and subjected to measurement of the current temperature specified on the applicable drawing. If any assembly fails to comply with the specified requirement, the quantity represented by failing part shall be rejected. The test shall be performed as specified in 4.4.6 using equipment in accordance with 4.3.4."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.

PAGE 12

4.4.2: Delete in its entirety and substitute the following:

"4.4.2 Push test of ball on ball and skirt assembly. The ball and skirt assembly shall be placed in the fixture specified on the equipment list and the force specified on Dwg. 8865604 shall be applied until complete separation occurs. NOTE: If any ball and skirt shows no adhesive sticking, corrective action shall be taken. This test is a destructive test. Parts so tested shall not be returned to the lot."

Add new paragraph 4.4.5 as follows:

"4.4.5 Pot life of adhesive. The time from preparation of the adhesive for use in assembly of the ball and skirts to its application to the skirt shall be determined. Any method considered satisfactory to the Contracting Officer may be used in performing this determination. This test is a non-destructive test. Adhesive so tested may be returned to the lot."

Add new paragraph 4.4.6 as follows:

"4.4.6 Curing temperature of ball and skirt assembly, before removing from oven. The ball and skirt assembly shall be subjected to this test using equipment specified on the equipment list. This test is a non-destructive test. Parts so tested may be returned to the lot."

PAGE 15

Add new paragraph 6.5 as follows:

"6.5 The pot life of the adhesive is defined as the time from mixing the adhesive to its application to the skirt. If the adhesive is frozen immediately after mixing, the pot life is defined as the time the adhesive reaches ambient temperature to the time of application to the skirt."

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No. 1310-A267

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:07Z
Check the source to verify that this is the current version before use.