MIL-F-60998A (PA)
AMENDMENT 2
3 June 1975
SUPERSEDING
AMENDMENT 1
16 March 1972

MILITARY SPECIFICATION

FUZE, PD, M557

LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-F-60998A, dated 15 March 1970, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 3, para. 3.6.2.2 add: "The fuzes tested with a target, using the 155mm How., shall cause the projectile to function at no more than 70 feet behind the target."

Page 5 - paragraph 4.2.2.2, Add Major 105:

105. Flash tube stake inadequate (see 4.3.4) . . . . . Test 02008

Page 5 - paragraph 4.2.2.2

Delete AQL 0.65 percent and substitute AQL 1.00 percent.

Page 6, para. 4.2.2.4, after "see dwg. 8595541", add: "or dwg. 10520747."

Page 7, para. 4.2.3.4.2.2, delete: "sixty-five (65)" loaded fuze assemblies add: "sixty-four (64) loaded fuze assemblies"

Page 7, para. 4.2.3.4.2.2, Table II, 90MM Gun, Sample Size Superquick, delete: "10" add: "9"

Page 10, Table I, Acceptance Criteria, Delay, Delete: "Projectile functions outside zone behind screen (90mm)". Substitute: "Projectile functions on subsequent impact, or outside zone behind screen (90mm, 155mm)".

Page 10, Table II, Acceptance Criteria, Delay, Delete: "Projectile functions outside zone behind screen (90mm)". Substitute: "Projectile functions on subsequent impact, or outside zone behind screen (90mm, 155mm)."

Custodian:
Army-PA

Preparing Activity
Army-PA

Project No. 1390-A-081

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.