| INCH-POUND |

MIL-C-55514/8D
AMENDMENT 2
19 December 1991
SUPERSEDING
AMENDMENT 1
21 May 1990

MILITARY SPECIFICATION

CAPACITORS, FIXED, METALLIZED PLASTIC DIELECTRIC, DC,
IN NONMETAL CASES, ESTABLISHED RELIABILITY
STYLES CFR12 AND CFR16

This amendment forms a part of MIL-C-55514/8D dated 15 February 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Following voltage rating, add:

"Dielectric withstanding voltage: Two hundred percent of rated voltage for 10-60 seconds".

* Following dissipation factor, add:

"Resistance to soldering heat: In accordance with MIL-C-55514 except that spacers or standoffs of 0.25 inch are required.

Application note: These capacitors are heat sensitive. Vapor phase soldering is not recommended. For applications that require wave soldering that exceeds a five second duration, it is recommended that a spacer or standoff be used".

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Navy - OS
Air Force - 17, 99
DLA - ES

User activities:
Navy - AS, MC
Air Force - 19

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5910-1806)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.