MILITARY SPECIFICATION

POWER CONTROL A

This amendment forms a part of Military Specification MIL-P-60165(MU), dated 11 February 1965.

Paragraph 3.4.7, Table III, Column E, line 3: Delete "2K ± 160" and substitute "3.1K ± 290"; line 5: Delete "1.7K ± 136" and substitute "2.4K ± 240".

Paragraph 3.4.7, Table IV, Column E, line 3: Delete "2.1K ± 168" and substitute "3.2K ± 310"; line 5: Delete "1.8K ± 144" and substitute "2.5K ± 255".

Paragraph 4.5.1.3.2: Delete in its entirety and substitute:

"4.5.1.3.2 Operating.- This test shall be conducted in accordance with the humidity test defined in Procedure III of MIL-F-13926, except that the humidity shall be maintained at 92 to 97 percent for the 24 hour period, and the test shall cease at the end of that period (Method 106 of MIL-STD-202 shall be excluded). Throughout the test period, the board shall be capable of performing the tests of 4.5.2.8.4. In order to demonstrate this capability, the tests of 4.5.2.8.4 shall be performed a minimum of once each 6 hours of the 24 hour period. The final test shall be conducted during the final portion of the 24 hour period. Between tests, the board shall be electrically energized as described in 4.5.2.8.1."

Paragraph 4.5.1.6: Delete in its entirety and substitute:

"4.5.1.6 Salt spray.- This test shall be conducted in accordance with the salt spray test defined in Method 101, Condition B of MIL-STD-202 using a 5 percent salt solution. At the end of the exposure period, salt deposits shall be removed from the board by a gentle wash, not exceeding 30 minutes, in running water not warmer than 100°F, using a soft-hair brush or plastic-bristle brush. The board shall then be air dried in a controlled environment at 72°F ± 5°F and a relative humidity of 30 to 50 percent for a period of 24 hours. The board shall be inspected visually for any physical damage, then tested in accordance with 4.5.2.4."

Paragraph 4.5.2.5.1: Delete paragraph in its entirety and substitute:

"4.5.2.5.1 The ac reference voltage of Table I shall be connected to the indicated pins of Power Control A. (This ac reference voltage shall remain connected during test of paragraphs 4.5.2.5.2, 4.5.2.6.1, 4.5.2.6.2, 4.5.2.7.1 and 4.5.2.7.2). With the input resistors connected (paragraph 4.5.2.4) the most positive portion of the periodic wave voltages at pins 1A, 23A, 25A, 35A, 40B, 48B, and 65A with respect to pin 17B, shall be more negative then zero volt. Upon completion of the test, disconnect the input resistors of Table II, Column A."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:13Z
Check the source to verify that this is the current version before use.

Paragraph 4.5.2.8.2: Delete third and fourth sentences and substitute the following:

"In sequence, each resistance value, Column A shall be continuously varied in the direction specified in Column C until the circuit output voltages at the pins specified in Column D change from minus 11 ± 1.3 vdc to minus 0.15 ± 0.15 vdc."

Paragraph 4.5.2.8.4: Change "4 hours" to "6 hours".

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A060

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:13Z
Check the source to verify that this is the current version before use.