MIL-S-55041/5 (USAF)
AMENDMENT 1
4 September 1979

MILITARY SPECIFICATION

SWITCH, WAVEGUIDE, ELECTROMECHANICAL, FAILSAFE
FREQUENCY RANGE 8.5 - 10.3 GH_z

This amendment is approved for use by the Air Force Acquisition Logistics Division, Directorate of Electronic Support (AFALD/PTS), Wright-Patterson AFB OH 45433, Department of the Air Force, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Add: "Material: Lubricants shall comply,as a minimum, to the requirements of MIL-G-83261."

Delete: "Drop-out voltage: 16 Vdc." and add:"Drop-out voltage: 2 Vdc."

Add: "The test set-ups specified in Figures 2, 3, and 4 of MIL-S-55041 may be modified to reflect current industry practice."

Delete: "Switching time: Switches shall be mounted in the position shown in Figure 3." and add: "Switching time: Switches shall be mounted in the position shown in figure 3; the connector shall point upwards."

PAGE 5

Add: "Explosion: Applicable. The test need not be done with full RF power applied if the switch is designed so that the switching mechanism is completely isolated from the RF energy path."

Custodian:
Air Force - 85

Review Activity:
Air Force - 99

Preparing Activity:
Air Force - 85

(Project 5985-F482)

FSC 5985

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:18Z
Check the source to verify that this is the current version before use.