MIL-S-63280(AR)
AMENDMENT 1
15 April 1988

MILITARY SPECIFICATION

SOLENOID
FOR MACHINE GUN, CALIBER .50: FIXED M85

This Amendment forms a part of Military Specification MIL-S-63280(AR), dated 13 November 1978 and is approved for use within the U.S. Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 8

Table 1, Add, after Temperature Range and after Static Force:

"Epoxy Encapsulation 3.2 4.5.17".

PAGE 24

4.5.12, Line 3, Delete: "202" substitute "213. Test Condition I".

4.5.12, Lines 5 and 6: Delete, "The pulse duration shall be 7 ± 1 milliseconds".

PAGE 25

4.5.13, Line 3: Delete "101. Test condition A" and substitute "110".

Add paragraph:

"4.5.17 Epoxy encapsulation. The solenoid shall be sectioned in half by cutting along section A-A callout on Drawing 7792921. The solenoid shall be examined for adherence and application of epoxy in accordance with Drawing 7792921 and paragraph 3.2 herein."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 5945-A616)

AMSC N/A

FSC 5945

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:31Z
Check the source to verify that this is the current version before use.